

# Specifications

## Eaton 14102A6513



Photo is representative

Eaton Comet 18mm tubular photoelectric sensor, Retroreflective, Forward Viewing, Output ON, 6.6 ft, 300 mA AC/DC at 20-264 Vac/15-30 Vdc, PVC, AC: L1 switched, DC: NPN open collector, 20-264 Vac 50/60 Hz, 15-30 Vdc (NPN)

### General specifications

<b>PRODUCT NAME</b>	Eaton Comet 18mm tubular photoelectric sensor
<b>CATALOG NUMBER</b>	14102A6513
<b>UPC</b>	782113824543
<b>PRODUCT LENGTH/DEPTH</b>	2.2 in
<b>PRODUCT HEIGHT</b>	0.71 in
<b>PRODUCT WIDTH</b>	0.47 in
<b>PRODUCT WEIGHT</b>	0.7 lb
<b>WARRANTY</b>	3 year
<b>CERTIFICATIONS</b>	UL Recognized cUL Recognized
<b>PRODUCT TYPE</b>	Tubular photoelectric sensor



Powering Business Worldwide

## Product specifications

<b>TYPE</b>	Photoelectric Sensor
<b>CONTACT RATING</b>	300 mA AC/DC at 20-264 Vac/15-30 Vdc
<b>CABLE TYPE</b>	Polyvinyl Chloride (PVC)
<b>ENCLOSURE MATERIAL</b>	Polyurethane foam (RIM)
<b>CONTACT CONFIGURATION</b>	AC: L1 switched DC: NPN open collector
<b>SENSOR TYPE</b>	Retroreflective
<b>INPUT VOLTAGE</b>	20-264 Vac at 50/60 Hz, 15-30 Vdc (NPN)
<b>LED INDICATOR</b>	Output ON
<b>PROTECTION</b>	Latching short circuit
<b>CORD LENGTH</b>	79.2 ft
<b>MAXIMUM AC CURRENT</b>	300 mA
<b>MAXIMUM DC CURRENT</b>	300 mA
<b>OPERATING TEMPERATURE - MAX</b>	158 °F
<b>OPERATING TEMPERATURE - MIN</b>	-40 °F
<b>ENVIRONMENTAL RATING</b>	NEMA 1, NEMA 3, NEMA 4, NEMA 4X, NEMA 6, NEMA 12, NEMA 13, IP69K

## Resources

<b>CATALOGS</b>	<a href="#">Product Range Catalog Sensors – products, basic information, applications</a> <a href="#">Sensing Solutions, Photoelectric Sensor, Volume 8, Tab 5</a>
<b>SPECIFICATIONS AND DATASHEETS</b>	<a href="#">Eaton Specification Sheet - 14102A6513</a>

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

