

Specifications



Eaton E57LAL30A2

Eaton Premium+ Inductive Proximity Sensor, E57, 10 mm range, Straight, 30 mm, Shielded, 360° viewable LED, 6.6 ft, 250 mA at 250V, <3% sensing range, PVC, 2-wire AC, NO, 20-250V

General specifications

PRODUCT NAME	Eaton E57 inductive proximity sensor
CATALOG NUMBER	E57LAL30A2
UPC	782113743066
PRODUCT LENGTH/DEPTH	2.73 in
PRODUCT HEIGHT	1.18 in
PRODUCT WIDTH	1.18 in
PRODUCT WEIGHT	0.5 lb
WARRANTY	1 year
COMPLIANCES	CE Marked
CERTIFICATIONS	CSA Certified UL Listed



Powering Business Worldwide

Product specifications

TYPE	Premium+ Inductive Proximity Sensor
CONTACT RATING	250 mA at 250V
ACTUATOR FUNCTION	Shielded
CABLE TYPE	Polyvinyl Chloride (PVC)
ACCURACY	< 3% sensing range
ENCLOSURE MATERIAL	303 stainless steel
CONTACT CONFIGURATION	2-wire AC, NO
SERIES	E57
ENVIRONMENTAL RATING	NEMA 4, NEMA 4X, NEMA 6, NEMA 6P, NEMA 12, NEMA 13, IP67, IP69K
CORD LENGTH	79.2 ft
OPERATING TEMPERATURE - MAX	158 °F
OPERATING TEMPERATURE - MIN	-13 °F
MAXIMUM AC CURRENT	250 mA
INPUT VOLTAGE	20-250 V
LED INDICATOR	360 ° viewable LED

Resources

CATALOGS	Product Range Catalog Sensors – products, basic information, applications Sensing Solutions, Inductive Proximity Sensors, Volume 8, Tab 3
MULTIMEDIA	We make what matters
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - E57LAL30A2

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

