

Specifications

Eaton E59-M12C110D01-D1



Eaton iProx Sensor, E59, Straight, 12 mm, Unshielded, 360° viewable LED, M12, 3-wire, 300 mA at 6-48 Vdc, 4 pin, <3% sensing range, NPN/PNP auto configure, NO, 6-48 Vdc

Photo is representative



General specifications

PRODUCT NAME	Eaton E59 iProx programmable inductive proximity sensor
CATALOG NUMBER	E59-M12C110D01-D1
UPC	782116183272
PRODUCT LENGTH/DEPTH	2.71 in
PRODUCT HEIGHT	0.47 in
PRODUCT WIDTH	0.47 in
PRODUCT WEIGHT	0.1 lb
WARRANTY	1 year
COMPLIANCES	CE Marked
CERTIFICATIONS	UL Listed CSA Certified



Powering Business Worldwide

Product specifications

TYPE	E59
CONTACT RATING	300 mA at 6-48 Vdc
ACTUATOR FUNCTION	Unshielded
ACCURACY	< 3% sensing range
ENCLOSURE MATERIAL	303 stainless steel
CONNECTION	M12
CONTACT CONFIGURATION	NPN/PNP auto configure, NO
SERIES	E59
NUMBER OF WIRES	3
ENVIRONMENTAL RATING	NEMA 4, NEMA 4X, NEMA 6, NEMA 6P, NEMA 12, NEMA 13, IP67, IP69K
TEMPERATURE RATING	-40 to 158 °F
NUMBER OF PINS	4
OPERATING TEMPERATURE - MAX	158 °F
OPERATING TEMPERATURE - MIN	-40 °F
MAXIMUM DC CURRENT	300 mA
INPUT VOLTAGE	6-48 Vdc
SIZE	12 mm
LED INDICATOR	360 ° viewable LED
PROTECTION	Auto reset

Resources

CATALOGS	Sensing Solutions, Inductive Proximity Sensors, Volume 8, Tab 3
MULTIMEDIA	We make what matters
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - E59-M12C110D01-D1

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

