



Sensors > Position Sensors > LVDT Sensors > MINIATURE LIGHTWEIGHT LVDT



Linearity Error (Full Range): $\pm 0.25\%$

Case Material: **Stainless Steel**

Product Shape: **Cylindrical**

Supply Voltage Range: **3 V**

Operating Temperature Range: **-55 – 150 °C [-67 – 302 °F]**

All MINIATURE LIGHTWEIGHT LVDT (0)

Features

Product Type Features

Product Shape	Cylindrical
---------------	-------------

Configuration Features

Electrical Connection	Leads
-----------------------	-------

Electrical Characteristics

Supply Voltage Range	3 V
----------------------	-----

Signal Characteristics

Excitation Frequency	2 – 20 kHz
----------------------	------------

Body Features

Case Material	Stainless Steel
Core Configuration	Separate Core

Dimensions

Product Diameter	9.52 mm[.375 in]
------------------	------------------

Usage Conditions

Operating Temperature Range	-55 – 150 °C[-67 – 302 °F]
-----------------------------	----------------------------

Industry Standards



IP Rating	IP61
-----------	------

Other

Linearity Error (Full Range)	±.25 %
------------------------------	--------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Out of Scope
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE’s information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) ‘Guidance on requirements for substances in articles’(Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of ‘complex object’, the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA “Guidance on requirements for substances in articles” (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts





Also in the Series | MEAS MHR

LVDT Sensors(36)

Customers Also Bought

TE Part #02560409-006
LVDT MHR 100 MC ASSY

TE Part #02560389-000
LVDT HR 050 ASSY

TE Part #MS583730BA01-50
MS5837-30BA01 30BA T&R PRESSURE
SEN

TE Part #754073-000
TMS-RJS-RIBBON-4HT

TE Part #213933-1
CPC,STRAIN RELIEF,SIZE 17

TE Part #321021
PIDG RING (26-22)

TE Part #323064
TERMINAL,SOLIS R HR 12-10 5/16

TE Part #1-1546306-2
12P.374" DR BARRIER STRIP

TE Part #1-1630012-0
HSC150 3K3 5%

TE Part #5787834-2
STD USB TYPE B, VERTICAL, T/H,
NATURAL

Documents

Datasheets & Catalog Pages
Miniature General Purpose AC LVDT
English