



MEAS

TE Internal #: GA10K3435DM010

TE Internal Description: PRO4-OVERMOLDED PROBE

[View on TE.com >](#)

Sensors > Temperature Sensors > NTC Sensors > NTC Probes



NTC Probe Type: HVAC/R

Electrical Connection: Open End

Resistance (at 25°C): 10 kΩ

β-Value(25/85): 3435 K

Accuracy (at T_ref): ± .22 @ 25 °C

Features

Product Type Features

Wire/Cladding Type	24 AWG Stranded Insulated Leads
NTC Probe Type	HVAC/R
Sensor Package	Overmold TPE

Configuration Features

Electrical Connection	Open End
-----------------------	----------

Electrical Characteristics

β-Value(25/85)	3435 K
----------------	--------

Mechanical Attachment

Wire Length	1000 mm[39 in]
-------------	----------------

Usage Conditions

T_ref for Resistance	25 °C[77 °F]
Operating Temperature Range	-40 – 125 °C[-40 – 257 °F]
Resistance (at 25°C)	10 kΩ
Accuracy (at T_ref)	± .22 @ 25 °C
Tolerance Resistance	± 1 %

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)



EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量超出标准 Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JAN 2025 (247) SVHC > Threshold: Pb (20% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



Customers Also Bought



Documents

CAD Files

3D PDF

3D

Customer View Model

[ENG_CVM_CVM_GA10K3435DM010_4.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_GA10K3435DM010_4.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_GA10K3435DM010_4.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[TPE OM NTC Probe 5x20mm](#)

English