



# Alvium

## 1500 C-120c

- AR0135CS CMOS sensor
- ALVIUM image processing
- MIPI CSI-2 interface
- Various hardware options

Hardware option: Open Housing C-Mount

### Alvium 1500 C – Powerful camera modules for embedded vision

#### Revolutionary MIPI CSI-2 camera module

Alvium 1500 C-120 with ON Semi AR0135CS runs 52 frames per second at 1.2 MP resolution.

Alvium 1500 C is a revolutionary MIPI CSI-2 camera optimized for embedded vision applications. The Alvium 1500 C offers the performance and versatility of industrial cameras for the embedded world. Equipped with industrial-grade CMOS sensors from ON Semiconductor, Alvium 1500 C cameras deliver excellent image quality and high frame rates.

The standardized CSI-2 driver ensures quick integration with the flexibility to change camera models easily.

To operate Alvium CSI-2 cameras on your vision system, Allied Vision provides different access modes: - **Direct Register Access (DRA)** to control the cameras via registers for advanced users. - Video4Linux2 Access allows to control the cameras via established V4L2 API and applications like GStreamer and OpenCV. Open-source CSI-2 drivers are available on [GitHub](#) for different boards and system on chips (SoCs).

In addition to lens mount and housing options, see [Customization and OEM Solutions webpage](#) for additional options.

## Specifications

Product code	11499   Frame, Flex, other modular options: Product code and ordering on request
Interface	MIPI CSI-2, up to 4 lanes
Resolution	1280 (H) × 960 (V)
Spectral range	300 to 1100 nm
Sensor	ON Semi AR0135CS
Sensor type	CMOS
Shutter mode	GS (Global shutter)
Sensor size	Type 1/3
Pixel size	3.75 μm × 3.75 μm
Lens mount	C-Mount
Optical Filter	Type IRC 625 colored glass IR cut filter
Max. frame rate at full resolution	52 fps using 1 to 4 lanes, RAW8 (GREY)
ADC	12 Bit
Image buffer (RAM)	256 KByte
Non-volatile memory (Flash)	1024 KByte

### Imaging performance

Imaging performance data is based on the evaluation methods in the EMVA 1288 Release 3.1 standard for characterization of image sensors and cameras. Measurements are typical values for monochrome models measured without optical filter.

Quantum efficiency at 529 nm	69 %
Temporal dark noise	6.1 e <sup>-</sup>
Saturation capacity	9430 e <sup>-</sup>
Dynamic range	63 dB
Absolute sensitivity threshold	6.7 dB

### Output

Bit depth	12-bit
Monochrome pixel formats	CSI-2: RAW8, RAW10, RAW12   FOURCC: GREY, Y10, Y12
YUV color pixel formats	CSI-2: YUV422 8-bit   FOURCC: UYVY

RGB color pixel formats

CSI-2: RGB888 (default) | FOURCC: RGB3

**General purpose inputs/outputs (GPIOs)**

TTL I/Os

2 programmable GPIOs

**Operating conditions/dimensions**

Operating temperature

-20 °C to +65 °C (housing)

Power requirements (DC)

5 VDC over MIPI CSI-2

Power consumption

Typical: 1.1 W


Mass

40 g

Body dimensions (L × W × H in mm)

26 × 29 × 29

**Quantum efficiency**



## Features

### Image control: Auto

- Auto exposure
- Auto gain
- Auto white balance (color models)

### Image control: Other

- Binning (digital)
- Black level
- Color transformation (incl. hue, saturation; color models)
- De-Bayering up to 5×5 (color models)
- DPC (defect pixel correction)
- FPNC (fixed pattern noise correction)
- Gamma
- Reverse X/Y
- ROI (region of interest)

### Camera control

- Acquisition frame rate
- Firmware update in the field
- I/O and trigger control
- Temperature monitoring

Technical drawing

