

1-1564416-1 ✓ ACTIVE

AMP | Heavy Duty Sealed Connector Series

TE Internal #: 1-1564416-1

12 V / 24 V / 48 V, 8 Position, Automotive Housing for Male Terminals, Wire-to-Wire, 4 mm [.157 in] Centerline, Heavy Duty Sealed Connector Series

[View on TE.com >](#)



Automotive Parts > Automotive Connectors > Automotive Housings > Heavy Duty Sealed Connector Series Housings



Nominal Voltage Architecture: 12 V, 24 V, 48 V

Connector & Housing Type: **Housing for Male Terminals**

Number of Positions: **8**

Sealable: **Yes**

Operating Temperature Range: -40 – 140 °C [ -40 – 284 °F ]

[All Heavy Duty Sealed Connector Series Housings \(176\)](#)

## Features

### Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector & Housing Type	Housing for Male Terminals
Sealable	Yes
Primary Locking Feature	On the Terminal
Connector System	Wire-to-Wire
Connector & Contact Terminates To	Wire & Cable

### Configuration Features

Number of Positions	8
Number of Rows	2

### Electrical Characteristics

Operating Voltage	60 VDC
Nominal Voltage Architecture	12 V, 24 V, 48 V

### Body Features

Cable Exit Angle	90 °, 180 °
Primary Product Color	Black



Connector & Keying Code	A
-------------------------	---

### Contact Features

Contact Size	1.6mm
--------------	-------

Contact Type	Tab
--------------	-----

Mating Tab Width	1.6 mm[.063 in]
------------------	-----------------

Contact Current Rating (Max)	10 A
------------------------------	------

### Mechanical Attachment

Terminal Position Assurance	No
-----------------------------	----

Mating Alignment Type	Keyed
-----------------------	-------

Mating Alignment	With
------------------	------

Connector Mounting Type	Cable Mount (Free-Hanging)
-------------------------	----------------------------

### Housing Features

Housing Material	PBT GF30
------------------	----------

Centerline (Pitch)	4 mm[.157 in]
--------------------	---------------

### Dimensions

Row-to-Row Spacing	6.9 mm[.272 in]
--------------------	-----------------

Product Width	47.05 mm[1.852 in]
---------------	--------------------

Product Length	42.5 mm[1.673 in]
----------------	-------------------

Connector Height	39.8 mm[1.567 in]
------------------	-------------------

### Usage Conditions

Operating Temperature Range	-40 – 140 °C[-40 – 284 °F]
-----------------------------	----------------------------

Operating Temperature (Max)	140 °C[284 °F]
-----------------------------	----------------

### Operation/Application

Circuit Application	Power
---------------------	-------

### Industry Standards

IP Rating	IP67
-----------	------

UL Flammability Rating	UL 94V-0
------------------------	----------

### Packaging Features

Packaging Quantity	250
--------------------	-----

Packaging Method	Carton
------------------	--------

### Other



Serviceable	Yes
Connector Position Assurance Capable	No

### Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

### Compatible Parts



TE Part # CAT-H3399-B128  
Heavy Duty Sealed Connector Series Backshells



TE Part # 964972-1  
EINZELLEITERDICHTNG



TE Part # 2112293-1  
PROTECTION CAP, GROUP C, ASSY



TE Part # 2-964269-2  
TAB A 1.6x0.6 CONTACT CF SWS Ag



TE Part # 3-1579018-8  
UNLOCK TOOL



TE Part # 1-1418479-1  
8POS,AMP MCP1.5K,REC. HSG,CODA




TE Part # 1670720-8  
SLIDE,TAB HSG GROUP C



TE Part # CAT-T4827-T273  
TIMER, RECEPTACLE AND TAB



TE Part # 2445670-1  
SLIDE,TAB HSG ASSY,GROUP C



TE Part # CAT-H3399-SL34  
Heavy Duty Sealed Connector Series  
Fixing Slides




TE Part # 1-1564512-1  
8POS,TAB 1.6X0.6,TAB HSG,ASSY


Also in the Series | **Heavy Duty Sealed Connector Series**



Automotive Housings(215)



Automotive Seals & Cavity Plugs(5)



Other Automotive Connector  
Accessories(36)

Customers Also Bought



TE Part #K1167031  
Relay (HVR) 60-311-12-905



TE Part #ADA035N00000151000  
623 BULKHEAD CONNECTOR



TE Part #1-1564526-1  
18POS,TAB 1.6X0.6,TAB HSG,ASSY



TE Part #1670720-5  
SLIDE, TAB HSG GROUP C



TE Part #1718230-2  
1,5MM PIN HSG 5-7 POS ASSY



TE Part #2377789-3  
TAB1.2X0.6,TERMINAL,SWS,REM  
1.2,0.75MM2



TE Part #2484891-1  
TPA TAB HSG,2POS,MCON 1.2



TE Part #2496891-1  
4POS,MCON 1.2,TAB HSG,SLD,COD  
A



## Documents

### Product Drawings

[8POS,TAB 1.6X0.6,TAB HSG,ASSY](#)

English

### CAD Files

Customer View Model

[ENG\\_CVM\\_CVM\\_1-1564416-1\\_H.2d\\_dxf.zip](#)

English

[3D PDF](#)

3D

Customer View Model

[ENG\\_CVM\\_CVM\\_1-1564416-1\\_H.3d\\_igs.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_1-1564416-1\\_H.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

### Datasheets & Catalog Pages

[Heavy Duty Sealed Connector Series](#)

English

[HDSCS Catalog](#)

English

[ICT Terminals and Connectors Catalogue](#)

English

[CONNECTOR SELECTOR](#)

English

### Product Specifications

[Application Specification](#)

English