

2MM-R-S10-VT-02-H-TB

✓ ACTIVE

AMPMODU | AMPMODU 2 mm


TE Internal #: 1-2314878-0

PCB Mount Receptacle, Vertical, Board-to-Board, 10 Position, 2 mm
[.079 in] Centerline, Gold (Au), Through Hole - Solder, Signal, Black,
AMPMODU 2 mm

[View on TE.com >](#)



Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Type: **PCB Mount Receptacle**

Connector System: **Board-to-Board**

Number of Positions: **10**

Number of Rows: **1**

Centerline (Pitch): **2 mm [.079 in]**

Features

Product Type Features

PCB Connector Type	PCB Mount Receptacle
Connector System	Board-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Connector Product Type	Connector Assembly

Configuration Features

Number of Loaded Positions	10
Number of Positions	10
Number of Rows	1
PCB Mount Orientation	Vertical

Electrical Characteristics

Operating Voltage	125 VAC
Dielectric Withstanding Voltage (Max)	650 VAC

Body Features

Connector Profile	Standard
-------------------	----------



Primary Product Color	Black
Contact Features	
Contact Underplating Material	Nickel
Contact Underplating Material Thickness	1.27 µm[50 µin]
PCB Contact Termination Area Plating Material Finish	Matte
Mating Square Post Dimension	.5 mm[.02 in]
PCB Contact Termination Area Plating Material Thickness	3 – 5 µm[118.11 – 196.85 µin]
Contact Layout	Inline
Contact Base Material	Phosphor Bronze
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material Finish	Matte
Contact Mating Area Plating Material Thickness	.76 µm[29.92 µin]
Contact Mating Area Plating Material	Gold (Au)
Contact Type	Socket
Contact Current Rating (Max)	2 A
Termination Features	
Rectangular Termination Post & Tail Width	.4 mm[.016 in]
Rectangular Termination Post & Tail Thickness	.2 mm[.008 in]
Termination Post & Tail Length	2.7 mm[.106 in]
Termination Method to PCB	Through Hole - Solder
Mechanical Attachment	
Connector Mounting Type	Board Mount
Mating Alignment	Without
PCB Mount Alignment	Without
PCB Mount Retention	Without
Housing Features	
Centerline (Pitch)	2 mm[.079 in]
Housing Material	Liquid Crystal Polymer (LCP)
Dimensions	
Connector Width	2 mm[.079 in]
Connector Height	4.5 mm[.18 in]
Connector Length	20 mm[.787 in]



PCB Thickness (Recommended)	1.6 mm[.063 in]
-----------------------------	-----------------

Usage Conditions

Housing Temperature Rating	High
Operating Temperature Range	-40 – 125 °C[-40 – 257 °F]

Operation/Application

Circuit Application	Signal
---------------------	--------

Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

Packaging Features

Packaging Method	Tube
------------------	------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Reflow solder capable to 260°C

Product Compliance Disclaimer





This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>



Compatible Parts

 TE Part # 1-2842104-0 10P,2MM,BRK HDR,SRVT,SMD,0.76AU, TR W/CAP	 TE Part # 1-2355182-0 10P,2MM,BRK HDR,SRVT,2.8,0.76AU, TB	 TE Part # 1-2355184-0 10P,2MM,BRK HDR,SRVT,2.8,0.76AU, TB W/CAP	 TE Part # 1-2355186-0 10P,2MM,BRK HDR,SRVT,2.8,0.76AU, BOX
 TE Part # 1-2842112-0 10P,2MM,BRK HDR,SRRT,2.8,0.76AU, TB	 TE Part # 1-2842116-0 10P,2MM,BRK HDR,SRRT,2.8,0.76AU, TB W/CAP	 TE Part # 1-2842124-0 10P,2MM,BRK HDR,SRRT,2.8,0.76AU, BOX	

Also in the Series | AMPMODU 2 mm

 Board-to-Board Headers & Receptacles(423)	 Connector Contacts(17)	 PCB Headers & Receptacles(432)	 Rectangular Connector Housings(103)
 Standard Rectangular Connectors(202)	 Wire-to-Board Connector Assemblies & Housings(202)	 Wire-to-Board Headers & Receptacles (53)	

Customers Also Bought



TE Part #384600-E
STVC 48 M ABC GGG 4-00 0606 **
247 E007

TE Part #CN9932-000
SBP200143WE2.5

TE Part #823774-000
462A023-3-0

TE Part #3-1825138-7
A208SYCQ04

TE Part #2-2176156-2
TLM 1206 0.5W R022 1% 50PPM 5K RL

TE Part #2-2314820-0
20P,2MM,B-B,REC,DRVT,2.7,0.1AU,TB

TE Part #1-2314876-0
10P,2MM,B-B,REC,SRVT,2.7,0.1AU,TB

TE Part #2314878-6
6P,2MM,B-B,REC,SRVT,2.7,0.76AU,TB

TE Part #928205-3
3P TELFIX BU-GEH

TE Part #928205-4
4P TELFIX BU-GEH

Documents

Product Drawings

10P,2MM,B-B,REC,SRVT,2.7,0.76AU,TB

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-2314878-0_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-2314878-0_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-2314878-0_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages



AMPMODU 2mm BOARD-TO-BOARD RECEPTACLES

English

AMPMODU 2mm interconnection system QRG

English

Product Specifications

Application Specification

English