

1318747-1 ✓ ACTIVE

AMP | 0.64/025 Connector System


TE Internal #: 1318747-1

12 V, 32 Position, Automotive Housing for Female Terminals, Wire-to-Board, 2.2 mm [.08 in] Centerline, Natural, 0.64/025 Connector System

[View on TE.com >](#)



Automotive Parts > Automotive Connectors > Automotive Housings > TH/.025 CONNECTOR SYSTEM, HOUSING



Nominal Voltage Architecture: 12 V

Connector & Housing Type: **Housing for Female Terminals**

Number of Positions: **32**

Sealable: **No**

Operating Temperature Range: -30 – 105 °C [-22 – 221 °F]

[All TH/.025 CONNECTOR SYSTEM, HOUSING \(167\)](#)

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector & Housing Type	Housing for Female Terminals
Sealable	No
Primary Locking Feature	Locking Lance
Connector System	Wire-to-Board
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Positions	32
Number of Rows	2

Electrical Characteristics

Operating Voltage	12 VDC
-------------------	--------



Nominal Voltage Architecture	12 V
------------------------------	------

Body Features

Cable Exit Angle	180 °
Primary Product Color	Natural

Contact Features

Contact Size	.64mm
Contact Type	Receptacle
Mating Tab Width	.64 mm[.02 in]

Mechanical Attachment

Strain Relief	Without
Terminal Position Assurance	No
Mating Alignment Type	Polarization
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	PBT
Centerline (Pitch)	2.2 mm[.08 in]

Dimensions

Row-to-Row Spacing	3 mm[.11 in]
Product Width	21 mm[.82 in]
Product Length	37.4 mm[1.47 in]
Connector Height	15.8 mm[.62 in]

Usage Conditions

Operating Temperature Range	-30 – 105 °C[-22 – 221 °F]
Operating Temperature (Max)	105 °C[221 °F]

Operation/Application

Circuit Application	Signal
---------------------	--------

Industry Standards

UL Flammability Rating	UL 94HB
------------------------	---------

Packaging Features

Packaging Quantity	100
--------------------	-----



Packaging Method	Bag
------------------	-----

Other

Serviceable	Yes
Connector Position Assurance Capable	No

Product Compliance


[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 2326784-2
32POS,TAB0.64X0.64,HDR ASSY,
90DEG,SLDR



TE Part # 2237138-1
32POS,TAB0.64X0.64,HDR ASSY,
90DEG,SMD




TE Part # 2327446-2
52POS,HYBRID,HDR ASSY,90DEG,
SLDR




TE Part # CAT-T319-CH8172
TH/.025 CONNECTOR SYSTEM,
HOUSING




TE Part # 1123343-1
025 REC CONTACT



TE Part # 2322737-1
32POS,TAB0.64X0.64,HDR ASSY,
90DEG,SLDR



TE Part # 2326784-3
32POS,TAB0.64X0.64,HDR ASSY,
90DEG,SLDR




TE Part # 2-2327446-0
52POS,HYBRID,HDR ASSY,90DEG,
SLDR



TE Part # 2326784-4
32POS,TAB0.64X0.64,HDR ASSY,
90DEG,SLDR



TE Part # CAT-SIGH262
Signal Header




TE Part # 2326784-1
32POS,TAB0.64X0.64,HDR ASSY,
90DEG,SLDR



TE Part # 1318745-4
025 32 POS CAP ASSY H RND AU

Also in the Series | **0.64/025 Connector System**



Automotive Connector Locks &
Position Assurance(1)



Automotive Housings(173)



Automotive Seals & Cavity Plugs(2)



Automotive Signal & Power Connector
Housings(173)



Other Automotive Connector
Accessories(4)

Customers Also Bought



Documents

Product Drawings

025 ECU PLUG HSG ASSY 32P

Japanese

CAD Files

3D PDF

English

Customer View Model

[ENG_CVM_1318747-1_A1.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_1318747-1_A1.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_1318747-1_A1.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Crimping of 025 Receptacle Contact

Japanese

Application Specification

Japanese

Instruction Sheets

Instruction Sheet (non U.S.)

English



[Instruction Sheet \(non U.S.\)](#)

English

[Instruction Sheet \(non U.S.\)](#)

Japanese