

174515-6 ✓ ACTIVE

MULTILOCK | Multilock Connector System

TE Internal #: 174515-6

12 V, 22 Position, Automotive Housing for Female Terminals, Wire-to-Board, 3 mm / 3.5 mm [.11 in / .13 in] Centerline, Multilock Connector System

[View on TE.com >](#)



Automotive Parts > Automotive Connectors > Automotive Housings > Multilock Connector Housing



Nominal Voltage Architecture: 12 V

Connector & Housing Type: **Housing for Female Terminals**

Number of Positions: 22

Sealable: No

Operating Temperature Range: -30 – 105 °C [ -22 – 221 °F ]

[All Multilock Connector Housing \(127\)](#)

## Features

### Product Type Features

Mixed & Hybrid Connector	Yes
Connector Shape	Rectangular
Connector & Housing Type	Housing for Female Terminals
Sealable	No
Primary Locking Feature	Clean Body
Connector System	Wire-to-Board
Connector & Contact Terminates To	Wire & Cable

### Configuration Features

Number of Positions	22
Number of Rows	2

### Electrical Characteristics

Operating Voltage	12 VDC
-------------------	--------

Nominal Voltage Architecture	12 V
------------------------------	------

### Body Features

Cable Exit Angle	180 °
Primary Product Color	Gray

### Contact Features

Contact Size	1.8mm, 1mm
Contact Type	Receptacle
Mating Tab Width	1 mm, 1.8 mm [.04 in] [.071 in]

### Mechanical Attachment

Strain Relief	Without
Terminal Position Assurance	No
Mating Alignment Type	Polarization
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

### Housing Features

Housing Material	PBT
Centerline (Pitch)	3 mm, 3.5 mm [.11 in] [.13 in]

### Dimensions

Row-to-Row Spacing	5.2 mm [.205 in]
Product Width	21 mm [.827 in]
Product Length	36.1 mm [1.421 in]
Connector Height	28 mm [1.102 in]

### Usage Conditions

Operating Temperature Range	-30 – 105 °C [-22 – 221 °F]
Operating Temperature (Max)	105 °C [221 °F]

### Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

### Industry Standards

UL Flammability Rating	UL 94HB
------------------------	---------

### Packaging Features

Packaging Quantity	50
--------------------	----



Packaging Method	Tray
------------------	------

### Other

Serviceable	Yes
Connector Position Assurance Capable	No

## Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability



#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

## Compatible Parts



Also in the Series | **Multilock Connector System**



Customers Also Bought



## Documents

### Product Drawings

[HYBRID I/O CONN PLUG HSG 22P](#)

Japanese

### CAD Files

[3D PDF](#)

English

Customer View Model

[ENG\\_CVM\\_174515-6\\_D.2d\\_dxf.zip](#)

English

Customer View Model

[ENG\\_CVM\\_174515-6\\_D.3d\\_igs.zip](#)

English

Customer View Model

[ENG\\_CVM\\_174515-6\\_D.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

### Datasheets & Catalog Pages



## MULTILOCK Connector System

English

---

### Product Specifications

#### Product Specification

English

---

### Instruction Sheets

#### HYBRID I/O CONNECTOR

English

#### HYBRID I/O CONNECTOR

English

#### HYBRID I/O CONNECTOR

English

#### HYBRID I/O CONNECTOR

English