

2-967616-1 ✓ ACTIVE



MQS

TE Internal #: 2-967616-1

12 V / 24 V / 48 V, 6 Position, Automotive Housing for Female
Terminals, Wire-to-Board / Wire-to-Wire, 4 mm [.157 in] Centerline,
Sealable, Gray

[View on TE.com >](#)

Automotive Parts > Automotive Connectors > Automotive Housings > MQS, CONNECTOR HOUSING



Nominal Voltage Architecture: 12 V, 24 V, 48 V

Connector & Housing Type: **Housing for Female Terminals**

Number of Positions: **6**

Sealable: **Yes**

Operating Temperature Range: -40 – 120 °C [-40 – 248 °F]

[All MQS, CONNECTOR HOUSING \(339\)](#)

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector & Housing Type	Housing for Female Terminals
Sealable	Yes
Primary Locking Feature	Locking Lance
Connector System	Wire-to-Board, Wire-to-Wire
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Positions	6
Number of Rows	2

Electrical Characteristics

Operating Voltage	50 VDC
-------------------	--------



Nominal Voltage Architecture	12 V, 24 V, 48 V
------------------------------	------------------

Body Features

Cable Exit Angle	180 °
Primary Product Color	Gray
Connector & Keying Code	B

Contact Features

Contact Size	.64mm
Contact Type	Receptacle
Mating Tab Width	.64 mm[.025 in]
Contact Current Rating (Max)	7.5 A

Mechanical Attachment

Strain Relief	Without
Terminal Position Assurance	No
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	PBT GF15
Centerline (Pitch)	4 mm[.157 in]

Dimensions

Row-to-Row Spacing	3.5 mm[.138 in]
Product Width	24 mm[.945 in]
Product Length	30.4 mm[1.19 in]
Connector Height	17 mm[.67 in]

Usage Conditions

Operating Temperature Range	-40 – 120 °C[-40 – 248 °F]
Operating Temperature (Max)	120 °C[248 °F]

Operation/Application

Circuit Application	Signal
---------------------	--------

Industry Standards

IP Rating	IPX9K
-----------	-------

Packaging Features



Packaging Quantity	1100
--------------------	------

Packaging Method	Bag
------------------	-----

Other

Serviceable	Yes
-------------	-----

Connector Position Assurance Capable	No
--------------------------------------	----

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
------------------------------	-----------

EU ELV Directive 2000/53/EC	Compliant
-----------------------------	-----------

China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
---	---

EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
--	--


Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
-----------------	--

Solder Process Capability	Not applicable for solder process capability
---------------------------	--

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 967067-1
MQS SGL WIRE SEAL



TE Part # 1-967587-3
6POS MQS TAB SEALED COD A




TE Part # 1241637-1
6P,TAB0.63X0.63,HDR,90DEG,SLDR, SN




TE Part # CAT-M8793-T273
MQS, RECEPTACLE AND TAB



TE Part # 967067-2
MQS EINZELLEITDICHT




TE Part # 968303-1
MQS PROTECTIV COVER FOR SOCKET HSG 6POS



TE Part # 967097-1
2,5MM DICHTUNG



TE Part # 2-968304-1
MQS SOCK HSG SWS 6P



TE Part # 968302-1
MQS 2.KONTAKTSICHG



TE Part # 1897096-2
WIRE COVER FOR MQS SLD 6P CONN'R



TE Part # 967056-1
MQS BLINDSTOPFEN4MM

Customers Also Bought



TE Part #928909-5
PL 250 REC TERMINAL 24-20 AWG PTPB



TE Part #5-1393304-7
V23134M0052G242-EV-CBOX



TE Part #4-1393560-3
V42254A4000D 9-SUB D BUEGEL



TE Part #CAT-SU763-H342
SUPERSEAL 1.0 Connector Headers



TE Part #2389577-1
BACKSHELL,CONN KIT



TE Part #927849-2
STC REC 6.3 Contact SRC Sn



TE Part #2098190-1
EVC500, RELAY, SPSTN

Documents



Product Drawings

6POS MQS REC SEALED COD B

English

CAD Files

Customer View Model

[ENG_CVM_CVM_2-967616-1_F.2d_dxf.zip](#)

English

3D PDF

3D

Customer View Model

[ENG_CVM_CVM_2-967616-1_F.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_2-967616-1_F.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

SHROUDED CONNECTION, 6 POS.

English

Application Specification

English

Application Specification

English

CONNEXIONS ETANCHES 2,3,4,6,8 ET 12 POSITIONS Micro Quadlock System Micro Twinleaf

English

Application Specification

English