

776535-1 ✓ ACTIVE

AMP | AMPSEAL 16

TE Internal #: 776535-1

12 V / 240 V / 48 V, 3 Position, Automotive Cap, Wire-to-Wire, 4.5 mm [.177 in] Centerline, Sealable, Black, Wire & Cable, AMPSEAL 16

[View on TE.com >](#)



Automotive Parts > Automotive Connectors > Automotive Housings > AMPSEAL 16 Housings



Nominal Voltage Architecture: 12 V, 24 V, 48 V, 240 V

Connector & Housing Type: Cap

Number of Positions: 3

Sealable: Yes

Operating Temperature Range: -40 – 125 °C [-40 – 257 °F]

[All AMPSEAL 16 Housings \(224\)](#)

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector & Housing Type	Cap
Sealable	Yes
Primary Locking Feature	Integrated in Housing
Connector System	Wire-to-Wire
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Positions	3
Number of Rows	1

Electrical Characteristics

Operating Voltage	250 VDC
Nominal Voltage Architecture	12 V, 24 V, 48 V, 240 V

Body Features

Cable Exit Angle	180 °
Primary Product Color	Black



Connector & Keying Code	A
-------------------------	---

Contact Features

Contact Size	1.5mm
--------------	-------

Contact Type	Pin
--------------	-----

Mating Pin Diameter	1.5 mm[.06 in]
---------------------	----------------

Mechanical Attachment

Strain Relief	Add By Accessory
---------------	------------------

Terminal Position Assurance	Yes
-----------------------------	-----

Mating Alignment Type	Keyed
-----------------------	-------

Mating Alignment	With
------------------	------

Connector Mounting Type	Cable Mount (Free-Hanging)
-------------------------	----------------------------

Housing Features

Housing Material	PBT GF
------------------	--------

Centerline (Pitch)	4.5 mm[.177 in]
--------------------	-----------------

Dimensions

Product Width	47.55 mm[1.872 in]
---------------	--------------------

Product Length	24.1 mm[.949 in]
----------------	------------------

Connector Height	19.15 mm[.754 in]
------------------	-------------------

Usage Conditions

Operating Temperature Range	-40 – 125 °C[-40 – 257 °F]
-----------------------------	----------------------------

Operating Temperature (Max)	125 °C[257 °F]
-----------------------------	----------------

Industry Standards

IP Rating	IP67
-----------	------

UL Flammability Rating	UL 94HB
------------------------	---------

Packaging Features

Packaging Quantity	1
--------------------	---

Packaging Method	Bag
------------------	-----

Other

Serviceable	Yes
-------------	-----

Connector Position Assurance Capable	Yes
--------------------------------------	-----

Product Compliance




[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) SVHC > Threshold: Dodecamethylcyclohexasiloxane (D6) (.5% in 27519261136) Decamethylcyclopentasiloxane (D5) (.5% in 27519261136) Octamethylcyclotetrasiloxane (D4) (.5% in 27519261136) Article Safe Usage Statements: Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 <p>TE Part # 2448820-2 AS16,BLIND PLUG ASSY,ST,03P</p>	 <p>TE Part # 2292861-3 AS16,CAP BACKSHELL KIT,ST,03P,NC08</p>	 <p>TE Part # 2203728-1 AS16; 2p Wire Seal; Reduced Diameter</p>	 <p>TE Part # 2035366-4 Backshell,AS16,3P,90Deg,NC12,LP,Plug</p>
--	--	---	---



Also in the Series | **AMPSEAL 16**



Customers Also Bought



TE Part #CAT-H3930-CH8172
DEUTSCH HD30 Housings



TE Part #T1926030116-000
H3APR-TGC-M16



TE Part #T2020082101-000
HD-008-M



TE Part #CAT-AM7801-CH8172
AMPSEAL 16 Housings



TE Part #2-1623707-7
TRIMMABLE 0805 0/-10% 120K



TE Part #CAT-AM7801-T273
Contacts: Size 16, 13A

Documents

Product Drawings

[AS16,CAP ASSY,ST,03P,E SEAL,CODE A](#)

English

CAD Files

[3D PDF](#)

3D

Customer View Model

[ENG_CVM_CVM_776535-1_C_c-776535-1-c.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_776535-1_C_c-776535-1-c.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_776535-1_C_c-776535-1-c.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[ICT Terminals and Connectors Catalogue](#)

English

[CONNECTOR SELECTOR](#)

English

Product Specifications

[Application Specification](#)

English

776535-1

12 V / 240 V / 48 V, 3 Position, Automotive Cap, Wire-to-Wire, 4.5 mm [.177 in]
Centerline, Sealable, Black, Wire & Cable, AMPSEAL 16



Instruction Sheets

Instruction Sheet (U.S.)

English