



Automotive Parts > Automotive Connectors > Automotive Housings > AMP Unsealed Connector Housing



Nominal Voltage Architecture: 12 V, 24 V
Connector & Housing Type: Housing for Female Terminals
Number of Positions: 18
Sealable: No
Operating Temperature Range: -40 – 120 °C [-40 – 248 °F]

[All AMP Unsealed Connector Housing \(109\)](#)

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector & Housing Type	Housing for Female Terminals
Sealable	No
Primary Locking Feature	Integrated in Housing
Connector System	Wire-to-Wire
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Positions	18
Number of Rows	3

Electrical Characteristics

Operating Voltage	28 VDC
-------------------	--------



Nominal Voltage Architecture	12 V, 24 V
------------------------------	------------

Body Features

Cable Exit Angle	180 °
Primary Product Color	Gray
Connector & Keying Code	A

Contact Features

Contact Size	2.8mm
Contact Type	Receptacle
Mating Tab Width	2.8 mm[.11 in]

Mechanical Attachment

Strain Relief	Without
Terminal Position Assurance	No
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	PBT GF
Centerline (Pitch)	5 mm[.197 in]

Dimensions

Row-to-Row Spacing	5.5 mm[.217 in]
Product Width	36 mm[1.417 in]
Product Length	36 mm[1.417 in]
Connector Height	24 mm[.945 in]

Usage Conditions

Operating Temperature Range	-40 – 120 °C[-40 – 248 °F]
Operating Temperature (Max)	120 °C[248 °F]

Operation/Application

Circuit Application	Power
---------------------	-------

Packaging Features

Packaging Quantity	1000
Packaging Method	Box

Other



Serviceable	No
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 967634-1
2. RETAINER FOR 18POS



TE Part # 966140-1
MESSERLEISTE 18P



TE Part # CAT-HPCH5372
High Pin Count Header



TE Part # CAT-LMPH9507
Low & Medium Power Header



TE Part # CAT-AM705-T273
AMP MCP, RECEPTACLE AND TAB




TE Part # 1-967629-1
FLA-STE-GEH2,8 18P



TE Part # CAT-T4827-CH8172
Timer Connector Housing

Also in the Series | AMP MCP 2.8



Automotive Connector Locks & Position Assurance(5)



Automotive Housings(237)



Automotive Seals & Cavity Plugs(6)




Automotive Signal & Power Connector Housings(83)



Other Automotive Connector Accessories(4)

Also in the Series | AMP MCP Connector System



Automotive Connector Locks & Position Assurance(5)



Automotive Housings(237)



Automotive Seals & Cavity Plugs(6)




Automotive Signal & Power Connector Housings(83)




Other Automotive Connector Accessories(4)


Customers Also Bought



TE Part #350200-1
.140 DIA SOK 14-10 PTPBR



TE Part #350201-1
.140 DIA PIN 14-10 PTPBR



TE Part #880685-2
.140 DIA PIN



TE Part #CAT-T4827-CH8172
Timer Connector Housing



TE Part #CAT-AM705-CH8173
AMP Unsealed Connector Housing

Documents

Product Drawings

MCP2.8 GEH 18P

English

MCP2.8 GEH 18P

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_8-968974-1_F.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_8-968974-1_F.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_8-968974-1_F.3d_stp.zip



English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English