

Ordering Information	
Part Number	Contact Area Plating Finish
K85X-AA-15S	Gold Flash (standard)
K85X-AA-15S-15	15u" Gold (15 option)
K85X-AA-15S-30	30u" Gold (30 option)

Material and Finish

Shell: Steel Material, Nickel Plated

Insert: PBT Thermoplastic,
Black Color, 30%
Glass Filled, UL 94V-0 Rated

Contact Material:
Socket - brass

Contact Plating:
Standard:
gold flash over nickel on
contact area, tin over
nickel on soldercups
-15 Option:
15u" gold over nickel on
contact area, tin over
nickel on soldercups
-30 Option:
30u" gold over nickel on
contact area, tin over
nickel on soldercups

Electrical Specifications

Contact Current Rating: 2A

Rated Voltage: 30V RMS

Dielectric Withstanding Voltage:
1000V (rms) AC for 1 minute

Insulation Resistance:
more than 1000 Megohm
at 500V DC

Contact Resistance:
13 milliohm max.

Operating Temperature
-55°C to +105°C

Tolerances

X.X ± 0.25
X.XX ± 0.15
Unless Stated
Otherwise




REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A1	04/10/07	New Drawing	E. Canoy	H. MA	E. Canoy	04/09/2007
A2	03/18/08	ECO #07-052	S. Vien	H. MA		
A3	12/31/17	ECO #17-030	J. Elbanna	C. Furumasu		
A4	09/15/25	ECO #25-061	K.Wang	C.Kelleher		

K85X-AA-15S

Vertical Soldercup Mount D-Sub

15 Pin Female, RoHS Compliant



UNITS
mm