



Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Type: **PCB Mount Hermaphroditic Connector**

Connector System: **Board-to-Board**

Number of Positions: **30**

Number of Rows: **2**

Centerline (Pitch): **.5 mm [.02 in]**

Features

Product Type Features

| | |
|-----------------------------------|------------------------------------|
| PCB Connector Type | PCB Mount Hermaphroditic Connector |
| Connector System | Board-to-Board |
| Sealable | No |
| Connector & Contact Terminates To | Printed Circuit Board |
| Connector Product Type | Connector Assembly |

Configuration Features

| | |
|------------------------------|----------|
| Number of Positions | 30 |
| Number of Rows | 2 |
| PCB Mount Orientation | Vertical |
| Board-to-Board Configuration | Parallel |

Body Features

| | |
|-----------------------|-------|
| Primary Product Color | Black |
|-----------------------|-------|

Contact Features

| | |
|--------------------------------------|----------------|
| Contact Thickness | 15 μ m |
| Contact Mating Area Plating Material | Gold (Au) |
| Contact Type | Hermaphroditic |
| Contact Current Rating (Max) | .5 A |

Termination Features

| | |
|---|-----------------|
| Rectangular Termination Post & Tail Width | .2 mm[.008 in] |
| Rectangular Termination Post & Tail Thickness | .15 mm[.005 in] |
| Termination Method to PCB | Surface Mount |

Mechanical Attachment

| | |
|--------------------------|----------------|
| PCB Mount Retention Type | Solder Peg |
| PCB Mount Alignment Type | Locating Posts |
| Mating Alignment Type | Polarization |
| Connector Mounting Type | Board Mount |
| Mating Alignment | With |
| PCB Mount Alignment | Without |
| PCB Mount Retention | Without |

Housing Features

| | |
|--------------------|---------------|
| Centerline (Pitch) | .5 mm[.02 in] |
| Housing Material | Thermoplastic |

Dimensions

| | |
|--------------|---------------|
| Stack Height | 4 mm[.157 in] |
|--------------|---------------|

Usage Conditions

| | |
|-----------------------------|----------------------------|
| Operating Temperature Range | -40 – 125 °C[-40 – 257 °F] |
|-----------------------------|----------------------------|

Operation/Application

| | |
|--------------------------|----------------------|
| Assembly Process Feature | Pick and Place Cover |
| Circuit Application | Signal |

Industry Standards

| | |
|------------------------|----------|
| UL Flammability Rating | UL 94V-0 |
|------------------------|----------|

Packaging Features

| | |
|------------------|-------------|
| Packaging Method | Tape & Reel |
|------------------|-------------|

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

| | |
|---|---|
| EU RoHS Directive 2011/65/EU | Compliant |
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | 有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold |



EU REACH Regulation (EC) No. 1907/2006

Current ECHA Candidate List: JUNE 2025 (250)

Candidate List Declared Against: JUNE 2024 (241)

Does not contain REACH SVHC

Halogen Content

Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free


Solder Process Capability

Wave solder capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 2291283-1
0.5MM FPH BTB, 4H/30POS/15U/TR/WOB/B



TE Part # 2291283-2
0.5MM FPH BTB, 4H/30POS/15U/TR/WOB/B


Customers Also Bought



TE Part #5103308-2
A/L LOW PRO HDR 14P VERT BLACK



TE Part #2199070-4
0.5MM FPH BTB, 4H/24POS/15U/TR/WOB



TE Part #2291283-1
0.5MM FPH BTB, 4H/30POS/15U/TR/WOB/B

Documents

Product Drawings

0.5MM FPH BTB, 4H/30POS/15U/TR/WOB/B



English

CAD Files

3D PDF

3D

Customer View Model

[ENG_CVM_CVM_2291283-2_A.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_2291283-2_A.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_2291283-2_A.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[1-1773721-3_0.5mm_FinePitch_Hermahroditic_BtB_Connector_flyer](#)

English

Product Specifications

[Application Specification](#)

English