

## DIN-Power shell housing C



Image is for illustration purposes only. Please refer to product description.

Part number	09 05 048 0501
Specification	DIN-Power shell housing C
HARTING eCatalogue	<a href="https://harting.com/09050480501">https://harting.com/09050480501</a>

### Identification

Category	Accessories
Series	DIN 41612
Identification	Type E har-bus® 64
Type of accessory	Shell housing
Description of the accessory	20 mm

### Version

Version	Top/side entry
Number of cable entries	4
Cable entry	4x
Strain relief	With cable tie
Locking type	Locking levers or locking screws
2 parts	Yes
Separable	Yes

### Technical characteristics

Limiting temperature	-40 ... +125 °C
Degree of protection acc. to IEC 60529	IP20
Isolation group	IIIa (175 ≤ CTI < 400)

### Material properties

Colour (hood/housing)	RAL 7032 (pebble grey)
-----------------------	------------------------



**Pushing Performance**  
Since 1945

## Material properties

Material (accessories)	Thermoplastic Fibre-glass reinforced
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel

## Specifications and approvals

Railway classification	F1/I2 acc. to NFF 16-101/102
------------------------	------------------------------

## Commercial data

Packaging size	10
Net weight	45.53 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140008793
eCl@ss	27440292 Connector component (accessories)
ETIM	EC002943
UNSPSC 24.0	39121400