

A black, cylindrical, weatherproof connector with a yellow band near one end, shown against a white background.

## NECTOR T PLUGGABLE CONNECTORS

TE Connectivity (TE)'s NECTOR T pluggable connectors provide an easy-to-use, pluggable power-distribution connector-cabling system, suited for moist and wet environments (sealed IP68). NECTOR T pluggable connectors offer a complete solution including 3-way and 4-way splitters and panel mount connectors, so power-splitting is fast and easy.

Installation is quick and flexible with both crimp and screw type terminals. These sealed pluggable connectors are used specifically and offer a new solution to high humidity and harsh environment applications like garden lighting, horticultural lighting, building facade lighting and other outdoor installations.

### BENEFITS

- Easy to install and repair with standard tools
- Helps provide flexibility and material cost savings during installation by reducing waste
- Allows pre-terminated cables with lower labor / installation costs
- Protects against UV (sun light), rain and dust for outdoors use without functional failure due to harsh environment helping provide long-life and reliability
- Provides protection to the mating interface in an unmated / open condition
- Significantly reduces mis-mating and potential re-work

## NECTOR T PLUGGABLE CONNECTORS

### APPLICATIONS

- Horticultural lighting installations
- Farm lights
- Grow light connections
- Sealed power distribution

### MECHANICAL

- **Cable gland range:**
  - **Range 1:** Ø7 to Ø11 mm
  - **Range 2:** Ø11 to Ø15 mm
- Polarizing key A & B
- **Crimp terminal range:**
  - 18 AWG
  - 1.5 mm<sup>2</sup> or 16 AWG
  - 2.5 mm<sup>2</sup> or 14 AWG
  - 4.0 mm<sup>2</sup> or 12 AWG
- **IP rated:** IP67, IP68

### ELECTRICAL

- 600 Vac (UL)
- 500 Vac (IEC)
- 7 Amp to 25 Amp

### STANDARD

- UL 2238
- IEC 61535-1

### MATERIALS

- PBT + PC resin with UL 94 VO & UV F1 rating
- Contacts high performance copper alloy

### SPECIFICATIONS

- **Application Spec:** [114-133123](#)
- **Product Spec:** [108-133123](#)
- 18 AWG and 16 AWG tin stranded wire is UL approved for use with screw termination

### SCREW TERMINATION

| Product                                                                                                                                                                                            | Connector                             | Part no.                    | Description                                  | Polarizing key |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------|-----------------------------|----------------------------------------------|----------------|
| In-line free hanging<br><br> | Socket connector<br>Screw termination | <a href="#">2379237-1</a>   | Socket connector, cable range 11 mm to 15 mm | A              |
|                                                                                                                                                                                                    |                                       | <a href="#">2379237-2</a>   |                                              | B              |
|                                                                                                                                                                                                    |                                       | <a href="#">1-2379237-1</a> | Socket connector, cable range 7 mm to 11 mm  | A              |
|                                                                                                                                                                                                    |                                       | <a href="#">1-2379237-2</a> |                                              | B              |
|                                                                                                                                                                                                    | Pin connector<br>Screw termination    | <a href="#">2379238-1</a>   | Pin connector, cable range 11 mm to 15 mm    | A              |
|                                                                                                                                                                                                    |                                       | <a href="#">2379238-2</a>   |                                              | B              |
|                                                                                                                                                                                                    |                                       | <a href="#">1-2379238-1</a> | Pin connector, cable range 7 mm to 11 mm     | A              |
|                                                                                                                                                                                                    |                                       | <a href="#">1-2379238-2</a> |                                              | B              |
| Panel mount<br><br>          | Socket connector<br>Screw termination | <a href="#">2359422-1</a>   | Socket connector, screw type                 | A              |
|                                                                                                                                                                                                    |                                       | <a href="#">2359422-2</a>   |                                              | B              |
|                                                                                                                                                                                                    | Pin connector<br>Screw termination    | <a href="#">2359518-1</a>   | Pin connector, screw type                    | A              |
|                                                                                                                                                                                                    |                                       | <a href="#">2359518-2</a>   |                                              | B              |

**Note:** Only polarizing key A is considered for initial product launch.  
Key B is available if there is specific customer request.

## NECTOR T PLUGGABLE CONNECTORS

### CRIMP TERMINATION

| Product                                                                                                                                                                                                   | Connector type                        | Part no.                    | Description                                    | Polarizing key |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------|-----------------------------|------------------------------------------------|----------------|
| In-line<br>free hanging<br><br><br><br> | Socket connector<br>Crimp termination | <a href="#">2379239-1</a>   | Socket connector, cable range 11 mm to 15 mm   | A              |
|                                                                                                                                                                                                           |                                       | <a href="#">2379239-2</a>   |                                                | B              |
|                                                                                                                                                                                                           |                                       | <a href="#">1-2379239-1</a> | Socket connector, cable range 7 mm to 11 mm    | A              |
|                                                                                                                                                                                                           |                                       | <a href="#">1-2379239-2</a> |                                                | B              |
|                                                                                                                                                                                                           | Pin connector<br>Crimp termination    | <a href="#">2379240-1</a>   | Pin connector, cable range 11 mm to 15 mm      | A              |
|                                                                                                                                                                                                           |                                       | <a href="#">2379240-2</a>   |                                                | B              |
|                                                                                                                                                                                                           |                                       | <a href="#">1-2379240-1</a> | Pin connector, cable range 7 mm to 11 mm       | A              |
|                                                                                                                                                                                                           |                                       | <a href="#">1-2379240-2</a> |                                                | B              |
| Panel mount<br><br><br><br>             | Socket connector<br>Crimp termination | <a href="#">1-2359422-1</a> | Socket connector, crimp type                   | A              |
|                                                                                                                                                                                                           |                                       | <a href="#">1-2359422-2</a> |                                                | B              |
|                                                                                                                                                                                                           | Pin connector<br>Crimp termination    | <a href="#">1-2359518-1</a> | Pin connector, crimp type                      | A              |
|                                                                                                                                                                                                           |                                       | <a href="#">1-2359518-2</a> |                                                | B              |
| Contacts<br><br>                                                                                                       | Socket contact                        | <a href="#">2359527-1</a>   | Wire termination 1.5 mm to 2.5 mm <sup>2</sup> | -              |
|                                                                                                                                                                                                           |                                       | <a href="#">2359527-2</a>   | Wire termination 4.0 mm <sup>2</sup>           | -              |
|                                                                                                                                                                                                           |                                       | <a href="#">2359527-3</a>   | Wire termination 18 AWG                        | -              |
|                                                                                                                                                                                                           | Pin contact                           | <a href="#">2359528-1</a>   | Wire termination 1.5 mm to 2.5 mm <sup>2</sup> | -              |
|                                                                                                                                                                                                           |                                       | <a href="#">2359528-2</a>   | Wire termination 4.0 mm <sup>2</sup>           | -              |
|                                                                                                                                                                                                           |                                       | <a href="#">2359528-3</a>   | Wire termination 18 AWG                        | -              |

**Note:** Only polarizing key A is considered for initial product launch. Key B is available if there is specific customer request.  
Contacts sold loose. Customer to choose based on their requirements.

### SPLITTERS

| Product                                                                                                   | Part no.                  | Description    | Polarizing key |
|-----------------------------------------------------------------------------------------------------------|---------------------------|----------------|----------------|
| T-splitter<br><br>     | <a href="#">2359420-1</a> | T splitter     | A              |
|                                                                                                           | <a href="#">2359420-2</a> |                | B              |
| Multi-splitter<br><br> | <a href="#">2359421-1</a> | Multi splitter | A              |
|                                                                                                           | <a href="#">2359421-2</a> |                | B              |

**Note:** Only polarizing key A is considered for initial product launch. Key B is available if there is specific customer request.

## NECTOR T PLUGGABLE CONNECTORS

### ACCESSORIES

| Product                                                                                                | Part no.                  | Description     |
|--------------------------------------------------------------------------------------------------------|---------------------------|-----------------|
| Socket safety cap<br> | <a href="#">2366866-1</a> | Socket dust cap |
| Pin safety cap<br>    | <a href="#">2363703-1</a> | Pin dust cap    |

**Note:** Parts sold separately as an accessory.

**CONTACT OUR PRODUCT TEAM ►**

**[te.com/nector-t-connector](https://te.com/nector-t-connector)**

TE Connectivity, TE, TE connectivity (logo), NECTOR and EVERY CONNECTION COUNTS are trademarks owned or licensed by the TE Connectivity plc family of companies. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information in this document, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any changes to the information contained herein without prior notice. TE Connectivity assumes only those obligations set forth in the terms and conditions for this product and shall in no event be liable for any incidental, indirect, or consequential damages arising out of the sale, resale, use, or misapplication of the product. TE expressly disclaims any implied warranties with respect to the information contained herein, including, but not limited to, implied warranties of merchantability or fitness for a particular purpose. Dimensions, specifications and/or information contained herein are for reference purposes only and are subject to change without notice. Consult TE for the latest dimensions, specifications and/or information. Users of TE Connectivity products must make their own assessment as to whether the respective product is suitable for the respective desired application.

© 2025 TE Connectivity. All Rights Reserved

05/25