

Standard



*Image for illustrative purpose only*

## Summary

[Request a quote](#)

---

[Customer Drawing](#)

---

Jacket cable outside diameter [mm]	3.00 - 3.40 mm
------------------------------------	----------------

---

Size	0B
------	----

---

Series	B - Indoor keyed
--------	------------------

[https://www.lemo.com/int\\_en/solutions/originals/b-indoor-keyed/gma-0b-030-dg.html](https://www.lemo.com/int_en/solutions/originals/b-indoor-keyed/gma-0b-030-dg.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

# Technical details

## Form & Material

---

Shell style / Model id	GMA - Bend relief Grey
Housing material	Thermoplastic polyurethane
Keying	No keying
Colour	Grey
Weight	0.42 g

---

## Environment

---

Technical domain	Audio Video, Energy and Industrial, Medical, Semiconductor, Specialties and Other, Test and Measurement, Transportation, Aerospace and UAV
Environmental sealing (IP rating)	No IP rating
Temperature range	-40°C / +80°C

---

## Cable fixation

---

Jacket cable outside diameter [mm]	3.00 - 3.40 mm
------------------------------------	----------------

---

[https://www.lemo.com/int\\_en/solutions/originals/b-indoor-keyed/gma-0b-030-dg.html](https://www.lemo.com/int_en/solutions/originals/b-indoor-keyed/gma-0b-030-dg.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.