

Standard



*Image for illustrative purpose only*

## Summary

[Request a quote](#)

---

[Customer Drawing](#)

---

|                                    |                |
|------------------------------------|----------------|
| Jacket cable outside diameter [mm] | 4.50 - 5.20 mm |
|------------------------------------|----------------|

---

|      |    |
|------|----|
| Size | 0B |
|------|----|

---

|        |                  |
|--------|------------------|
| Series | B - Indoor keyed |
|--------|------------------|

[https://www.lemo.com/int\\_en/solutions/originals/b-indoor-keyed/gma-0b-045-ra.html](https://www.lemo.com/int_en/solutions/originals/b-indoor-keyed/gma-0b-045-ra.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

# Technical details

## Form & Material

---

|                        |                        |
|------------------------|------------------------|
| Shell style / Model id | GMA - Bend relief Blue |
|------------------------|------------------------|

|                  |                        |
|------------------|------------------------|
| Housing material | Silicone elastomer VMQ |
|------------------|------------------------|

|        |           |
|--------|-----------|
| Keying | No keying |
|--------|-----------|

|        |      |
|--------|------|
| Colour | Blue |
|--------|------|

|        |        |
|--------|--------|
| Weight | 0.46 g |
|--------|--------|

---

## Environment

---

|                  |  |
|------------------|--|
| Technical domain | Audio Video, Energy and Industrial, Medical, Semiconductor, Specialties and Other, Test and Measurement, Transportation, Aerospace and UAV |
|------------------|--|

|                                   |              |
|-----------------------------------|--------------|
| Environmental sealing (IP rating) | No IP rating |
|-----------------------------------|--------------|

|                   |   |
|-------------------|---|
| Temperature range | -60°C / +200°C (max. temperature valid for short periods of use.) |
|-------------------|---|

|                                  |        |
|----------------------------------|--------|
| Temperature range in water steam | +140°C |
|----------------------------------|--------|

---

## Cable fixation

---

|                                    |                |
|------------------------------------|----------------|
| Jacket cable outside diameter [mm] | 4.50 - 5.20 mm |
|------------------------------------|----------------|

---

[https://www.lemo.com/int\\_en/solutions/originals/b-indoor-keyed/gma-0b-045-ra.html](https://www.lemo.com/int_en/solutions/originals/b-indoor-keyed/gma-0b-045-ra.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.