



*Image for illustrative purpose only*

## Summary

[Request a quote](#)

---

[Catalog](#)

---

[Customer Drawing](#)

---

|                                    |                |
|------------------------------------|----------------|
| Jacket cable outside diameter [mm] | 5.40 - 6.00 mm |
|------------------------------------|----------------|

---

|      |    |
|------|----|
| Size | 1B |
|------|----|

---

|        |                  |
|--------|------------------|
| Series | B - Indoor keyed |
|--------|------------------|

---

[https://www.lemo.com/int\\_en/solutions/originals/b-indoor-keyed/gma-1b-054-dn.html](https://www.lemo.com/int_en/solutions/originals/b-indoor-keyed/gma-1b-054-dn.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

# Technical details

## Form & Material

|                        |                            |
|------------------------|----------------------------|
| Shell style / Model id | GMA - Bend relief Black    |
| Housing material       | Thermoplastic polyurethane |
| Keying                 | No keying                  |
| Colour                 | Black                      |
| Weight                 | 0.9 g                      |

## Environment

|                                   |                                                                                                                                            |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| Technical domain                  | Audio Video, Energy and Industrial, Medical, Semiconductor, Specialties and Other, Test and Measurement, Transportation, Aerospace and UAV |
| Environmental sealing (IP rating) | No IP rating                                                                                                                               |
| Temperature range                 | -40°C / +80°C                                                                                                                              |

## Cable fixation

|                                    |                |
|------------------------------------|----------------|
| Jacket cable outside diameter [mm] | 5.40 - 6.00 mm |
|------------------------------------|----------------|