

131332 ✓ ACTIVE



PIDG

TE Internal #: 131332

Tab Terminal, Yellow, 4.06 mm [.16 in] Tab Width, 1.02 mm [.04 in]

Tab Thickness, 12 – 10 AWG, 2.62 – 6.64 mm² Wire, 5180 – 13100

CMA, PIDG

[View on TE.com >](#)

Terminals & Splices > Crimp Wire Pins, Tabs & Ferrules > PIDG Pre-Insulated Diamond Grip Tabs



Crimp Wire Terminal Type: **Tab Terminal**

Mating Tab Width: **4.06 mm [.16 in]**

Mating Tab Thickness: **1.02 mm [.04 in]**

Compatible Insulation Diameter Range: **3.8 – 6.4 mm, 6.4 mm [.149 – .251 in, .25 in]**

Wire Size: **12 – 10 AWG**

[All PIDG Pre-Insulated Diamond Grip Tabs \(8\)](#)

Features

Product Type Features

Sealable	No
Compatible With Discrete Wire Type	Solid, Stranded
Wire Insulation Support Retention Type	Insulation Support

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
-----------------------------------	---------------

Body Features

Sleeve Plating Material	Tin
Sleeve Material	Copper
Insulation Material	Nylon
Primary Product Color	Yellow

Contact Features

Contact Mating Area Length	12.4 mm[.487 in]
----------------------------	------------------



Crimp Wire Terminal Type	Tab Terminal
--------------------------	--------------

Mating Tab Width	4.06 mm [.16 in]
------------------	------------------

Mating Tab Thickness	1.02 mm [.04 in]
----------------------	------------------

Barrel Type	Closed
-------------	--------

Terminal Plating Material	Tin
---------------------------	-----

Terminal Orientation	Straight
----------------------	----------

Mechanical Attachment

Wire Insulation Support	With
-------------------------	------

Dimensions

DIN Wire Size	2.5 – 6 mm ²
---------------	-------------------------

Compatible Insulation Diameter Range	3.8 – 6.4 mm, 6.4 mm [.149 – .251 in] [.25 in]
--------------------------------------	--

Wire Size	5180 – 13100 CMA
-----------	------------------

Barrel Inside Diameter	6.4 mm [.253 in]
------------------------	------------------

Terminal Material Thickness	1 mm [.039 in]
-----------------------------	----------------

Overall Product Length	29.21 mm [1.15 in]
------------------------	--------------------

Usage Conditions

Insulation Option	Partially Insulated
-------------------	---------------------

Packaging Features

Packaging Quantity	500
--------------------	-----

Packaging Method	Loose Piece
------------------	-------------

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
------------------------------	-----------

EU ELV Directive 2000/53/EC	Compliant
-----------------------------	-----------

China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
---	---

EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
--	---

Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
-----------------	--

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts




TE Part # 59824-1
TETRA-CRIMP PIDG PG FASTON 22-10 ASSY



TE Part # 59239-4
HHHT PIDG PG 12-10 ASSY



TE Part # 169400
CERTI-LOK FRAME W/O DIES



TE Part # 47808-6
DIES PIDG 12-10 DIE SET



TE Part # 58433-3
PRO CR ASSY, RBY IS9252



TE Part # 58423-1
DIE, RBY IS9252



TE Part # 169404
CERTI-LOK DIE



TE Part # 539691-2
ERGO DIE R.B.Y

Also in the Series | PIDG



Compression Connectors(50)




Crimp Wire Pins, Tabs & Ferrules(39)




Knife Disconnects(11)



Quick Disconnects(38)



Ring Terminals(587)



Spade Terminals(228)



Special Purpose Terminals(1)




Splices(41)


Customers Also Bought




TE Part #ANT-5GWWS3-SMA
Antenna Dipole Blade 5G/LTE Swivel
SMA



TE Part #130625
TERM, PIDG, SPD, 12-10, M6



TE Part #160404-2
TERM, WIRE PIN, PIDG, 12-10 AWG




TE Part #165564-1
110 PIDG FASTON REC



TE Part #200336-1
CONTACT PIN ASSY.



TE Part #201310-1
MALE BLOCK 75 PL.-MIN RECT.



TE Part #201358-1
MALE BLOCK 50 PL. SER. "M"



TE Part #201369-4
75 POS. PIN HOOD



TE Part #327638
SPLICE BUTT PIDG 12-10/16-14



TE Part #5-1423164-6
7022WC=RLY,STD,OFF,2P,96VDC,15

Documents

Product Drawings

TERM, TAB, PIDG, 12-10

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_131332_F.2d_dxf.zip



English

Customer View Model

[ENG_CVM_CVM_131332_F.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_131332_F.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[PIDG TERMINALS & SPLICES Quick Reference Guide](#)

English

Product Specifications

[Application Specification](#)

English