

172076-2 ✓ ACTIVE

Positive Lock | Mark II, Positive Lock 250

TE Internal #: 172076-2

Receptacle Terminal Housing, 1 Position, Straight, Black, UL 94V-2,  
Nylon, Cable Mount (Free-Hanging), -40 – 105 °C [-40 – 221 °F],  
Positive Lock 250

[View on TE.com >](#)



Terminals & Splices > Terminal Housings, Insulation Sleeves & Blocks > Crimp Terminal Housings



Terminal Type: **Receptacle**

Connector & Housing Type: **Receptacle**

Number of Positions: **1**

Terminal Orientation: **Straight**

UL Flammability Rating: **UL 94V-2**

## Features

### Product Type Features

Connector & Contact Terminates To	Wire & Cable
Sealable	No
Connector System	Wire-to-Board, Wire-to-Wire
Connector & Housing Type	Receptacle

### Configuration Features

Number of Positions	1
---------------------	---

### Body Features

Primary Product Color	Black
-----------------------	-------

### Contact Features

Terminal Type	Receptacle
Terminal Orientation	Straight
Contact Mating Retention	With

### Mechanical Attachment



Mating Alignment Type	Polarization
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

### Housing Features

Housing Material	Nylon
------------------	-------

### Usage Conditions

Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
-----------------------------	----------------------------

### Industry Standards

UL Flammability Rating	UL 94V-2
------------------------	----------

### Packaging Features

Packaging Quantity	1000
--------------------	------

## Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

## Compatible Parts



TE Part # 170328-1  
250 PL MKII REC. 18-14AWG PTBR



TE Part # 170327-1  
250 PL MKII REC. 22-18AWG PTBR



TE Part # 2238155-1  
POS LOCK 250 Rec, MKII, 18-14 TPBR



TE Part # 63239-1  
POSITIVE LOCK 250 REC 12-10 AWG TPBR



TE Part # 170329-1  
250 PL MKII REC. 15-10AWG PTBR



TE Part # 2238156-1  
POS LOCK 250 Rec, MKII, 22-18 TPBR



TE Part # 170333-1  
PL 250 RECEPTACLE 22-18 AWG PTPBR



TE Part # 170334-1  
250 PL MIII,REC.,18-14 AWG,PTBR




TE Part # 170335-1  
PL 250 RECEPTACLE 15-10 AWG PTPBR



TE Part # 724659-2  
EXT TOOL FOR POSITIVE .250

## Also in the Series | Mark II



Automotive Connector Locks & Position Assurance(1)




Automotive Housings(6)



Automotive Seals & Cavity Plugs(1)




Automotive Signal & Power Connector Housings(6)




Crimp Terminal Housings(176)

Also in the Series | **Positive Lock 250**



Automotive Terminals(1)



Crimp Terminal Housings(176)



Insertion & Extraction Tools(3)



Insulation Boots & Sleeves(5)



Quick Disconnects(171)


Customers Also Bought



TE Part #EK5493-000  
ES2000-NO.8-A1-0-2IN




TE Part #280311  
IS 375 FASTON NYLON



TE Part #360050-1  
090 DIA CLSTR BLK



TE Part #CAT-AM7801-T273  
AMPSEAL 16 CONTACTS



TE Part #1969823-1  
250 HIGH TEMP POS LOCK HSG FLAG



TE Part #1-2035366-0  
Backshell,AS16,6P,90Deg,NC12,LP,  
Plug



TE Part #2040594-2  
SEAL CAP HSG 3P, AMPSEAL16 SEA



TE Part #2238104-1  
250 PL MKII REC. 16-14AWG NPST



## Documents

### CAD Files

#### 3D PDF

3D

#### Customer View Model

[ENG\\_CVM\\_CVM\\_172076-2\\_W.2d\\_dxf.zip](#)

English

#### Customer View Model

[ENG\\_CVM\\_CVM\\_172076-2\\_W.3d\\_igs.zip](#)

English

#### Customer View Model

[ENG\\_CVM\\_CVM\\_172076-2\\_W.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

### Datasheets & Catalog Pages

#### Positive Lock Receptacles

English

### Product Specifications

#### Application Specification

English

#### Application Specification

English

#### Application Specification

Japanese

#### CRIMP OF MATE-N-LOK PIN CONTACT

Japanese

#### CRIMP OF MATE-N-LOK PIN CONTACT

English

#### Application Specification

English

### Agency Approvals

#### CSA Certificate

English

172076-2

Receptacle Terminal Housing, 1 Position, Straight, Black, UL 94V-2, Nylon, Cable Mount (Free-Hanging), -40 – 105 °C [-40 – 221 °F], Positive Lock 250

