




Terminals & Splices > Terminal Housings, Insulation Sleeves & Blocks > Crimp Terminal Housings



Terminal Type: **Tab**
Connector & Housing Type: **Tab Housing**
Number of Positions: **1**
Terminal Orientation: **Straight**
UL Flammability Rating: **UL 94V-2**

Features

Product Type Features

Connector & Contact Terminates To	Wire & Cable
Sealable	No
Connector & Housing Type	Tab Housing

Configuration Features

Number of Positions	1
---------------------	---

Body Features

Primary Product Color	Natural
-----------------------	---------

Contact Features

Terminal Type	Tab
Terminal Orientation	Straight
Contact Mating Retention	With

Mechanical Attachment

Mating Retention Type	Latch
-----------------------	-------



Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	Polyamide
------------------	-----------

Dimensions

Product Length	31.1 mm[1.22 in]
----------------	------------------

Usage Conditions

Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
-----------------------------	----------------------------

Industry Standards

UL Flammability Rating	UL 94V-2
------------------------	----------

Packaging Features

Packaging Quantity	1400
--------------------	------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on



requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 626063-1 FASTIN-ON .110 HOUSING TAB PA 6.6	TE Part # 170340-1 FF 250 TAB 20-14AWG BR WITHOUT LATCH	TE Part # 170341-3 FF 250 TAB 14-12AWG PTBR WITHOUT LATCH	TE Part # 170349-2 FF 250 TAB 22-20AWG TPBR WITHOUT LATCH
TE Part # 170340-3 FF 250 TAB 20-14AWG PTBR WITHOUT LATCH	TE Part # 170349-1 FF 250 TAB 22-20AWG BR WITHOUT LATCH	TE Part # 521744-1 FASTIN FASTON 250 HOUSING TAB NYLON 6/6	


Also in the Series | FASTIN-FASTON 250

Crimp Terminal Housings(192)	Insertion & Extraction Tools(2)	Quick Disconnects(216)

Customers Also Bought

TE Part #OF84005-FNF OMNI,FG,840-868MHz ,5dBi,	TE Part #180907 FF 250 REC HSG 2P NYLON NAT	TE Part #180908 FF 250 TAB HSG 2P NYLON NAT	TE Part #180923 FF 250 REC HSG 2P NYLON NAT





TE Part #180941
FF 250 REC HSG 3P NYLON NAT



TE Part #2-644803-8
08P MTA100 SHRD HDR ASSY RA FL



TE Part #2-964338-2
MAG MATE CONTACT MK II

TE Part #K1152517
Foot Switch 44-02-013-900



TE Part #1776113-5
5P,3.81MM,SIDE ENTRY,HIGH TMP



TE Part #4-1105100-2
HE/HA-C-STI.AU.2,5

Documents

Product Drawings

FF 250 TAB HSG 1P NYLON NAT

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_180916_AD_c-180916-ad.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_180916_AD_c-180916-ad.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_180916_AD_c-180916-ad.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

White Paper: Nylon Discoloration

English

Product Specifications

Application Specification

English