

1969357-1 ✓ ACTIVE


TE Internal #: 1969357-1

2 Circuit Cluster Block, Polyester PBT, 22 – 10 AWG, .326 – 5.26 mm<sup>2</sup> Wire, -20 – 120 °C [-4 – 248 °F]

[View on TE.com >](#)



Terminals & Splices > Terminal Housings, Insulation Sleeves & Blocks > Cluster Blocks



Number of Circuits: 2

Primary Product Material: Polyester PBT

Wire Size: .326 – 5.26 mm<sup>2</sup>

Operating Temperature Range: -20 – 120 °C [-4 – 248 °F]

## Features

### Product Type Features

Compatible With Discrete Wire Type	Lead Wire
------------------------------------	-----------

### Configuration Features

Number of Circuits	2
--------------------	---

### Body Features

Primary Product Color	Natural
-----------------------	---------

Primary Product Material	Polyester PBT
--------------------------	---------------

### Contact Features

Mating Pin Diameter	2.29 mm[.09 in]
---------------------	-----------------

### Mechanical Attachment

Mount Diameter	13.46 mm[.53 in]
----------------	------------------

Block Mounting Configuration	2 Forward - 1 Back
------------------------------	--------------------

### Dimensions

Product Length	22.45 mm[.884 in]
----------------	-------------------

Wire Size	.326 – 5.26 mm <sup>2</sup>
-----------	-----------------------------

### Usage Conditions



Operating Temperature Range	-20 – 120 °C[-4 – 248 °F]
-----------------------------	---------------------------

### Industry Standards

UL Flammability Rating	UL 94HB
------------------------	---------

### Packaging Features

Packaging Method	Package
Packaging Quantity	1

### Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

### Compatible Parts



## Customers Also Bought



## Documents

### Product Drawings

[HSG .090 CLUSTER BLOCK 2 POS](#)

English

### CAD Files

[3D PDF](#)

3D

Customer View Model

[ENG\\_CVM\\_CVM\\_1969357-1\\_A\\_c-1969357-1-a.2d\\_dxf.zip](#)

1969357-1

2 Circuit Cluster Block, Polyester PBT, 22 – 10 AWG, .326 – 5.26 mm<sup>2</sup> Wire, -20 – 120 °C [-4 – 248 °F]



English

**Customer View Model**

[ENG\\_CVM\\_CVM\\_1969357-1\\_A\\_c-1969357-1-a.3d\\_igs.zip](#)

English

**Customer View Model**

[ENG\\_CVM\\_CVM\\_1969357-1\\_A\\_c-1969357-1-a.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

**Product Specifications**

[Engineering Report](#)

English