




Specialty Terminals

751-250, 752-250, 754-250

Female Flag Disconnect, Non-Insulated, Butted Seam



Data Sheet

Product Number	Wire Range (AWG)	Mates with Male Tab Width(W') x Thickness	L	Barrel Length	Barrel I.D.
751-250	22-18	0.250 x 0.032	0.50	0.25	0.075
752-250	16-14	0.250 x 0.032	0.51	0.26	0.095
754-250*	12-10	0.250 x 0.032	0.63	0.25	0.175

*Not UL Listed or CSA Certified.



LISTED 314R
UNDERWRITERS
LABORATORIES
STANDARD NO. UL 486A
3M FILE NO. E70512



CANADIAN STANDARDS
ASSOCIATION
STANDARD NO. 22.2
NO. 0, 65
3M FILE NO. LR22190

Installation Information

WARNING

Turn power off before installing or removing terminal. All electrical work should be done according to appropriate electrical codes.

Strip away the end 3/8 inch of wire insulation.

Make the crimp in the proper station of a recommended 3M crimp tool: TH-450 (scissor style) hand tools.

Specifications

Wire Size:
Barrel Seam:
Maximum Operating Temp:
Maximum Current:
Terminal Material:
Plating:

See Table Above
Butted
347°F (175°C)
Same as Wire
Brass
Tin



● Barrel Crimp (Electrical)

Suitable for field or factory installation.

Engineering Specification

Crimp-type female disconnects shall, electrically and mechanically, connect permanently to a prestripped end of a stranded copper wire, and have a tongue portion with fingers which grip a male disconnect in a separable, reusable manner, forming a Quick Connect Wiring Termination.

The connector line shall offer tongue variations (sized to grip male tabs: 0.250" x 0.032" or 0.187" x 0.020") and barrel variations in wire (AWG) range (12-18, 16-14, 12-10) and construction, non-insulated, vinyl insulated, nylon fully insulated, etc. The tongue portion shall be marked with the wire range and manufacturer's symbol (↑).

The non-insulated Female Flag Disconnect shall be tin plated 0.020" thick brass, with a tongue for gripping a 0.250" x 0.032" male tab, and with a butted seam barrel positioned across the closed end of the tongue and sized for a specified (AWG) wire range: 22-18, 16-14, 12-10*.

Disconnects shall be suitable for field or factory wiring, with the required UL approved strain relief.

*Not UL Listed or CSA Certified.

3M is a trademark of 3M Company.

 is a trademark of Underwriters Laboratories.

 is a trademark of Canadian Standards Association.

IMPORTANT NOTICE

Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use.

Warranty; Limited Remedy; Limited Liability. This product will be free from defects in material and manufacture as of the date of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any loss or damage arising from this 3M product, whether direct, indirect, special, incidental or consequential regardless of the legal theory asserted.**

3M

Electrical Products Division

6801 River Place Blvd.
Austin, TX 78726-9000
<http://www.3M.com/elpd>

Litho in USA.
© 3M 2003 78-8126-5542-7-B