

66261-5 ✓ ACTIVE

AMP

TE Internal #: 66261-5

Tin (Sn), Tab Contact, 16 AWG, 1.25 – 1.4 mm<sup>2</sup> / 2 – 3 mm<sup>2</sup> Wire,  
Crimp, Copper, Power, -40 – 85 °C [-40 – 185 °F]

[View on TE.com >](#)



Connectors > Contacts > Connector Contacts



Contact Type: **Tab**

Contact Mating Area Plating Material: **Tin (Sn)**

Wire Contact Termination Area Plating Material: **Tin**

Wire Size: **1.25 – 1.4 mm<sup>2</sup>, 2 – 3 mm<sup>2</sup>**

## Features

### Contact Features

|   |                  |
|---|------------------|
| Contact Type  | Tab              |
| Contact Mating Area Plating Material                  | Tin (Sn)         |
| Wire Contact Termination Area Plating Material        | Tin              |
| Contact Base Material                                 | Copper           |
| Contact Current Rating (Max)                          | 15 A             |
| Mating Tab Width                                      | 5.84 mm[.23 in]  |
| Mating Tab Thickness                                  | 2.67 mm[.105 in] |
| Contact Mating Area Plating Material Thickness        | 1.27 µm[50 µin]  |
| Wire Contact Termination Area Plating Thickness       | 1.27 µm[50 µin]  |
| Wire Contact Termination Area Plating Material Finish | Matte            |
| Contact Orientation                                   | Right Angle      |
| Contact Underplating Material                         | Copper           |

### Termination Features

|                                    |              |
|------------------------------------|--------------|
| Termination Method to Wire & Cable | Crimp        |
| Product Terminates To              | Wire & Cable |

### Mechanical Attachment

|                         |      |
|-------------------------|------|
| Wire Insulation Support | With |
|-------------------------|------|

### Dimensions

|           |  |
|-----------|--|
| Wire Size | 1.25 – 1.4 mm <sup>2</sup> , 2 – 3 mm <sup>2</sup> |
|-----------|--|



|                                      |                                |
|--------------------------------------|--------------------------------|
| Compatible Insulation Diameter Range | 3.43 – 4.06 mm [.135 – .16 in] |
|--------------------------------------|--------------------------------|

### Usage Conditions

|                             |                            |
|-----------------------------|----------------------------|
| Operating Temperature Range | -40 – 85 °C [-40 – 185 °F] |
|-----------------------------|----------------------------|

### Operation/Application

|                     |       |
|---------------------|-------|
| Circuit Application | Power |
|---------------------|-------|

### Packaging Features

|                    |     |
|--------------------|-----|
| Packaging Quantity | 100 |
|--------------------|-----|

|                  |     |
|------------------|-----|
| Packaging Method | Bag |
|------------------|-----|

### Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

|   |   |
|---|---|
| EU RoHS Directive 2011/65/EU                  | Compliant   |
| EU ELV Directive 2000/53/EC                   | Compliant   |
| China RoHS 2 Directive MIIT Order No 32, 2016 | 有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold   |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2025 (250)<br>Candidate List Declared Against: JUNE 2025 (250)<br>Does not contain REACH SVHC |
| Halogen Content                               | BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.  |
| Solder Process Capability                     | Not applicable for solder process capability  |

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

### Compatible Parts



### Customers Also Bought



### Documents



### Product Drawings

#### MALE CONTACT ASSY. (L.P.)

English

---

### CAD Files

#### Customer View Model

[ENG\\_CVM\\_66261-5\\_Y.3d\\_igs.zip](#)

English

#### Customer View Model

[ENG\\_CVM\\_66261-5\\_Y.3d\\_stp.zip](#)

English

#### Customer View Model

[ENG\\_CVM\\_66261-5\\_Y.2d\\_dxf.zip](#)

English

### 3D PDF

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

---

### Product Specifications

#### Application Specification

English