

OVERVIEW

DISTRIBUTOR

SPECIFICATION

OVERVIEW



DESCRIPTION

Board to Board connector, Unshrouded Header, Through Hole, Single Row, 2 Position, Vertical.

DOCUMENTATION

Product Drawing

Product Presentation

PRODUCT ENVIRONMENTAL COMPLIANCE

Click to download [Certificate of Compliance Report](#)

DISTRIBUTOR STOCK CHECK

AMERICAS

EUROPE

ASIA

Distributor Name	Stock	Updated Date	
Mouser Electronics Inc.	3599	7/22/2021	Buy Now

PART SPECIFICATION DETAIL

The information below is for reference only. For more technical details, refer to product specification and application specification.

Number of Contacts	2	Number of Rows	1
Orientation	Straight	Termination Style	DIP
Length (Overall pin)	12.60mm (0.496in)	Mating Length	7.00mm (0.275in)
Pitch	2.54mm (0.100in)	Tail Length	3.00mm (0.118in)
Current Rating	3A Continuous	Resistance (Insulation)	1000MΩ
Voltage Rating	1000V AC rms	Color - Housing	Black
Flammability Rating	UL 94 V-0	Material Contact	Copper Alloy
Material Housing	Self Extinguishing Thermoplastic	Operating Temperature Range	-55°C to +125°C
Plating Contact Area	0.20µm (8µin) Gold	Tail Plating	0.20µm (7.874µin) Gold
Retention Feature	No	Packaging	Bulk Packaging

AMPHENOL ICC

ABOUT US
CAREERS
SITEMAP

SUPPORT

CONTACT US
LIVE CHAT
DISTRIBUTOR
AMPHENOL ICC SALES OFFICES

FOLLOW US



NEWSLETTER

Enter your email address: [SUBMIT](#)

Signing up for newsletter indicates you agree with our [Terms of Services](#).