





APPROVED: _____
 DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	8/10/18	
A		ADDED LAYOUT	3/31/21	LH/TY
B		ADDED RING DRAWING	11/12/21	LH/TY



RECOMMENDED PCB LAYOUT



SPECIFICATIONS:

Material:

Plug: Brass, 10u" Gold plated over Nickel
 Plunger: Brass, 10u" Gold plated over Nickel
 Barrel: Brass, 10u" Gold plated over Nickel
 Spring: SUS 304, Gold plated
 Bead: Zirconia

Waterproof ring: Silicone

Electrical:

Rated Voltage: 12 VDC
 Rated Current: 10 A
 Contact resistance: 50 mohms max

Mechanical:

Contact Force: 175g±20g @ 1.80mm working stroke
 Max. Stroke: 2.50mm force 230±20%
 Life Test: 20,000 Cycles
 Ingress Protection Rating: IP67

Environmental:

Salt spray: 96H
 Lead free, RoHS compliant.



UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM]. TOLERANCES: EXCEPT AS NOTED

INCHES	HOLES
.X ± .10	Ø.X ± .10
.XX ± .020	Ø.XX ± .015
.XXX ± .015	Ø.XXX ± .010

DRAWN	AY	8/10/18
CHECKED	TW	8/10/18
APPROVED		

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY AND SHOULD NOT BE USED WITHOUT PRIOR WRITTEN PERMISSION FROM ADAM TECH

ADAM TECH

909 Rahway Avenue,
 Union, NJ 07083
 Phone: 908-687-5000
 Fax: 908-687-5710

TITLE
DIP SPRING LOADED PIN, STRAIGHT WATERPROOF

SIZE X	PART NO. PH-MVP-26515-10/10-WP	REV. -
REF: S00170C	SCALE: NTS	SHEET 1 OF 1