


PX0833 Datasheet

Product Name // Front Panel Mount Connector PX0833
Series CAT5e Shielded Coupler

 [View Product Page](#)



// Product Description:

- Front Panel Mounting Connector
 - Water and dustproof to IP68 when mated with compatible connector
 - Single hole fixing
 - Supplied with panel sealing gasket
 - CAT5e or Cat6a shielded coupler - standard RJ45 patchcord can be plugged into rear
- PX0833/E or PX0893/E version has additional Earth wire
 - PX0888 Shielding Backshell available separately - fits to rear of connector to maintain RJ45 coupler shielding directly to panel
 - PX0733 Sealing Cap available separately to maintain IP rating of unmated connectors
 - Mate with Cat 5e PX0834, PX0836, PX0837, PX0838 Standard Series Flex Cable Connectors
 - Mate with Cat 6a PX0894, PX0896, PX0897, PX0898 Standard Series Flex Cable Connectors

// General Information:

Product Display Title:	Front Panel Mounting Connector
Product Family:	Circular Data Connectors
Product Series:	Standard Buccaneer - Ethernet
Body Material:	Polyester (PET)
Body Material Type:	Plastic Body
Contact Type:	Socket Contact
Coupling Type:	Screw
Current Max:	1.5A
Data Cable Type:	IP68 RJ45 Coupler
Diameter Over Coupling Ring Mm:	38.1mm
Ethernet Category:	Cat 5e
Flamability Rating:	UL94V-0
Function:	Front Panel Mount Connector
Ip Rating:	IP68 IP69K
Max Operating Temperature:	+70°C
Min Operating Temperature:	-20°C
Number Of Contacts:	8 Contacts
Voltage Max:	42V

// Product PDF Links



// Product 3D CAD Model Links

