

			<table><tr><th colspan="4">REVISIONS</th></tr><tr><th>REV</th><th>DESCRIPTION</th><th>DATE</th><th>APPROVED</th></tr><tr><td>02₂</td><td>REVISED</td><td>07/07/94</td><td>AP</td></tr></table>				REVISIONS				REV	DESCRIPTION	DATE	APPROVED	02 ₂	REVISED	07/07/94	AP																																																								
			REVISIONS																																																																							
			REV	DESCRIPTION	DATE	APPROVED																																																																				
02 ₂	REVISED	07/07/94	AP																																																																							
<table><tr><th>ELECTRICAL</th><th>MECHANICAL</th><th>ENVIRONMENTAL</th></tr><tr><td>Nominal Impedance (Ohms) 50</td><td>Interface Dimensions MIL-STD-348A</td><td>Temperature Rating -65°C To 125°C</td></tr><tr><td>Frequency Range (GHz) DC to 18</td><td>Fig. 310.1 & 310.2</td><td>Vibration MIL-STD-202, Method</td></tr><tr><td>Volt Rating (VRMS MAX)</td><td>Recommended Mating</td><td>204, Condition D</td></tr><tr><td> @ Sea Level 335</td><td>Torque 7-10 in-Lb</td><td>Shock MIL-STD-202, Method 213,</td></tr><tr><td>VSWR 1.05 + .005f(GHz)</td><td>Mating Characteristics:</td><td>Condition I</td></tr><tr><td>Insertion Loss (dB MAX) .03 √f(GHz)</td><td>Insertion (MAX Lbs) 3</td><td>Thermal Shock MIL-STD-202,</td></tr><tr><td>RF Leakage (dB MIN) [-60-f(GHz)]</td><td>Withdrawal (MIN Oz) 1</td><td>Method 107, Condition B,</td></tr><tr><td>Corona, 70,000 Ft (VRMS MIN) 250</td><td>Force to Engage and</td><td>except high temp shall be +155°C</td></tr><tr><td>Dielectric Withstanding Voltage</td><td>Disengage (In-Lbs MAX) 2</td><td>Moisture Resistance MIL-STD-202,</td></tr><tr><td>(VRMS MIN) @ Sea Level 1500</td><td>Center Contact Captivation</td><td>Method 106</td></tr><tr><td>Contact Resistance (Milliohms MAX)</td><td>Axial (Lbs) 6</td><td>Corrosion - MIL-STD-202, Method</td></tr><tr><td>Center Contact 4.0</td><td>Radial (In-Oz) 4</td><td>101, Condition B, 5% salt spray</td></tr><tr><td>Outer Contact 2.0</td><td>Coupling Proof Torque (In-Lbs MIN) 15</td><td></td></tr><tr><td>Cable to Housing N/A</td><td>Coupling Mechanism Retention</td><td></td></tr><tr><td>RF High Potential @ Sea Level</td><td>Force (Lbs MIN) 60</td><td></td></tr><tr><td>(VRMS MIN @ 5 MHz) 670</td><td>Weight (Grams) TBD</td><td></td></tr><tr><td>I.R.(Megohms MIN) 5,000</td><td></td><td></td></tr></table>			ELECTRICAL	MECHANICAL	ENVIRONMENTAL	Nominal Impedance (Ohms) 50	Interface Dimensions MIL-STD-348A	Temperature Rating -65°C To 125°C	Frequency Range (GHz) DC to 18	Fig. 310.1 & 310.2	Vibration MIL-STD-202, Method	Volt Rating (VRMS MAX)	Recommended Mating	204, Condition D	@ Sea Level 335	Torque 7-10 in-Lb	Shock MIL-STD-202, Method 213,	VSWR 1.05 + .005f(GHz)	Mating Characteristics:	Condition I	Insertion Loss (dB MAX) .03 √f(GHz)	Insertion (MAX Lbs) 3	Thermal Shock MIL-STD-202,	RF Leakage (dB MIN) [-60-f(GHz)]	Withdrawal (MIN Oz) 1	Method 107, Condition B,	Corona, 70,000 Ft (VRMS MIN) 250	Force to Engage and	except high temp shall be +155°C	Dielectric Withstanding Voltage	Disengage (In-Lbs MAX) 2	Moisture Resistance MIL-STD-202,	(VRMS MIN) @ Sea Level 1500	Center Contact Captivation	Method 106	Contact Resistance (Milliohms MAX)	Axial (Lbs) 6	Corrosion - MIL-STD-202, Method	Center Contact 4.0	Radial (In-Oz) 4	101, Condition B, 5% salt spray	Outer Contact 2.0	Coupling Proof Torque (In-Lbs MIN) 15		Cable to Housing N/A	Coupling Mechanism Retention		RF High Potential @ Sea Level	Force (Lbs MIN) 60		(VRMS MIN @ 5 MHz) 670	Weight (Grams) TBD		I.R.(Megohms MIN) 5,000			<table><tr><td>HOUSING COUPLING NUT</td><td>STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303</td><td>PASSIVATE PER ASTM-A380</td></tr><tr><td>DIELECTRIC</td><td>TFE FLUOROCARBON PER ASTM-D-1457</td><td>N/A</td></tr><tr><td>CENTER CONTACT</td><td>BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H</td><td>GOLD PLATE PER MIL-G-45204</td></tr><tr><td>RETAINING RING</td><td>BERYLLIUM COPPER PER ASTM B 194, ALLOY C17200, CONDITION H</td><td>N/A</td></tr><tr><td>GASKET</td><td>SILICONE RUBBER PER ZZ-R-765</td><td>N/A</td></tr></table>			HOUSING COUPLING NUT	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER ASTM-A380	DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A	CENTER CONTACT	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204	RETAINING RING	BERYLLIUM COPPER PER ASTM B 194, ALLOY C17200, CONDITION H	N/A	GASKET	SILICONE RUBBER PER ZZ-R-765	N/A
ELECTRICAL	MECHANICAL	ENVIRONMENTAL																																																																								
Nominal Impedance (Ohms) 50	Interface Dimensions MIL-STD-348A	Temperature Rating -65°C To 125°C																																																																								
Frequency Range (GHz) DC to 18	Fig. 310.1 & 310.2	Vibration MIL-STD-202, Method																																																																								
Volt Rating (VRMS MAX)	Recommended Mating	204, Condition D																																																																								
@ Sea Level 335	Torque 7-10 in-Lb	Shock MIL-STD-202, Method 213,																																																																								
VSWR 1.05 + .005f(GHz)	Mating Characteristics:	Condition I																																																																								
Insertion Loss (dB MAX) .03 √f(GHz)	Insertion (MAX Lbs) 3	Thermal Shock MIL-STD-202,																																																																								
RF Leakage (dB MIN) [-60-f(GHz)]	Withdrawal (MIN Oz) 1	Method 107, Condition B,																																																																								
Corona, 70,000 Ft (VRMS MIN) 250	Force to Engage and	except high temp shall be +155°C																																																																								
Dielectric Withstanding Voltage	Disengage (In-Lbs MAX) 2	Moisture Resistance MIL-STD-202,																																																																								
(VRMS MIN) @ Sea Level 1500	Center Contact Captivation	Method 106																																																																								
Contact Resistance (Milliohms MAX)	Axial (Lbs) 6	Corrosion - MIL-STD-202, Method																																																																								
Center Contact 4.0	Radial (In-Oz) 4	101, Condition B, 5% salt spray																																																																								
Outer Contact 2.0	Coupling Proof Torque (In-Lbs MIN) 15																																																																									
Cable to Housing N/A	Coupling Mechanism Retention																																																																									
RF High Potential @ Sea Level	Force (Lbs MIN) 60																																																																									
(VRMS MIN @ 5 MHz) 670	Weight (Grams) TBD																																																																									
I.R.(Megohms MIN) 5,000																																																																										
HOUSING COUPLING NUT	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER ASTM-A380																																																																								
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A																																																																								
CENTER CONTACT	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204																																																																								
RETAINING RING	BERYLLIUM COPPER PER ASTM B 194, ALLOY C17200, CONDITION H	N/A																																																																								
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A																																																																								
<table><tr><th>COMPONENT</th><th>MATERIAL</th><th>FINISH</th></tr><tr><td>UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON</td><td>DRAWN BY R.L. DATE 7/18/73</td><td rowspan="3"> AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599</td></tr><tr><td>FRAC. DEC. ANGLES</td><td>CHECKED BY L.P. DATE 7/18/73</td></tr><tr><td>± 1/64 ±.005 ± 1°</td><td>APPROD BY L.P. DATE 7/18/73</td></tr><tr><td>These drawings and specifications are the property of M/A-COM Interconnect Division and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.</td><td>USE ASS'Y PROCEDURE</td><td>TITLE OSM PLUG TO OSM JACK ADAPTER</td></tr><tr><td></td><td>NO. A.P. N/A</td><td>SIZE B CODE IDENT NO. 26805 2082-5133-02 REV 02₂</td></tr><tr><td></td><td></td><td>SCALE 5:1 SHEET 1 OF 1</td></tr></table>			COMPONENT	MATERIAL	FINISH	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON	DRAWN BY R.L. DATE 7/18/73	 AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599	FRAC. DEC. ANGLES	CHECKED BY L.P. DATE 7/18/73	± 1/64 ±.005 ± 1°	APPROD BY L.P. DATE 7/18/73	These drawings and specifications are the property of M/A-COM Interconnect Division and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	USE ASS'Y PROCEDURE	TITLE OSM PLUG TO OSM JACK ADAPTER		NO. A.P. N/A	SIZE B CODE IDENT NO. 26805 2082-5133-02 REV 02 ₂			SCALE 5:1 SHEET 1 OF 1																																																					
COMPONENT	MATERIAL	FINISH																																																																								
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON	DRAWN BY R.L. DATE 7/18/73	 AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599																																																																								
FRAC. DEC. ANGLES	CHECKED BY L.P. DATE 7/18/73																																																																									
± 1/64 ±.005 ± 1°	APPROD BY L.P. DATE 7/18/73																																																																									
These drawings and specifications are the property of M/A-COM Interconnect Division and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	USE ASS'Y PROCEDURE	TITLE OSM PLUG TO OSM JACK ADAPTER																																																																								
	NO. A.P. N/A	SIZE B CODE IDENT NO. 26805 2082-5133-02 REV 02 ₂																																																																								
		SCALE 5:1 SHEET 1 OF 1																																																																								