



BNC

TE Internal #: 5227726-2

BNC Connector, Jack, 50 ohm, Bayonet, 4 GHz, Cable-to-Board, 1 Position, Wire & Cable, Panel Mount, -55 – 85 °C [-67 – 185 °F], Solder, Straight, BNC

[View on TE.com >](#)

Connectors > RF Connectors > Coax Connectors > BNC RF Connector: Jack Assembly, Isolated Ground Protection, 50 Ohm



RF Interface: **BNC**

RF Connector Style: **Jack**

RF Connector Mated Outer Diameter (Approximate): **14.53 mm [.572 in]**

Impedance: **50 Ω**

RF Connector Coupling Mechanism: **Bayonet**

[All BNC RF Connector: Jack Assembly, Isolated Ground Protection, 50 Ohm \(3\)](#)

Features

Product Type Features

RF Interface	BNC
RF Connector Style	Jack
Connector System	Cable-to-Board
Sealable	No
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Positions	1
Number of Coaxial Contacts	1

Electrical Characteristics

EMI & RFI Protection & Suppression Type	Isolated Ground
Impedance	50 Ω

Body Features



Body Material	Zinc
---------------	------

Body Plating Material	Nickel
-----------------------	--------

Contact Features

	5080 μin
--	----------

RF Connector Center Contact Underplating Material	Nickel
---	--------

RF Connector Center Contact Plating Material	Silver (Ag)
--	-------------

RF Connector Center Contact Material	Phosphor Bronze
--------------------------------------	-----------------

Termination Features

Termination Method to Wire & Cable	Solder
------------------------------------	--------

Mechanical Attachment

Panel Attachment Style	Front Mount
------------------------	-------------

RF Connector Coupling Mechanism	Bayonet
---------------------------------	---------

Connector Mounting Type	Panel Mount
-------------------------	-------------

RF Contact Captivation Method	Mechanical
-------------------------------	------------

Detent	With
--------	------

Housing Features

Housing Color	White
---------------	-------

Body Orientation	Straight
------------------	----------

Dimensions

RF Connector Mated Outer Diameter (Approximate)	14.53 mm[.572 in]
---	-------------------

Usage Conditions

Insulation Option	Uninsulated
-------------------	-------------

Operating Temperature Range	-55 – 85 °C[-67 – 185 °F]
-----------------------------	---------------------------

Operation/Application

Operating Frequency Range	4 GHz
---------------------------	-------

Packaging Features

Packaging Method	Carton
------------------	--------

Other

Grade	Commercial
-------	------------

Dielectric Material	PBT
---------------------	-----



Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量超出标准 Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2022 (224) SVHC > Threshold: Pb (3.7% in Component part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts






TE Part # 5228980-7
JACK,BHD,COML,SERIES BNC,GOLD



TE Part # 1-221128-0
PLUG,COMMERCIAL BNC



TE Part # 1-5227079-6
COMM BNC PLUG



TE Part # 1-5221128-0
PLUG,COMMERCIAL BNC



TE Part # 5413779-3
COML BNC,50 OHM, HEX CRIMP



TE Part # CAT-076-BNCVTBAY
BNC Vertical Jack RF Connector, 50 Ohm, Bayonet Coupling Mechanism



TE Part # 5227169-7
BNC SOLDER JACK RECEPTACLE



TE Part # 5227169-4
BNC - SOLDER RECEPT



TE Part # ADP-BNCM-BNCF-T
BNC Plug to BNC Jack (2) Tee



TE Part # ADP-BNCM-BNCF-T-2
BNC Plug to BNC Jack (2) Tee



TE Part # 1-5221128-7
PLUG,COMMERCIAL BNC



TE Part # 6274315-1
BNC JACK, NONSWITCHING



TE Part # 8-5227079-2
COMM BNC PLUG



TE Part # CAT-076-BNCRABAY
BNC RF Connector: Male (Jack), Right Angle



TE Part # 5413515-2
JACK,DECOUPLER,RTANG,BNC PCB



TE Part # 5227079-1
COMM BNC PLUG

Also in the Series | **BNC**



Coax Connectors(166)



RF Cable Assemblies(25)




RF Terminators(1)

Customers Also Bought



TE Part #65002-06N
RECP ASSY



TE Part #806809-000
234A021-25-0



TE Part #806179-SF
FN3270H-10-44



TE Part #1-103168-3
30 MODII HDR DRST SHRD .100CL



TE Part #1-534206-3
26 MODII VRT DR CE 100/115



TE Part #1462052-3
HF6 53 = 50OHM 140MW 5V MONO



TE Part #3-1609115-4
10EGG1-1=F8227



TE Part #4-1617118-7
J1MAPD-26XM = M39016/23-024M



TE Part #1617121-9
JMAC-26XM = M39016/9-062M



TE Part #5102159-6
A/L UNIV HDR 26P RA

Documents

Product Drawings

ISOLATED BNC SOLDER JACK ASSY

English

CAD Files

3D PDF

3D

Customer View Model

[ENG_CVM_CVM_5227726-2_B.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_5227726-2_B.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_5227726-2_B.3d_stp.zip](#)

English

3D PDF

English



Customer View Model

[ENG_CVM_5227726-2_A.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_5227726-2_A.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_5227726-2_A.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[BNC Connectors](#)

English