



*1:PHOSPHOR BRONZE

RoHS Compliant [Cd ≤75ppm]
 REMARKS BRASS: Cd ≤75ppm
 PHOSPHOR BRONZE: Pb <4wt%

NO.	DESCRIPTION	MATERIAL	Q'TY	FINISH	REMARK
10	BODY	BRASS	1	Ni	
9	WASHER	BRASS	1	Ni	
8	INSULATOR B	PTFE	1	--	
7	CENTER PIN	*1	1	Au	
6	WASHER	FE	1	Ni	
5	SPRING	SK5	1	Ni	
4	INNER RETAINING RING	SK5	1	Ni	
3	GASKET	SILICONE	1	--	
2	INSULATOR A	PTFE	1	--	
1	SHELL	BRASS	1	Ni	

SCALE 3/1

UNIT mm

DATE 2025.03.18

DRAWN	INSPECTED	APPROVED	CHECKED
グエン '25.03.18 テイエン	檜 '25.03.18 澤	山 '25.03.18 本	三 '25.03.18 村

PROJECTION

株式会社 トーコネ
 TO-CONNE CO., LTD.

PART NUMBER

BNCP-MHVJ

DRAWING NO. Z-0676769

■ Part number : BNCP-MHVJ

■ Drawing number : Z-0676769

■ Nominal

Standard : MIL-C-39012

Voltage rating : AC 500V

Rated frequency : 500MHz

Impedance : Non-constant

Operating temperature range : -40°C~+85°C

Operating humidity range : 95%(Max.) ※No condensation

■ Structural shape : Conformity with the drawings.

■ Electrical

Test Items	Test Method/Value	Remarks
Insulation resistance	5000M Ω (Min.) at DC 500V	
Withstanding voltage	1 minute at AC 1000V	
Contact resistance	Inner conductor : 1.5m Ω (Max.)(BNC)、2.0m Ω (Max.)(MHV) Outer conductor : 1.4m Ω (Max.)(BNC)、2.2m Ω (Max.)(MHV)	
VSWR	DC~500MHz : 1.1(Max.)	

■ Mechanical

Test Items	Test Method/Value	Remarks
Compatibility	No defects or abnormalities	Connecting with a standard compliant connector
Tensile strength of coupling mechanism	445N	At axial tensile force
Center contact captivation	26.69N(Min.)	At axial tensile force
Center contact retaining force	0.56N(Min.)(MHV)	With a standard pin gauge

■ Revisions

No.	Date	Contents
1		
2		
3		

Date	Name
2025/03/18	テイエン(Prepared)
2025/03/18	山本(Inspected)
2025/03/18	檜澤(Approved)
2025/03/18	三村(Checked)