



Image for illustrative purpose only

Summary

[Request a quote](#)

[Customer Drawing](#)

| | |
|---------------------|----------------|
| Nb of contacts Coax | 1 |
| Plug | Plug - Elbow |
| Locking system | Push-pull |
| Size | 00 |
| Series | 00 - NIM-CAMAC |

https://www.lemo.com/int_en/solutions/specialties/00-nim-camac/ftr-00-250-nta.html

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Technical details

Electrical Configuration

| | |
|---|--------------------------|
| Nb of contacts Coax | 1 |
| Contact Termination Coax - Conductor fixing | Solder |
| R (max) | 6.1 mOhm |
| Insert configuration value | 0.25 - 1 Coax (50 Ohm) |
| Insulator | T: PTFE |
| Rated current | 4 A |
| Impedance | 50 Ohms |
| VSWR | 1.09 + 0.11 * f/GHz |
| Vtest | 2100 V (AC), 3000 V (DC) |
| Test voltage | 2.1 kV (rms) |
| Bucket Dia. | 0.6 mm (0.024in) |
| Contact Dia. | 0.7 mm (0.028in) |

Form & Material

| | |
|------------------------|---|
| Shell style / Model id | FTR - Elbow plug with receptacle |
| Plug | Elbow |
| Housing material | Brass (nickel plated [SAE AMS QQ N 290]) shell, collet nut, latch sleeve and mid pieces |
| Locking system | Push-pull |
| Keying | Circular, male |
| Colour | Grey |
| Weight | 6.51 g |

Environment

| | |
|-----------------------------------|---|
| Environmental sealing (IP rating) | IP50 |
| Endurance | 5000 mating cycles |
| Temperature range | -55°C / +260°C (max. temperature valid for short periods of use.) |
| F ret (min) | 100 N |
| Salt Spray Corrosion | >144 hr |

https://www.lemo.com/int_en/solutions/specialties/00-nim-camac/ftr-00-250-nta.html

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Cable fixation

Cable termination protection

Standard back nut (no additional protection)

Fixation type

Cable collet

https://www.lemo.com/int_en/solutions/specialties/00-nim-camac/ftr-00-250-nta.html

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.