



Connectors > Terminal Blocks & Strips > Terminal Block & Strip Accessories > Terminal Block & Strip Marking Accessories



Marking Product Type: **Marker Card**
Pre-Printed Mark Details: **N (x100)**
Primary Product Color: **White**
Product Orientation: **Vertical**
Operating Temperature Range: **-55 – 110 °C [-67 – 230 °F]**

Features

Product Type Features

Marking Product Type	Marker Card
----------------------	-------------

Configuration Features

Number of Digits per Marker - Vertical	8
Number of Digits per Marker - Horizontal	3
Number of Cards per Package	1
Pre-Printed Mark Details	N (x100)

Body Features

Product Weight	10 g[.353 oz]
Primary Product Material	Polyamide
Primary Product Color	White
Product Orientation	Vertical

Dimensions

Product Width	5.2 mm[.205 in]
Product Depth	4.8 mm
Product Length	5 mm[.197 in]
Product Height	12 mm[.472 in]

Usage Conditions

Operating Temperature Range	-55 – 110 °C[-67 – 230 °F]
-----------------------------	----------------------------



Industry Standards

UL Flammability Rating	UL 94V-2
------------------------	----------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts




Customers Also Bought






TE Part #1SNK146122R0000
MC512PA L (x100) Vertical




TE Part #RE11-442S
PLUG ASSY



TE Part #75700-1142S
PLUG ASSY



TE Part #1SNK146162R0000
MC512PA P (x100) Vertical




TE Part #34320-1
SOLIS, PARA 4 60/40 SN-PB



TE Part #7-146261-0
40 MODII HDR DRST B/A .100CL LF



TE Part #2102735-1
BP, Half Left End, MULTIGIG RT 2R



TE Part #3-2213772-1
AV22 SPL 3A MOVE RING LED
YELLOW 24V



TE Part #2488219-7
AV12 SPM 0.1A/24VDC WHITE LED
24V FLUSH



TE Part #1SNK146102R0000
MC512PA J (x100) Vertical

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1SNK146142R0000_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1SNK146142R0000_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1SNK146142R0000_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

MC512PA N (x100) Vertical

English

ENTRELEC Terminal Block - Master Catalog

1SNK146142R0000

Marker Card, N (x100) Mark Details, White, Vertical, -55 – 110 °C [-67 – 230 °F], UL 94V-2, Terminal Block & Strip Marking Accessories



[ENTRELEC Terminal Block - Master Catalog](#)

English

[SNK SERIES TERMINAL BLOCKS](#)

English

[ENTRELEC Terminal Blocks Catalogue \(RUS\)](#)