

# Data Sheet | Item Number: 2004-406/020-000

Delta jumper; insulated; light gray

<https://www.wago.com/2004-406/020-000>



Color: ■ light gray

Similar to illustration

## Electrical data

### Ratings per IEC/EN

Nominal voltage (III/3)	800 V
Rated impulse withstand voltage (III / 3)	8 kV
Rated current	32 A

## Physical data

Width	35.2 mm / 1.386 inches
Height	4.1 mm / 0.161 inches
Depth	19 mm / 0.748 inches
Jumper assignment	1-2 3-4 5-6

## Material data

Note (material data)

[Information on material specifications can be found here](#)

Color	light gray
Fire load	0.024 MJ
Weight	4.1 g

## Commercial data

PU (SPU)	25 pcs
Packaging type	Bag
Country of origin	DE
GTIN	4055143700191
Customs tariff number	85366990990

Product classification	
UNSPSC	39121421

Environmental Product Compliance	
RoHS Compliance Status	Compliant, No Exemption

## Downloads

### Environmental Product Compliance

Compliance Search	
Environmental Product Compliance 2004-406/020-000	↓

## Documentation

Bid Text			
2004-406/020-000	19.02.2019	xml 2.54 KB	↓
2004-406/020-000	28.04.2017	doc 23.50 KB	↓

## CAD/CAE-Data

CAD data	
2D/3D Models 2004-406/020-000	↓

CAE data	
EPLAN Data Portal 2004-406/020-000	↓
WSCAD Universe 2004-406/020-000	↓
ZUKEN Portal 2004-406/020-000	↓

## Installation Notes

### Commoning



This delta jumper has been specially developed to create a delta configuration and is used on motor terminal boards equipped with rail-mount terminal blocks TOPJOB® S.

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at: [www.wago.com](http://www.wago.com)