

Data Sheet | Item Number: 283-407

Power tap; with 500 mm cable; for 16 mm² (283/783 Series) and 35 mm²; gray

<https://www.wago.com/283-407>



Color: ■ gray

Notes

Safety Information

Always push voltage tap down into the terminal block until fully inserted!

Electrical data

Ratings per IEC/EN

Nominal voltage (III/3)	800 V
Rated impulse withstand voltage (III / 3)	8 kV
Rated current	24 A

Material data

Note (material data)

[Information on material specifications can be found here](#)

Color	gray
Material group	I
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	15.474 MJ
Weight	22.1 g

Environmental requirements

Processing temperature	-35 ... +85 °C
Continuous operating temperature	-60 ... +105 °C

Commercial data	
Product Group	1 (Rail Mounted Terminal Blocks)
eCl@ss 10.0	27-14-11-92
eCl@ss 9.0	27-14-11-92
ETIM 9.0	EC002848
ETIM 8.0	EC002848
PU (SPU)	25 pcs
Packaging type	Box
Country of origin	DE
GTIN	4044918853408
Customs tariff number	85366990990

Environmental Product Compliance	
RoHS Compliance Status	Compliant, No Exemption

Downloads

Environmental Product Compliance	
Compliance Search	
Environmental Product Compliance 283-407	↓

Documentation

Additional Information		Bid Text				
Technical Section	pdf 2246.92 KB	↓	283-407	19.02.2019	xml 2.81 KB	↓
			283-407	02.05.2017	doc 22.50 KB	↓

CAD/CAE-Data

CAD data		CAE data	
2D/3D Models 283-407	↓	EPLAN Data Portal 283-407	↓
		WSCAD Universe 283-407	↓

Installation Notes

Power tap



Always push voltage tap (283-407) down into the terminal block until fully inserted!

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at: www.wago.com