

## Data Sheet | Item Number: 285-168

Fixing element; for 95 mm<sup>2</sup> high-current terminal blocks; orange

<https://www.wago.com/285-168>



Color: ■ orange

### Material data

Note (material data)	<a href="#">Information on material specifications can be found here</a>
Color	orange
Material group	I
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.048 MJ
Weight	1.6 g

### Environmental requirements

Processing temperature	-35 ... +85 °C
Continuous operating temperature	-60 ... +105 °C

### Commercial data

PU (SPU)	50 (25) pcs
Packaging type	Box
Country of origin	PL
GTIN	4055143578172
Customs tariff number	39269097900

### Product Classification

UNSPSC	39121421
eCl@ss 10.0	27-14-11-92
eCl@ss 9.0	27-14-11-92
ETIM 9.0	EC002848
ETIM 10.0	EC002848
ECCN	NO US CLASSIFICATION

**Environmental Product Compliance**

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

**Downloads**

**Environmental Product Compliance**

Compliance Search

Environmental Product Compliance 285-168	<a href="#">↓</a>
--	-------------------

**Documentation**

Bid Text

285-168	01.07.2019	xml 2.72 KB	<a href="#">↓</a>
285-168	01.07.2019	doc 22.00 KB	<a href="#">↓</a>
285-168	01.07.2019	docx 13.49 KB	<a href="#">↓</a>

**CAD/CAE-Data**

CAD data

2D/3D Models 285-168	<a href="#">↓</a>
----------------------	-------------------

CAE data

EPLAN Data Portal 285-168	<a href="#">↓</a>
---------------------------	-------------------

**Installation Notes**

**Installation**



Optionally, insert block-to-block connector (285-168) into housing slot.



Align and snap high-current, through terminal blocks together.