



Color: ■ silver-colored

Electrical data

Ratings per IEC/EN

Nominal voltage (III/3)	1000 V
Rated current	125 A

Ratings per UL

Rated voltage UL (Use Group B)	1000 V
Rated current UL (Use Group B)	130 A
Rated voltage UL (Use Group C)	1000 V
Rated current UL (Use Group C)	130 A
Rated voltage UL (Use Group D)	1000 V
Rated current UL (Use Group D)	130 A

Ratings per CSA

Rated voltage CSA (Use Group B)	1000 V
Rated current CSA (Use Group B)	115 A
Rated voltage CSA (Use Group C)	1000 V
Rated current CSA (Use Group C)	115 A
Rated voltage CSA (Use Group D)	1000 V
Rated current CSA (Use Group D)	115 A

Material data

Note (material data)	Information on material specifications can be found here
Color	silver-colored
Fire load	0 MJ
Weight	14.4 g

Commercial data

PU (SPU)	10 pcs
Packaging type	Bag
Country of origin	DE
GTIN	4055143941907
Customs tariff number	85366990990

Product Classification	
UNSPSC	39121410
ETIM 9.0	EC000489
ETIM 8.0	EC000489
ECCN	NO US CLASSIFICATION

Environmental Product Compliance	
RoHS Compliance Status	Compliant, No Exemption

Downloads

Environmental Product Compliance

Compliance Search
Environmental Product Compliance 884-3542 

CAD/CAE-Data

CAD data
2D/3D Models 884-3542 

CAE data
EPLAN Data Portal 884-3542 
ZUKEN Portal 884-3542 