



△

	Dim A	Dim B
2-6p	±0.15	±0.15
7-12p	±0.20	±0.20
13-18p	±0.25	±0.25
19-24p	±0.30	±0.30

N = Number of poles
 Dim A = N x 3.81
 Dim B = (N-1) x 3.81

SIGN	DATE	DESCRIPTION	APPROVER
△	11/01'05	Electrical standard changed.	Marvin
△	04/20'06	2p to 6p with wedge is changed.	Marvin
△	8/13'06	Added VDE standard	黎仁松
△	12/04'08	Add the tolerance table	Jacke
△	12/04'08	The temperature changed from -30°,105° to -40°,115°	Jacke
△	12/04'08	The wire entry hole was changed.	Jacke
△	2010.07.12	The solid and Stranded wire is changed from 16-26 to 16-28	Chen Bo
△	2010.07.12	Remove the CSA mark	Chen Bo

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material

- Item a Clamp: Brass(CuZn) Ni plated
- Item b Terminal screw: Steel Zinc plating "-" slot type
- Item c Female contact: PhBz ,Tin plated
- Item d Terminal (housing): Thermoplastic (UL94V-0)
- Item e Terminal (cover): Thermoplastic (UL94V-0)

△ △ Electrical cULus/VDE

- Voltage rating: 300VAC/300VAC
- Current rating: 10A/10.5A
- Wire range: 1.5mm²
- △ ● Solid wire(AWG): 16-28/16-28
- Stranded wire(AWG): 16-28/16-28
- Torque: 3Lb-In/0.2Nm
- Screw: M2
- Wire strip length: 6-7mm
- Withstanding Voltage: 1.6KV/2.5KV
- △ ● Operating temperature: -40°C to +115°C
- △ ● Safety Approval:

TJ xx 31x 3 xxxx G

- | | | | | |
|-----|-------------|---|-------------------|---------------------------------------|
| 02 | 2 CONTACTS | 0 | Black (RAL9005) | RoHS |
| 03 | 3 CONTACTS | 2 | Red (RAL3001/D) | Pb<40,000ppm |
| ... | ... | 3 | Orange(RAL2011/P) | 0000: "@" Logo |
| 24 | 24 CONTACTS | 4 | Yellow(RAL1018/A) | 000A: "ANYTEK" Mark |
| | | 5 | Green(RAL6018/T) | Any special item by customer request. |
| | | 6 | Blue (RAL5015/A) | please contact sales department. |
| | | 8 | Grey(RAL7035/D) | |

ANYTEK				CUSTOMER COPY			
ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD							
TITLE		TJ-3.81mm Series		DWG NO.		8TJ0601	
PART NO.		TJxx31x3xxxxG		CUST NO.			
APPROVED	CHECKED	DESIGNED	DRAWN	Tolerance			
			Chen Bo 2010.07.12			UNIT: mm SCALE: NONE REV.: H	
				SHEET: 01/01		X. ±0.50 X.X ±0.30 X.XX ±0.10 X° ±1°	