

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: USB 3.1TYPE-C connector female connector 6P four pin plug, on board type (no bullet)	
	Model No. Connector	Part No./Ordering No. JACK-USBC-061SMT-4BVC11
		Rev A3

In Addition to GlobTek Inc.'s renewed ISO9001:2008 - Quality Management System Certification, GlobTek Inc. is now certified to:

- ISO13485:2003 - Medical Devices Quality Management System Certification
- ISO14001:2004 - Environmental Management System Certification

ISO Certificates are available online at <http://www.globtek.com/iso-certificates/>

The acceptance of this specification and use of the product described in this document indicates the acceptance and binding of the customer to Globtek TERMS AND CONDITIONS (attached to the end of this document), which supersede all other agreements, terms, and conditions (<http://www.globtek.com/terms-and-conditions/>).

Prop 65 Statement:<https://www.globtek.com/prop-65-statement.pdf>

Footnote:

GlobTek Inc. will not be liable for the safety and performance of these power supplies if unauthorized access and repair occurs. End user should consult applicable UL, CSA or EN standards for proper installation instruction.

Limitation of Use:

GlobTek products are intended for use with commercial, medical, and/or industrial equipment only. GlobTek product are not authorized for use as mission critical components in life support hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of GlobTek Inc.

Contents of this document are subject to change without prior notice.

Customer Approval of Specification:

Please approve, sign and send back to GlobTek so we can complete order processing.

A delay in receipt of this form will delay delivery schedule.

Company Name: _____	Customer P/N: _____
Quote Number: _____	Date: _____
Authorized Representative Name: _____	Authorized Representative Signature: _____

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: USB 3.1TYPE-C connector female connector 6P four pin plug, on board type (no bullet)	
	Model No. Connector	Part No./Ordering No. JACK-USBC-061SMT-4BVC11
		Rev A3

REVISION HISTORY

REV	DESCRIPTION	SUB	DATE	APPROVED
A3	Add MOQ, MPQ data	QA	02/09/2025	QA
A2	Update the box quantity information	QA	06/20/2024	QA
A1	Update Product description in the Drawing title	QA	06/06/2024	QA
A	Initial release	QA	08/03/2022	QA

3D CAD FILE:

https://www.globtek.com/file/dl/jack-usbc-061smt-4bvc11_asm.stp

AGENCY ONLINE DOCUMENTS


RoHS/RoHS3 Declaration https://www.globtek.com/pdf/rohs_cert/01t3a000005hbPJAAY

REACH Declaration <https://www.globtek.com/r2/eM2co8>

Conflict Minerals Declaration <https://www.globtek.com/r2/SNw6P3>

Prop 65 Statement <https://www.globtek.com/r2/VMPRnr>

IPXY rating is based on 3rd party testing and customers should check suitability and test system level IPXY rating before ordering.



PROPRIETARY INFORMATION

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC. © GlobTek, Inc. 2022 - 2025

Page 2 of 5

quest /11/19/2025 7:39:03 AM CLONED FROM JACK-USBC-243SMT-3BVC84

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: USB 3.1TYPE-C connector female connector 6P four pin plug, on board type (no bullet)	
	Model No. Connector	Part No./Ordering No. JACK-USBC-061SMT-4BVC11
		Rev A3

NOTES:

1.MATERIAL:

MOLDING: LCP UL94V-0

CONTACT: COPPER ALLOY.

2. Finished: contact area: plating Au 0.8u",
solder tail: plating Au 0.8u", all plating Ni 40u"
SHELL: SUS201-1/2HT=0.30+0.03mm
50U' NICKEL PLATING OVER ALL.

3.MECHANICAL:

INSERTION: 5~20N.

EXTRACTION: 8~20N AFTER TEST.

DURABILITY: 8000 CYCLES

4.ELECTRICAL:

CURRENT: 5A FOR VBUS:

1.25A FOR GND PIN

0.25A FOR OTHER

VOLTAGE: 20 V MAX

WITHSTANDING VOLTAGE: 100V AC R.M.S.

CONTACT RESISTANCE: 40mΩ MAX.

INSULATION RESISTANCE: 100MΩ MIN.

5.ENVIRONMENTAL

TEMPERATURE RATING: -25°C ~ +85°C

Temperature Life, Vibration, Cyclic Temperature and Humidity, Thermal Shock, Mixed Flowing Gas and etc.:

<https://www.globtek.com/pdf/ENVIRONMENTAL.pdf>

GlobTek, Inc.
 www.globtek.com
 186 Veterans Drive,
 Northvale, NJ 07647
 Tel. (201) 784-1000
 Fax (201) 784-0111


Drawing Title: USB 3.1TYPE-C connector female connector 6P four pin plug, on board type (no bullet)

Model No. [Connector](#)

Part No./Ordering No. [JACK-USBC-061SMT-4BVC11](#)

Rev A3

Packing:



- Notes:
1. The start and end of each reel, based on the actual quantity, reserved 50pcs space;
 2. Peel off force of top tape: 10g~130g, peel deg.:165°~175°; peel speed: 250~300mm/min;
 3. Carton size: 340*340*200mm; ed
 4. QTY: 1000pcs/reel, 5reel/carton, total5000pcs/carton;

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: USB 3.1TYPE-C connector female connector 6P four pin plug, on board type (no bullet)	
	Model No. Connector	Part No./Ordering No. JACK-USBC-061SMT-4BVC11
		Rev A3

PACKAGING

Packing Spec P/N:

Box Qty: 1000

Gift Box Size (mm):

Gift Box Color: White

Master Carton Size (mm): 340 x 340 x 220

Master Carton Cubic Volume (m³): 0.03

Master GW (Kg): 8.0 kg

wt Ea. (Kg): 0.01 kg

wt Ea. (Kg): 0.02 kg

LABEL SPECS: ,

PACK SPEC: