




Connectors > PCB Connectors > Battery Connectors & Holders > Battery Holders



Battery Compatibility: **CR2032**

Number of Positions: **2**

PCB Mount Orientation: **Vertical**

Contact Mating Area Plating Material: **Gold (Au)**

PCB Mount Alignment: **Without**

Features

Product Type Features

Connector & Contact Terminates To	Printed Circuit Board
Connector System	Board-to-Board

Configuration Features

Number of Positions	2
PCB Mount Orientation	Vertical

Body Features

Primary Product Color	Blue
Battery Holder Type	Coin Cell
Battery Holder Material	Glass Filled Nylon 66
Battery Compatibility	CR2032

Contact Features

Contact Underplating Material	Nickel
Contact Mating Area Plating Material	Gold (Au)
Contact Current Rating (Max)	7 A

Mechanical Attachment



Connector Mounting Type	Board Mount
-------------------------	-------------

PCB Mount Alignment	Without
---------------------	---------

Dimensions

Compatible Battery Dimensions	23 x 18.49 x 21 mm [.906 x .728 x .827 in]
-------------------------------	--

Usage Conditions

Operating Temperature Range	-55 – 105 °C [-67 – 221 °F]
-----------------------------	-----------------------------

Operation/Application

Circuit Application	Signal
---------------------	--------

Packaging Features

Packaging Method	Box & Tray
------------------	------------

Packaging Quantity	80
--------------------	----

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
------------------------------	-----------

EU ELV Directive 2000/53/EC	Out of Scope
-----------------------------	--------------

China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
---	---

EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
--	---

Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
-----------------	--

Solder Process Capability	Wave solder capable to 265°C
---------------------------	------------------------------

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 2-1775485-2
Battery Holder, 3.6mm, BLU,low profile



TE Part # 796136-1
ASSY, SMT BATTERY CONN



TE Part # 3-1775485-2
BATTERY HOLDER, 3.6MM, BLACK, LOW PROFILE



TE Part # 120591-1
TOP LOAD BATTERY

Customers Also Bought



TE Part #CAT-DMC-MD-24
Rectangular Connector Receptacles, Tool-less Assembly



TE Part #5-146130-6
14 MODII HDR DRST SFMNT B/A LF



TE Part #5-147279-5
20 MODII HDR DR SFMT B/A T&R LF



TE Part #440053-2
2.5MM,HDR,2POS,R/A



TE Part #1-2176584-7
RLC73PD 2B R887 1% 1K RL



TE Part #1-2324271-3
RIGHT SEGMENT LGA4189-4 SOCKETP4 FOR ODM



TE Part #1-2324271-4
LEFT SEGMENT LGA4189-4 SOCKET-P4 FOR ODM



TE Part #2369317-1
16G 05FH 8H plug aassy 440POS 8u" Au

Documents

Product Drawings

Battery Holder, 3.6mm, BLU,low profile

English

CAD Files

3D PDF

3D

Customer View Model

[ENG_CVM_CVM_1775485-2_A.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1775485-2_A.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1775485-2_A.3d_stp.zip](#)



English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

[Product Specifications](#)

[Application Specification](#)

English