

# R-78K-1.0 series $\diamond$ Switching Regulator

1.0Amp  $\diamond$  Single Output  $\diamond$  SIP3

## FEATURES

- Efficiency up to 96%, no need for heat-sinks
- 4.5-36VDC wide input voltage
- -40°C to +90°C ambient operation without derating
- Pin compatible with 78 series regulators
- Non isolated DC/DC converter
- Undervoltage and short circuit protection
- 3 year warranty



Dimensions (LxWxH): 11.5 x 7.55 x 10.2mm (0.45 x 0.30 x 0.40 inch)  
1.7g (0.038 lbs)

## APPLICATIONS



## SAFETY & EMC



## DESCRIPTION

The R-78K-1.0 series is a switching regulator module that has been designed to offer all the advantages of a switching regulator (high efficiency, wide input range, accurate output voltage regulation) but with a low cost for production quantities. Due to the R-78K-1.0's high efficiency of up to 95% no heat-sink is required, and operation from -40 to 90°C is possible with slight derating. The compact TO-220 compatible SIP3 package measures only 11.5 x 7.55 x 10.2mm, so it saves precious board space.


## SELECTION GUIDE

| Part Number  | Input Voltage Range [VDC] | Output Voltage nom. [VDC] | Output Current max. [mA] | Efficiency     |                |
|--------------|---------------------------|---------------------------|--------------------------|----------------|----------------|
|              |                           |                           |                          | @ min. Vin [%] | @ max. Vin [%] |
| R-78K1.8-1.0 | 4.5-36                    | 1.8                       | 1000                     | 83             | 71             |
| R-78K2.5-1.0 | 4.5-36                    | 2.5                       | 1000                     | 85             | 75             |
| R-78K3.3-1.0 | 4.5-36                    | 3.3                       | 1000                     | 88             | 79             |
| R-78K5.0-1.0 | 6.5-36                    | 5                         | 1000                     | 92             | 85             |
| R-78K9.0-1.0 | 12-36                     | 9                         | 1000                     | 93             | 89             |
| R-78K12-1.0  | 15-36                     | 12                        | 1000                     | 95             | 91             |
| R-78K15-1.0  | 18-36                     | 15                        | 1000                     | 94             | 91             |

# R-78K-1.0 series $\diamond$ Switching Regulator

## 1.0Amp $\diamond$ Single Output $\diamond$ SIP3

### MODEL NUMBERING



### ABSOLUTE MAX. RATINGS (exceeding these ratings may damage the device)

| Parameters                                     | Condition               | Min.  | Typ. | Max.           |
|--|-------------------------|-------|------|----------------|
| Maximum Input Voltage Slew Rate <sup>(1)</sup> | +V <sub>IN</sub> to GND |       |      | 10VDC/ $\mu$ s |
| Case Temperature                               |                         | -40°C |      | 110°C          |
| Storage Temperature                            |                         | -50°C |      | 125°C          |



Note1: At higher slew rates or hard plugging, add 27 $\mu$ F E-Cap between +V<sub>in</sub> and GND, especially when V<sub>in</sub> is >18VDC

### BASIC CHARACTERISTICS (measured @ T<sub>AMB</sub>= 25°C, nom. V<sub>IN</sub>, full load and after warm-up unless otherwise stated)

| Parameter                              | Condition                                | Min.                        | Typ.     | Max.    |     |
|--|--|-----------------------------|----------|---------|-----|
| Input Under Voltage Lockout (UVLO)     | R-78K1.8-1.0, R-78K2.5-1.0, R-78K3.3-1.0 | DC-DC ON                    | 3.75VDC  | 4.05VDC |     |
|  |  | DC-DC OFF                   | 3.6VDC   | 3.8VDC  |     |
|  | R-78K5.0-1.0                             | DC-DC ON                    | 5VDC     | 5.25VDC |     |
|  |  | DC-DC OFF                   | 4.6VDC   | 4.9VDC  |     |
|  | R-78K9.0-1.0                             | DC-DC ON                    | 9.5VDC   | 10.5VDC |     |
|  |  | DC-DC OFF                   | 9.1VDC   | 9.7VDC  |     |
|  | R-78K12-1.0                              | DC-DC ON                    | 13.0VDC  | 13.5VDC |     |
|  |  | DC-DC OFF                   | 12.5VDC  | 13.1VDC |     |
|  | R-78K15-1.0                              | DC-DC ON                    | 16.9VDC  | 17.5VDC |     |
|  |  | DC-DC OFF                   | 15.6VDC  | 16.6VDC |     |
|  | Quiescent Current                        |                             |          |         | 1mA |
|  | Internal Operating Frequency             |                             |          | 400kHz  |     |
| Minimum Load                           |  | 0%                          |          |         |     |
| Output Ripple and Noise <sup>(2)</sup> | 20MHz BW                                 | R-78K1.8-1.0 - R-78K5.0-1.0 | 50mVp-p  |         |     |
|  |  | R-78K9.0-1.0                | 60mVp-p  |         |     |
|  |  | R-78K12-1.0                 | 75mVp-p  |         |     |
|  |  | R-78K15-1.0                 | 100mVp-p |         |     |

Note2: The test setup can have an impact on ripple noise values (placement of scope probe, capacitors, it's specifications, wires, PCB tracks, distances, etc.)

#### R-78K1.8-1.0





# R-78K-1.0 series $\diamond$ Switching Regulator



1.0Amp  $\diamond$  Single Output  $\diamond$  SIP3

**BASIC CHARACTERISTICS** (measured @  $T_{AMB}=25^{\circ}C$ , nom.  $V_{IN}$ , full load and after warm-up unless otherwise stated)



### R-78K2.5-1.0



### R-78K3.3-1.0



### R-78K5.0-1.0





# R-78K-1.0 series $\diamond$ Switching Regulator



1.0Amp  $\diamond$  Single Output  $\diamond$  SIP3

**BASIC CHARACTERISTICS** (measured @  $T_{AMB} = 25^{\circ}\text{C}$ , nom.  $V_{IN}$ , full load and after warm-up unless otherwise stated)



## R-78K9.0-1.0



## R-78K12-1.0



## R-78K15-1.0



# R-78K-1.0 series $\diamond$ Switching Regulator

## 1.0Amp $\diamond$ Single Output $\diamond$ SIP3

### REGULATIONS

| Parameter       | Condition                        | Value                               |
|-----------------|----------------------------------|-------------------------------------|
| Output Accuracy |                                  | $\pm 2.0\%$ typ. / $\pm 3.5\%$ max. |
| Line Regulation | low line to high line, full load | $\pm 0.5\%$ max.                    |
| Load Regulation | 0% to 100%                       | 2.0% typ. / 3.5% max.               |


### PROTECTIONS

| Parameter                      | Condition | Value                          |
|--------------------------------|-----------|--------------------------------|
| Short Circuit Protection (SCP) |           | continuous, automatic recovery |
| Short Circuit Input Current    |           | 50mA max.                      |

#### Optional Diode Protection Circuit

Add a blocking diode to Vout if current can flow backwards into the output, as this can damage the converter when it is powered down.

The diode can either be fitted across the device if the source is low impedance or fitted in series with the output (recommended).





### ENVIRONMENTAL

| Parameter                         | Condition                               | Value                                   |                              |
|-----------------------------------|---|---|------------------------------|
| Operating Temperature Range       | refer to „Derating Graph“               | -40°C to +100°C                         |                              |
| Maximum Case Temperature          |   | +110°C                                  |                              |
| Temperature Coefficient           |   | 0.01%/K                                 |                              |
| Operating Altitude <sup>(3)</sup> |   | 5000m max.                              |                              |
| Operating Humidity                | non-condensing                          | 95% RH max.                             |                              |
| Vibration                         |   | 10-55Hz, 2G, 30min along X,Y and Z axis |                              |
| MTBF                              | according to MIL-HDBK-217F, G.B., +25°C | R-78K1.8-1.0                            | 5139 x 10 <sup>3</sup> hours |
|                                   |   | R-78K2.5-1.0                            | 4990 x 10 <sup>3</sup> hours |
|                                   |   | R-78K3.3-1.0                            | 4878 x 10 <sup>3</sup> hours |
|                                   |   | R-78K5.0-1.0                            | 5031 x 10 <sup>3</sup> hours |
|                                   |   | R-78K9.0-1.0                            | 4546 x 10 <sup>3</sup> hours |
|                                   |   | R-78K12-1.0                             | 4340 x 10 <sup>3</sup> hours |
|                                   |   | R-78K15-1.0                             | 4546 x 10 <sup>3</sup> hours |

Note3: For altitude higher than 2000m, 5% power derating for every 1000m

#### Derating Graph

(@ Chamber and natural convection 0.1m/s)







# R-78K-1.0 series $\diamond$ Switching Regulator

## 1.0Amp $\diamond$ Single Output $\diamond$ SIP3

### ENVIRONMENTAL

#### Derating Graph

(@ Chamber and natural convection 0.1m/s)



### SAFETY AND CERTIFICATIONS

#### Certificate Type (Safety)

Audio/Video, information and communication technology equipment - Part 1: Safety requirements (CB Scheme)

Audio/Video, information and communication technology equipment - Part 1: Safety requirements

RoHS2

#### Report Number

085-210593601-100

#### Standard

IEC62368-1:2018 3rd Edition

EN IEC 62368-1:2020+A11:2020

RoHS 2011/65/EU + AM2015/863

#### EMC Compliance

Electromagnetic compatibility of multimedia equipment - Emission requirements


#### Condition

with external filter

#### Standard /Criterion

EN55032, Class B

#### EMC Filtering Suggestions according to EN55032



#### Component List Class B for 1.8V, 2.5V, 3.3V version


| C1         | L1                      | C2  |
|------------|-------------------------|-----|
| 10 $\mu$ F | <a href="#">RLS-186</a> | 1nF |

# R-78K-1.0 series $\diamond$ Switching Regulator

## 1.0Amp $\diamond$ Single Output $\diamond$ SIP3

### SAFETY AND CERTIFICATIONS

EMC Filtering Suggestions according to EN55032



Component List Class B for 5V, 12V & 15V version



| C1/C2      | L1                      | C3         | C4  | L2                      |
|------------|-------------------------|------------|-----|-------------------------|
| 10 $\mu$ F | <a href="#">RLS-397</a> | 22 $\mu$ F | 1nF | <a href="#">RLS-186</a> |

### DIMENSION & PHYSICAL CHARACTERISTICS

| Parameter         | Type    | Value   |
|-------------------|---------|---|
| Materials         | case    | black plastic, (UL94 V-0)                       |
|                   | potting | PU, (UL94 V-0)                                  |
|                   | PCB     | FR4, (UL94 V-0)                                 |
| Dimension (LxWxH) |         | 11.5 x 7.55 x 10.2mm<br>0.45 x 0.30 x 0.40 inch |
| Weight            |         | 1.7g typ.<br>0.038 lbs                          |

### DIMENSION & PHYSICAL CHARACTERISTICS

Dimension Drawing



Pinning information

| Pin # | Single     |
|-------|------------|
| 1     | $+V_{IN}$  |
| 2     | GND        |
| 3     | $+V_{OUT}$ |

Tolerances:  
x.x=  $\pm 0.5$ mm  
x.xx=  $\pm 0.25$ mm

### PACKAGING INFORMATION

| Parameter                   | Type           | Value                |
|-----------------------------|----------------|----------------------|
| Packaging Dimension (LxWxH) | tube           | 520.0 x 9.2 x 19.0mm |
| Packaging Quantity          |                | 43pcs                |
| Storage Temperature Range   |                | -50°C to +125°C      |
| Storage Humidity            | non-condensing | 95% RH max.          |

The product information and specifications may be subject to changes even without prior written notice. The product has been designed for various applications; its suitability lies in the responsibility of each customer. The products are not authorized for use in safety-critical applications without RECOM's explicit written consent. A safety-critical application is an application where a failure may reasonably be expected to endanger or cause loss of life, inflict bodily harm or damage property. The applicant shall indemnify and hold harmless RECOM, its affiliated companies and its representatives against any damage claims in connection with the unauthorized use of RECOM products in such safety-critical applications.