

GloTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: GT-86182-1812-W2E-USB, ICT/ITE Power Supply, Efficiency Level: USA DOE Level VI / Eco-design Directive 2009/125/EC, (EU) 2019/1782, Case Color/Style: GlobTek Black, Wall Plug-in, USB Adaptive Power Supply AC Adaptor, Input Rating: 100-240V- , 50/60Hz, Euro Plug Fixed , Output Rating: 18W, 5.0V / 9.0V / 12.0VV@3.0A / 2.0A / 1.5AA, Output Configuration: N/A mm, N/A/ Cond, N/A, Type "A" USB "and"A" USB (USB battery charging BC1.2 compliant) Female Sockets integral to power supply enclosure, Ferrite: None, N/A, GT Cord # C72386, Pin Out: USBA Pin 1: (+), Pin 2: D-, Pin 3: D+, Pin 4: Com, Blades/Input Cord: Fixed Blades Europlug 2 pins, Class II, Approvals: CE; China RoHS; Double Insulation; EAC; WEEE; LPS 60950; RoHS; Ukraine; Morocco;	
	Model No. GT-86182-1812-W2E-USB	
	Part No./Ordering No. WR9MZ1500USBAFR6B	Rev A1

In Addition to GlobTek Inc.'s renewed ISO9001:2015 - Quality Management System Certification, GlobTek Inc. is now certified to:

ISO13485:2016 - Medical Devices Quality Management System Certification  
ISO14001:2015 - Environmental Management System Certification

ISO Certificates are available online at <https://www.globtek.com/iso-certificates/>

The acceptance of this specification and use of the product described in this document indicates the acceptance and binding of the customer to Globtek TERMS AND CONDITIONS (attached to the end of this document), which supersede all other agreements, terms, and conditions (<https://en.globtek.com/terms-and-conditions/>).

The purchaser of this product (Customer) agrees that it is their sole responsibility to determine suitability/fitness of the product described in this specification for their application and to take precautions for protection against any hazards attendant to the handling and use of the product.

Footnote:

GlobTek Inc. will not be liable for the safety and performance of these power supplies/battery packs if unauthorized access and repair occurs. End user should consult applicable UL, CSA or EN standards for proper installation instruction.

Limitation of Use:

GlobTek products are intended for use with commercial, medical, and/or industrial equipment only. GlobTek product are not authorized for use as mission critical components in life support hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of GlobTek Inc.

Contents of this document are subject to change without prior notice.

### Customer Approval of Specification:

Please approve, sign and send back to GlobTek so we can complete order processing.  
A delay in receipt of this form will delay delivery schedule.

Company Name: _____	Customer P/N: _____
Quote Number: _____	Date: _____
Authorized Representative Name: _____	Authorized Representative Signature: _____

**RELEASED**  
By pudxc at 8:44 am, Jun 12, 2023

GloTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: GT-86182-1812-W2E-USB, ICT/ITE Power Supply, Efficiency Level: USA DOE Level VI / Eco-design Directive 2009/125/EC, (EU) 2019/1782, Case Color/Style: GlobTek Black, Wall Plug-in, USB Adaptive Power Supply AC Adaptor, Input Rating: 100-240V- , 50/60Hz, Euro Plug Fixed , Output Rating: 18W, 5.0V / 9.0V / 12.0VV@3.0A / 2.0A / 1.5AA, Output Configuration: N/A mm, N/A/ Cond, N/A, Type "A" USB "and"A" USB (USB battery charging BC1.2 compliant) Female Sockets integral to power supply enclosure, Ferrite: None, N/A, GT Cord # C72386, Pin Out: USBA Pin 1: (+), Pin 2: D-, Pin 3: D+, Pin 4: Com, Blades/Input Cord: Fixed Blades Europlug 2 pins, Class II, Approvals: CE; China RoHS; Double Insulation; EAC; WEEE; LPS 60950; RoHS; Ukraine; Morocco;	
	Model No. GT-86182-1812-W2E-USB	
	Part No./Ordering No. WR9MZ1500USBAFR6B	Rev A1

## REVISION HISTORY

REV	DESCRIPTION	SUB	DATE	APPROVED
A1	Update Input from 0.6A to 0.8A	QA	06/08/2023	QA
A	Initial release	dhock	04/20/2023	DOROTHEA

### POWER SUPPLY INFORMATION

TYPE	Wall Plug-in
TECHNOLOGY	USB Adaptive Power Supply AC Adaptor
CASE COLOR	GlobTek Black
NAMEPLATE RATED INPUT	100-240V- , 50/60Hz, 0.8 A
INPUT CONFIG	Euro Plug Fixed
WATTS	18.00
VOLTS OUT	5.0V / 9.0V / 12.0V
CURRENT OUT (Amps)	3.0A / 2.0A / 1.5A
BLADE/CORD INCLUDED	FBEU Fixed Blades Europlug 2 pins, Class II
INGRESS PROTECTION	Indoor Use
GROUNDING CONFIGURATION	(F1) Class II / Double Insulated
EFFICIENCY LEVEL	USA DOE Level VI / Eco-design Directive 2009/125/EC, (EU) 2019/1782
OUTPUT CONFIGURATION	N/A mm, N/A/ Cond, N/A, Type "A" USB "and"A" USB (USB battery charging BC1.2 compliant) Female Sockets integral to power supply enclosure, Ferrite: None, N/A, GT Cord # C72386
OVERMOLDED	No
OUTPUT CONNECTOR GENDER	Female
CONNECTOR PIN OUT	USBA Pin 1: (+), Pin 2: D-, Pin 3: D+, Pin 4: Com
LABEL SPECS	Standard GT,L-1186
SPECIAL BARCODE LABEL MATERIAL	No
PACK SPEC	Standard WPI, Individually Box
USER MANUAL	

<b>GlobTek, Inc.</b> <b>www.globtek.com</b> <b>186 Veterans Drive,</b> <b>Northvale, NJ 07647</b> <b>Tel. (201) 784-1000</b> <b>Fax (201) 784-0111</b>	Drawing Title: GT-86182-1812-W2E-USB, ICT/ITE Power Supply, Efficiency Level: USA DOE Level VI / Eco-design Directive 2009/125/EC, (EU) 2019/1782, Case Color/Style: GlobTek Black, Wall Plug-in, USB Adaptive Power Supply AC Adaptor, Input Rating: 100-240V- , 50/60Hz, Euro Plug Fixed , Output Rating: 18W, 5.0V / 9.0V / 12.0VV@3.0A / 2.0A / 1.5AA, Output Configuration: N/A mm, N/A/ Cond, N/A, Type "A" USB "and"A" USB (USB battery charging BC1.2 compliant) Female Sockets integral to power supply enclosure, Ferrite: None, N/A, GT Cord # C72386, Pin Out: USBA Pin 1: (+), Pin 2: D-, Pin 3: D+, Pin 4: Com, Blades/Input Cord: Fixed Blades Europlug 2 pins, Class II, Approvals: CE; China RoHS; Double Insulation; EAC; WEEE; LPS 60950; RoHS; Ukraine; Morocco;	
	Model No. GT-86182-1812-W2E-USB	
	Part No./Ordering No. WR9MZ1500USBAFR6B	Rev A1

Notes/Modifications/Customizations (notes in this section supersede the values shown in the standard spec)

DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE


GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: GT-86182-1812-W2E-USB, ICT/ITE Power Supply, Efficiency Level: USA DOE Level VI / Eco-design Directive 2009/125/EC, (EU) 2019/1782, Case Color/Style: GlobTek Black, Wall Plug-in, USB Adaptive Power Supply AC Adaptor, Input Rating: 100-240V- , 50/60Hz, Euro Plug Fixed , Output Rating: 18W, 5.0V / 9.0V / 12.0VV@3.0A / 2.0A / 1.5AA, Output Configuration: N/A mm, N/A/ Cond, N/A, Type "A" USB "and"A" USB (USB battery charging BC1.2 compliant) Female Sockets integral to power supply enclosure, Ferrite: None, N/A, GT Cord # C72386, Pin Out: USBA Pin 1: (+), Pin 2: D-, Pin 3: D+, Pin 4: Com, Blades/Input Cord: Fixed Blades Europlug 2 pins, Class II, Approvals: CE; China RoHS; Double Insulation; EAC; WEEE; LPS 60950; RoHS; Ukraine; Morocco;	
	Model No. GT-86182-1812-W2E-USB	
	Part No./Ordering No. WR9MZ1500USBAFR6B	Rev A1

## ELECTRICAL SPECIFICATIONS

### A) ELECTRICAL SPECIFICATIONS:

01. Input Voltage: Specified 90-264 Vac, Nameplate rated: 100-240Vac
02. Input Frequency: Specified 47-63 Hz, Nameplate rated 50-60Hz
03. Inrush Current: at full load, 25° C, cold start
04. Efficiency: Compliant with Efficiency Level VI and ErP European Commission's Ecodesign Directive (2005/32/EC) / CoC Tier 2 Compliant
05. No Load Standby Power: <0.075W @ 230Vac
06. Line regulation:  $\pm 2\%$  At nominal input voltage and full load
07. Total output regulation:  $\pm 5\%$
08. Output Voltage: Tolerance  $\pm 5\%$
09. Turn On Delay: 3 Seconds maximum at nominal input Voltage
10. Hold Up Time: 5ms min at nominal Input Voltage
11. Ripple Voltage: 200 mVp-p At 20 MHz, and output parallel with 0.1uF & 10uF capacitors to ground Temperature at 25°C, and nominal input voltage
12. Compliant with CLASS A Qualcomm Quick Charge 3.0 and Quick Charge 2.0. 3.6V~12V DC with 18 watts maximum output. Also compliant with BC1.2, APPLE 2.4A., SAMSUNG 2.0A, FCP, SFCP, AFC

## Quick Charger 3.0 protocol



### B) PROTECTION

01. Over voltage protection: Output shut down and auto restart
02. Short circuit protection: The adapter shall not be damaged by short the DC output to Ground
03. Over Load Protection: Output shut down and auto restart

### C) SAFETY

#### PROPRIETARY INFORMATION

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN

WRITING BY GLOBTEK, INC. © GlobTek, Inc. 2023 - 2023

specC / 06/09/2023 6:37:13 AM GMT

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: GT-86182-1812-W2E-USB, ICT/ITE Power Supply, Efficiency Level: USA DOE Level VI / Eco-design Directive 2009/125/EC, (EU) 2019/1782, Case Color/Style: GlobTek Black, Wall Plug-in, USB Adaptive Power Supply AC Adaptor, Input Rating: 100-240V- , 50/60Hz, Euro Plug Fixed , Output Rating: 18W, 5.0V / 9.0V / 12.0VV@3.0A / 2.0A / 1.5AA, Output Configuration: N/A mm, N/A/ Cond, N/A, Type "A" USB "and"A" USB (USB battery charging BC1.2 compliant) Female Sockets integral to power supply enclosure, Ferrite: None, N/A, GT Cord # C72386, Pin Out: USBA Pin 1: (+), Pin 2: D-, Pin 3: D+, Pin 4: Com, Blades/Input Cord: Fixed Blades Europlug 2 pins, Class II, Approvals: CE; China RoHS; Double Insulation; EAC; WEEE; LPS 60950; RoHS; Ukraine; Morocco;	
	Model No. GT-86182-1812-W2E-USB	
	Part No./Ordering No. WR9MZ1500USBAFR6B	Rev A1

01. HI-POT : Input to output : 3000VAC or 4242VDC 10mA 1 minute
02. Leakage current: 0.25mA maximum, at nominal AC input voltage and frequency
03. ESD: 8KV(air) / 4KV (contact)

D) EMC

01. Emissions, per EN 55032, EN 61000-6-3, EN 61000-6-4
  - Conducted Emissions: Class B, FCC Part 15, Class B
  - Radiated Emissions: Class B, FCC Part 15, Class B
02. Line Frequency Harmonics EN61000-3-2, Class A
03. Voltage Fluctuations/Flicker EN61000-3-3
04. Immunity, per EN 55024, EN 61000-6-1, EN 61000-6-2
  - Static Discharge Immunity EN61000-4-2, 4kV Contact Discharge, 8kV air discharge
  - Radiated RF Immunity EN61000-4-3, 3V/m 80-1000MHz, 80% 1KHz AM.
  - EFT/Burst Immunity EN61000-4-4, 1kV/100kHz.
  - Line Surge Immunity EN61000-4-5, 1kV differential, 2kV common-mode
  - Conducted RF Immunity EN61000-4-6, 3Vrms, 80% 1KHz AM
  - Power Frequency Magnetic Field Immunity EN61000-4-8, 1A/m
  - Voltage Dip Immunity EN61000-4-11, Criteria

E) OTHER:

01. MTBF: 200,000 Hours @ 25°C ambient temperature
02. Operating Temperature: 0°C to 40°C ambient temperature
03. Humidity Operating : 20% to 85%
04. Storage Temperature: -20°C to 60°C
05. RoHS 2: Complies with EU 2011/65/EU and China GB/T26572-2011

F) ENCLOSURE

01. Housing: High impact plastic, 94V0 polycarbonate, non-vented
02. Size: 38.7 (L) \* 23.7 (W) \* 51.5(H) mm maximum
03. Weight : 48.0 g
04. Markings: Label and/or Pad Printed and/or Molded in the case

TO ADDRESS SYSTEM-LEVEL EMI CONCERNS, FERRITE CHOKES/BEADS MAY BE ADDED/REVISED UPON REQUEST. A SAMPLE KIT OF GLOBTEK'S STANDARD FERRITES IS AVAILABLE UNDER GLOBTEK P/N: EMI-MITIGATION-KIT1




FOR ADDITIONAL INFORMATION, PLEASE READ OUR WHITE PAPER AT: <https://r.globtek.info/3QeaqtD>

INGRESS PROTECTION: Indoor Use

<p>GlobTek, Inc.  www.globtek.com  186 Veterans Drive,  Northvale, NJ 07647  Tel. (201) 784-1000  Fax (201) 784-0111</p>	<p>Drawing Title: GT-86182-1812-W2E-USB, ICT/ITE Power Supply, Efficiency Level: USA DOE Level VI / Eco-design Directive 2009/125/EC, (EU) 2019/1782, Case Color/Style: GlobTek Black, Wall Plug-in, USB Adaptive Power Supply AC Adaptor, Input Rating: 100-240V- , 50/60Hz, Euro Plug Fixed , Output Rating: 18W, 5.0V / 9.0V / 12.0VV@3.0A / 2.0A / 1.5AA, Output Configuration: N/A mm, N/A/ Cond, N/A, Type "A" USB "and"A" USB (USB battery charging BC1.2 compliant) Female Sockets integral to power supply enclosure, Ferrite: None, N/A, GT Cord # C72386, Pin Out: USBA Pin 1: (+), Pin 2: D-, Pin 3: D+, Pin 4: Com, Blades/Input Cord: Fixed Blades Europlug 2 pins, Class II, Approvals: CE; China RoHS; Double Insulation; EAC; WEEE; LPS 60950; RoHS; Ukraine; Morocco;</p>
	<p>Model No. GT-86182-1812-W2E-USB</p>
	<p>Part No./Ordering No. WR9MZ1500USBAFR6B <span style="float: right;">Rev A1</span></p>


3D File Download [https://www.globtek.com/file/dl/gt-86182-wwwv-w2e-usb\\_asm.stp](https://www.globtek.com/file/dl/gt-86182-wwwv-w2e-usb_asm.stp)

Mechanical drawing



<p>GlobTek, Inc.  www.globtek.com  186 Veterans Drive,  Northvale, NJ 07647  Tel. (201) 784-1000  Fax (201) 784-0111</p>	<p>Drawing Title: GT-86182-1812-W2E-USB, ICT/ITE Power Supply, Efficiency Level: USA DOE Level VI / Eco-design Directive 2009/125/EC, (EU) 2019/1782, Case Color/Style: GlobTek Black, Wall Plug-in, USB Adaptive Power Supply AC Adaptor, Input Rating: 100-240V- , 50/60Hz, Euro Plug Fixed , Output Rating: 18W, 5.0V / 9.0V / 12.0VV@3.0A / 2.0A / 1.5AA, Output Configuration: N/A mm, N/A/ Cond, N/A, Type "A" USB "and"A" USB (USB battery charging BC1.2 compliant) Female Sockets integral to power supply enclosure, Ferrite: None, N/A, GT Cord # C72386, Pin Out: USBA Pin 1: (+), Pin 2: D-, Pin 3: D+, Pin 4: Com, Blades/Input Cord: Fixed Blades Europlug 2 pins, Class II, Approvals: CE; China RoHS; Double Insulation; EAC; WEEE; LPS 60950; RoHS; Ukraine; Morocco;</p>
<p>Model No. GT-86182-1812-W2E-USB</p>	<p>Part No./Ordering No. WR9MZ1500USBAFR6B</p>
	<p>Rev A1</p>


DERATING CURVE



<p>GlobTek, Inc.  www.globtek.com  186 Veterans Drive,  Northvale, NJ 07647  Tel. (201) 784-1000  Fax (201) 784-0111</p>	<p>Drawing Title: GT-86182-1812-W2E-USB, ICT/ITE Power Supply, Efficiency Level: USA DOE Level VI / Eco-design Directive 2009/125/EC, (EU) 2019/1782, Case Color/Style: GlobTek Black, Wall Plug-in, USB Adaptive Power Supply AC Adaptor, Input Rating: 100-240V- , 50/60Hz, Euro Plug Fixed , Output Rating: 18W, 5.0V / 9.0V / 12.0VV@3.0A / 2.0A / 1.5AA, Output Configuration: N/A mm, N/A/ Cond, N/A, Type "A" USB "and" "A" USB (USB battery charging BC1.2 compliant) Female Sockets integral to power supply enclosure, Ferrite: None, N/A, GT Cord # C72386, Pin Out: USBA Pin 1: (+), Pin 2: D-, Pin 3: D+, Pin 4: Com, Blades/Input Cord: Fixed Blades Europlug 2 pins, Class II, Approvals: CE; China RoHS; Double Insulation; EAC; WEEE; LPS 60950; RoHS; Ukraine; Morocco;</p>
	<p>Model No. GT-86182-1812-W2E-USB</p>
	<p>Part No./Ordering No. WR9MZ1500USBAFR6B</p>
	<p>Rev A1</p>

**INPUT CONFIGURATION**


(F1) Class II / Double Insulated



[Alternate grounding configurations](#) available upon request.

Blades/Cord Included:FBEU:Fixed Blades Europlug 2 pins, Class II

Europe Blades Class II, (2) Conductors




GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: GT-86182-1812-W2E-USB, ICT/ITE Power Supply, Efficiency Level: USA DOE Level VI / Eco-design Directive 2009/125/EC, (EU) 2019/1782, Case Color/Style: GlobTek Black, Wall Plug-in, USB Adaptive Power Supply AC Adaptor, Input Rating: 100-240V- , 50/60Hz, Euro Plug Fixed , Output Rating: 18W, 5.0V / 9.0V / 12.0VV@3.0A / 2.0A / 1.5AA, Output Configuration: N/A mm, N/A/ Cond, N/A, Type "A" USB "and"A" USB (USB battery charging BC1.2 compliant) Female Sockets integral to power supply enclosure, Ferrite: None, N/A, GT Cord # C72386, Pin Out: USBA Pin 1: (+), Pin 2: D-, Pin 3: D+, Pin 4: Com, Blades/Input Cord: Fixed Blades Europlug 2 pins, Class II, Approvals: CE; China RoHS; Double Insulation; EAC; WEEE; LPS 60950; RoHS; Ukraine; Morocco;	
	Model No. GT-86182-1812-W2E-USB	
	Part No./Ordering No. WR9MZ1500USBAFR6B	Rev A1

**OUTPUT CORD AND CONNECTOR: USBA-USBAMT/C72386**

ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW

CABLE TYPE	N/A
CABLE LENGTH (mm)	N/A
CABLE TOLERANCE (mm)	N/A
WIRE GAUGE (AWG)	N/A
<b>CONDUCTORS</b>	
HANK DIMENSION (mm)	N/A
CABLE / CONNECTOR OVERMOLD COLOR	N/A
FERRITE TYPE AND DIMENSION	None
FERRITE NUMBER OF TURNS <a href="#">(Definition)</a>	N/A
FERRITE DIMENSION FROM STRAIN RELIEF	N/A
FERRITE DIMENSION FROM PLUG	N/A
PLUG TYPE	Type "A" USB "and"A" USB (USB battery charging BC1.2 compliant) Female Sockets integral to power supply enclosure
OUTPUT CONNECTOR GENDER	Female
OVERMOLDED	No
OVER MOLD ORIENTATION	PCB Mount Connector
CONNECTOR PIN OUT	USBA Pin 1: (+), Pin 2: D-, Pin 3: D+, Pin 4: Com



Pin1..... Vo  
Pin2..... D-  
Pin3..... D+  
Pin4..... GND

ADDITIONAL OUTPUT PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/>  
STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/>  
CALCULATE VOLTAGE REGULATION/DROP WITH OUR ONLINE CALCULATOR: <https://en.globtek.com/output-cable-regulation-calculator/>

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: GT-86182-1812-W2E-USB, ICT/ITE Power Supply, Efficiency Level: USA DOE Level VI / Eco-design Directive 2009/125/EC, (EU) 2019/1782, Case Color/Style: GlobTek Black, Wall Plug-in, USB Adaptive Power Supply AC Adaptor, Input Rating: 100-240V- , 50/60Hz, Euro Plug Fixed , Output Rating: 18W, 5.0V / 9.0V / 12.0VV@3.0A / 2.0A / 1.5AA, Output Configuration: N/A mm, N/A/ Cond, N/A, Type "A" USB "and"A" USB (USB battery charging BC1.2 compliant) Female Sockets integral to power supply enclosure, Ferrite: None, N/A, GT Cord # C72386, Pin Out: USBA Pin 1: (+), Pin 2: D-, Pin 3: D+, Pin 4: Com, Blades/Input Cord: Fixed Blades Europlug 2 pins, Class II, Approvals: CE; China RoHS; Double Insulation; EAC; WEEE; LPS 60950; RoHS; Ukraine; Morocco;	
	Model No. GT-86182-1812-W2E-USB	
	Part No./Ordering No. WR9MZ1500USBAFR6B	Rev A1

## OUTPUT CONNECTOR HOOK UP

TO ADDRESS SYSTEM-LEVEL EMI CONCERNS, FERRITE CHOKES/BEADS MAY BE ADDED/REVISED UPON REQUEST. A SAMPLE KIT OF GLOBTEK'S STANDARD FERRITES IS AVAILABLE UNDER GLOBTEK P/N: EMI-MITIGATION-KIT1

FOR ADDITIONAL INFORMATION, PLEASE READ OUR WHITE PAPER AT:


<https://en.globtek.com/technical-articles/ferrite-kit-radiated-emi-suppression-kit-for-globtek-power-supplies-cable-assemblies>

<b>GlobTek, Inc.</b> www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: GT-86182-1812-W2E-USB, ICT/ITE Power Supply, Efficiency Level: USA DOE Level VI / Eco-design Directive 2009/125/EC, (EU) 2019/1782, Case Color/Style: GlobTek Black, Wall Plug-in, USB Adaptive Power Supply AC Adaptor, Input Rating: 100-240V- , 50/60Hz, Euro Plug Fixed , Output Rating: 18W, 5.0V / 9.0V / 12.0VV@3.0A / 2.0A / 1.5AA, Output Configuration: N/A mm, N/A/ Cond, N/A, Type "A" USB "and"A" USB (USB battery charging BC1.2 compliant) Female Sockets integral to power supply enclosure, Ferrite: None, N/A, GT Cord # C72386, Pin Out: USBA Pin 1: (+), Pin 2: D-, Pin 3: D+, Pin 4: Com, Blades/Input Cord: Fixed Blades Europlug 2 pins, Class II, Approvals: CE; China RoHS; Double Insulation; EAC; WEEE; LPS 60950; RoHS; Ukraine; Morocco;	
	Model No. GT-86182-1812-W2E-USB	
	Part No./Ordering No. WR9MZ1500USBAFR6B	Rev A1

**LABEL:L-1186**

LABEL P/N	Standard GT
MATERIAL	Flat Thermal Transfer, Imprintable, Polyester Label and/or Pad Printed and/or Molded, and/or Laser Engraved in the case
BACKGROUND COLOR	Black if housing is Black, White or Silver if housing is White or Gray.
TEXT COLOR	White or Silver if label is Black Background for Black housing. Black if label is White or Silver background and Housing is White or Gray.
LABEL WIDTH (mm)	38.6
LABEL HEIGHT (mm)	22.1
SPECIAL BARCODE LABEL MATERIAL	No

Below is the minimum information which will appear on the label. NOTE: in the logo area additional/actual positioning of symbols and text is subjected to change as per agency updates/requirements or additional model approvals become available.  
Regulatory certifications/label markings may be in logo area on the label or molded into the case housing outside the label area.  
Information will be shown via label and/or pad printed and/or molded and/or laser engraved in the case. \* Date code markings at GlobTek option



or  
**DATE CODE B \***  
**WWYY**  
**WW = WEEK**  
**YY = YEAR**

A=ICT/ITE Power Supply  
B=P/N: (料号) WR9MZ1500USBAFR6B  
C=Model (型号) GT-86182-1812-W2E-USB  
D=Input (输入)100-240V- , 50/60Hz, 0.8 A  
E=Output (输出)5.0V / 9.0V / 12.0V V  $\equiv$  3.0A / 2.0A / 1.5A A, 18,00W

GloBtek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: GT-86182-1812-W2E-USB, ICT/ITE Power Supply, Efficiency Level: USA DOE Level VI / Eco-design Directive 2009/125/EC, (EU) 2019/1782, Case Color/Style: GlobTek Black, Wall Plug-in, USB Adaptive Power Supply AC Adaptor, Input Rating: 100-240V- , 50/60Hz, Euro Plug Fixed , Output Rating: 18W, 5.0V / 9.0V / 12.0VV@3.0A / 2.0A / 1.5AA, Output Configuration: N/A mm, N/A/ Cond, N/A, Type "A" USB "and"A" USB (USB battery charging BC1.2 compliant) Female Sockets integral to power supply enclosure, Ferrite: None, N/A, GT Cord # C72386, Pin Out: USBA Pin 1: (+), Pin 2: D-, Pin 3: D+, Pin 4: Com, Blades/Input Cord: Fixed Blades Europlug 2 pins, Class II, Approvals: CE; China RoHS; Double Insulation; EAC; WEEE; LPS 60950; RoHS; Ukraine; Morocco;	
	Model No. GT-86182-1812-W2E-USB	
	Part No./Ordering No. WR9MZ1500USBAFR6B	Rev A1

AGENCY ONLINE DOCUMENTS	<a href="http://www.globtek.info/certs/GT-86182-W(F)2-USB/">http://www.globtek.info/certs/GT-86182-W(F)2-USB/</a>
CE EC-Declaration for Medical	<a href="#">Contact GlobTek for more information</a>
CE EC-Declaration for Industrial/Commercial/ITE	<a href="http://globtek.force.com/models/ec_declaration_product?id=01t3a0000054Oxc&amp;i=5">http://globtek.force.com/models/ec_declaration_product?id=01t3a0000054Oxc&amp;i=5</a>
CE EC-Declaration for Household	<a href="#">Contact GlobTek for more information</a>
UKCA-Declaration for Medical	<a href="#">Contact GlobTek for more information</a>
UKCA-Declaration for Industrial/Commercial/ITE	<a href="http://globtek.force.com/models/ukca_declaration_product?id=01t3a0000054Oxc&amp;i=5">http://globtek.force.com/models/ukca_declaration_product?id=01t3a0000054Oxc&amp;i=5</a>
UKCA-Declaration for Household	<a href="#">Contact GlobTek for more information</a>
Morocco SDoC Declaration	<a href="https://globtek.secure.force.com/models/Morocco_SDoC_Declaration?id=a003a00000Lu6L5EAJ">https://globtek.secure.force.com/models/Morocco_SDoC_Declaration?id=a003a00000Lu6L5EAJ</a>
RoHS/RoHS3 Declaration	<a href="https://www.globtek.com/pdf/rohs_cert/01t3a0000054OxcAAE">https://www.globtek.com/pdf/rohs_cert/01t3a0000054OxcAAE</a>
REACH Declaration	<a href="https://www.globtek.com/pdf/iso_certificates/REACH.pdf">https://www.globtek.com/pdf/iso_certificates/REACH.pdf</a>
Conflict Minerals Declaration	<a href="https://www.globtek.com/pdf/conflict-minerals.pdf">https://www.globtek.com/pdf/conflict-minerals.pdf</a>
Prop 65 Statement	<a href="https://en.globtek.com/prop-65-statement.pdf">https://en.globtek.com/prop-65-statement.pdf</a>
IPXY rating is based on 3rd party testing and customers should check suitability and test system level IPXY rating before ordering.	

## Regulatory Certifications/Label Markings

Below follows a link to the latest regulatory certifications and marks for this specific product. National standards as well as certification schemes are constantly changing and so is the set of certification marks and symbols applicable to this product. Various standards, marks and symbols, and certificates are subject to change at any time without notice.

Additional standards or unique country certifications are available upon request. Please contact Globtek to request a quotation.

LATEST PRODUCT/MODEL CERTIFICATIONS: <https://www.globtek.com/datasheet/w70574>

AGENCY ONLINE DOCUMENTS [http://www.globtek.info/certs/GT-86182-W\(F\)2-USB/](http://www.globtek.info/certs/GT-86182-W(F)2-USB/)



(F1) Class II / Double Insulated



USBA  
Pin 1: (+), Pin 2: D-, Pin 3: D+, Pin 4: Com


<b>GlobTek, Inc.</b> www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: GT-86182-1812-W2E-USB, ICT/ITE Power Supply, Efficiency Level: USA DOE Level VI / Eco-design Directive 2009/125/EC, (EU) 2019/1782, Case Color/Style: GlobTek Black, Wall Plug-in, USB Adaptive Power Supply AC Adaptor, Input Rating: 100-240V- , 50/60Hz, Euro Plug Fixed , Output Rating: 18W, 5.0V / 9.0V / 12.0VV@3.0A / 2.0A / 1.5AA, Output Configuration: N/A mm, N/A/ Cond, N/A, Type "A" USB "and"A" USB (USB battery charging BC1.2 compliant) Female Sockets integral to power supply enclosure, Ferrite: None, N/A, GT Cord # C72386, Pin Out: USBA Pin 1: (+), Pin 2: D-, Pin 3: D+, Pin 4: Com, Blades/Input Cord: Fixed Blades Europlug 2 pins, Class II, Approvals: CE; China RoHS; Double Insulation; EAC; WEEE; LPS 60950; RoHS; Ukraine; Morocco;	
	Model No. GT-86182-1812-W2E-USB	
	Part No./Ordering No. WR9MZ1500USBAFR6B	Rev A1

## PACKAGING

Packing Spec P/N	Standard WPI, Individually Box
Box Qty	300
Gift Box Size (mm)	95*43*30
Gift Box Color	White
Master Carton Size (mm)	455 x 317 x 325
Master Carton Cubic Volume (m³)	0.05
Master GW (Kg)	16,0 kg
BLADES INCLUDED	FBEU: Fixed Blades Europlug 2 pins, Class II
BLADE/CORD INSTALLED	:
USER MANUAL*	
USER MANUAL WEB LINK	

\* This specification sheet is considered the user manual for all applications. It is expected that the buyer of this product will use it to formulate their own user manual for their end product and a user manual specifically for the power adapter is not usually required. If a user manual is not specifically listed above then none will be provided with this unit.

If specific packaging is required, this section must specify all requirements and note "no exceptions". If this section does not specify packaging, it is subject to change without notice at GlobTek's discretion



<p>GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111</p>	<p>Drawing Title: GT-86182-1812-W2E-USB, ICT/ITE Power Supply, Efficiency Level: USA DOE Level VI / Eco-design Directive 2009/125/EC, (EU) 2019/1782, Case Color/Style: GlobTek Black, Wall Plug-in, USB Adaptive Power Supply AC Adaptor, Input Rating: 100-240V- , 50/60Hz, Euro Plug Fixed , Output Rating: 18W, 5.0V / 9.0V / 12.0VV@3.0A / 2.0A / 1.5AA, Output Configuration: N/A mm, N/A/ Cond, N/A, Type "A" USB "and"A" USB (USB battery charging BC1.2 compliant) Female Sockets integral to power supply enclosure, Ferrite: None, N/A, GT Cord # C72386, Pin Out: USBA Pin 1: (+), Pin 2: D-, Pin 3: D+, Pin 4: Com, Blades/Input Cord: Fixed Blades Europlug 2 pins, Class II, Approvals: CE; China RoHS; Double Insulation; EAC; WEEE; LPS 60950; RoHS; Ukraine; Morocco;</p>
	<p>Model No. GT-86182-1812-W2E-USB</p>
	<p>Part No./Ordering No. WR9MZ1500USBAFR6B</p>
	<p>Rev A1</p>

**INSTRUCTIONS TO THE OEM SYSTEMS ENGINEER**

It is the responsibility of the OEM systems engineer to provide the end system user instructions and warnings for the use of this product in the end system.

If an input cord is required for this product, AC Mains voltage should be provided to the power supply by a power supply cord approved to the national standards of the country in which it will be used.

This product is not designed to be repaired. No serviceable parts inside. A blown internal fuse is an indication of catastrophic failure of circuit component(s). If a Failure Analysis is required for a failed power supply/battery charger, please return the damaged unit to GlobTek for an accurate determination of the root cause of the failure.

EMC Compliance of the complete OEM product, including the GlobTek power supply/battery charger needs to be verified by the OEM systems engineer.

**INSTRUCTION SHEET**

---

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: GT-86182-1812-W2E-USB, ICT/ITE Power Supply, Efficiency Level: USA DOE Level VI / Eco-design Directive 2009/125/EC, (EU) 2019/1782, Case Color/Style: GlobTek Black, Wall Plug-in, USB Adaptive Power Supply AC Adaptor, Input Rating: 100-240V- , 50/60Hz, Euro Plug Fixed , Output Rating: 18W, 5.0V / 9.0V / 12.0VV@3.0A / 2.0A / 1.5AA, Output Configuration: N/A mm, N/A/ Cond, N/A, Type "A" USB "and"A" USB (USB battery charging BC1.2 compliant) Female Sockets integral to power supply enclosure, Ferrite: None, N/A, GT Cord # C72386, Pin Out: USBA Pin 1: (+), Pin 2: D-, Pin 3: D+, Pin 4: Com, Blades/Input Cord: Fixed Blades Europlug 2 pins, Class II, Approvals: CE; China RoHS; Double Insulation; EAC; WEEE; LPS 60950; RoHS; Ukraine; Morocco;	
	Model No. GT-86182-1812-W2E-USB	
	Part No./Ordering No. WR9MZ1500USBAFR6B	Rev A1

