

## Product Use in your Country or Municipality

Standards that govern use of this product vary by country and sometimes municipality. In the United States, this product is not for use in the Patient Care Vicinity, as defined in the National Electric Code (NEC). This product is approved to CSA C22.2/CuL standards and approved for use in Canada. For application guidance and product selection in your country, please consult a [Healthcare Product Specialist](#) or your own expert.

## Safe-IT Medical-Grade Power Strip, UL 1363, 6x Hospital-Grade Outlets, Antimicrobial, 1.5 ft. (0.45 m) Cord, TAA

MODEL NUMBER: PS-602-HG



Medical-grade power strip with patented antimicrobial coating and 1.5 ft. cord provides safe, versatile power distribution.

## Features

**Power Distribution Outside of Patient-Care Vicinities** Ideal for use in administrative areas and resident rooms with no line-operated electrical equipment for diagnostic, treatment or monitoring purposes 120V, 50/60 Hz power strip complies with UL 1363 specifications

**Exclusive Antimicrobial Protection** Antimicrobial coating helps resist the growth of bacteria, viruses, fungi, mold and mildew Coating meets the requirements of JIS Z 2801:2000, an international standard for evaluating efficacy in antimicrobial products

**Versatile Medical-Grade Solution** 6 NEMA 5-15R-HG hospital-grade outlets provide consistent power Rugged, all-metal housing for long life in demanding environments

**Premium Safety Features** Resettable 15A circuit breaker protects against dangerous overloads Switchless design prevents accidental shut-off

**Ready to Use Right Out of the Box** Built-in keyhole mounting tabs and flanges make the PS-602-HG easy to install on a variety of surfaces

## Highlights

- Antimicrobial protection helps prevent the growth of bacteria, viruses, fungi, mold and mildew
- Complies with UL 1363 specifications
- 1.5 ft. cord with NEMA 5-15P-HG hospital-grade plug
- Features 6 NEMA 5-15R-HG hospital-grade outlets

## Package Includes

- PS-602-HG UL 1363 Medical-Grade Power Strip with six 15A Hospital-Grade Outlets and 1.5 ft. Cord
- Owner's Manual

## Specifications

### OVERVIEW



Powering Business Worldwide

TRIPP LITE  
SERIES

|   |   |
|---|---|
| UPC Code  | 037332121042  |
| <b>INPUT</b>                                      |   |
| Nominal Input Voltage(s) Supported                | 120V AC   |
| Recommended Electrical Service                    | 15A 120V  |
| Input Plug Features                               | Hospital Grade Plug   |
| Voltage Compatibility (VAC)                       | 120   |
| Input Plug Type                                   | NEMA 5-15P-HG   |
| Input Cord Length (ft.)                           | 1.5   |
| Right-Angle Plug                                  | No  |
| Input Cord Length (m)                             | 0.46  |
| Integrated Cord Clip                              | No  |
| <b>OUTPUT</b>                                     |   |
| Frequency Compatibility                           | 50 / 60 Hz  |
| Output (Watts)                                    | 1800  |
| Output Receptacles                                | (6) 5-15R-HG  |
| Circuit Breaker (amps)                            | 15  |
| Overload Protection                               | 15 amp circuit breaker  |
| Transformer Accommodation                         | (2) Yes   |
| Outlet Orientation                                | Single row of 6   |
| Right-Angle Outlets                               | No  |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b>      |   |
| Switches  | No power switch   |
| <b>PHYSICAL</b>                                   |   |
| Color   | White   |
| Material of Construction                          | Metal   |
| Power Cord Color                                  | White   |
| Housing Color                                     | White   |
| Mounting Holes or Slots                           | Yes   |
| Slot or Hole Mount Measurement (Center to Center) | Distance between keyhole slots = 261.92mm; Distance between end tabs = 330.17mm |
| Outlets Measurement (Center to Center)            | 1.52 in.  |
| Receptacle Color                                  | White   |
| Shipping Dimensions (hwd / in.)                   | 2.20 x 5.80 x 14.40   |
| Shipping Dimensions (hwd / cm)                    | 5.59 x 14.73 x 36.58  |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                      |                                  |
|--------------------------------------|----------------------------------|
| Shipping Weight (lbs.)               | 2.20                             |
| Shipping Weight (kg)                 | 1.00                             |
| Unit Dimensions (hwd / in.)          | 1.250 x 2.250 x 13.750           |
| Unit Dimensions (hwd / cm)           | 3.8 x 34.9 x 6.4                 |
| Unit Weight (lbs.)                   | 2.00                             |
| Unit Weight (kg)                     | 0.91                             |
| Mounting Details                     | Includes flanges                 |
| <b>ENVIRONMENTAL</b>                 |                                  |
| Operating Temperature Range          | 32° to 104°F (0° to 40°C)        |
| Storage Temperature Range            | 14° to 122°F (-10° to 50°C)      |
| Operating Humidity Range             | 10% to 90% RH                    |
| Storage Humidity Range               | 5% to 95% RH                     |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                                  |
| Antimicrobial                        | Yes                              |
| Built-In Circuit Breaker             | Yes                              |
| Antibacterial                        | No                               |
| Built-in Cable Management            | No                               |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                                  |
| Product Certifications               | cUL Listed; UL 1363; UL Listed   |
| Product Compliance                   | RoHS; Trade Agreements Act (TAA) |
| <b>WARRANTY &amp; SUPPORT</b>        |                                  |
| Product Warranty Period (Worldwide)  | Lifetime limited warranty        |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.