



Powering Business Worldwide

## 850VA 510W 120V AC DIN Rail Industrial UPS - Hardwire Input/Output

MODEL NUMBER: **DIN850AC**



DIN rail UPS battery backup offers network-grade power protection for industrial and machine control installations.

### Features

#### Flexible Power Protection for Smart Industrial Applications

The DIN850AC standby UPS system with hardwire AC input/output delivers reliable power and battery backup for computing, networking, control and storage equipment in factories, warehouses, edge computing locations and automated manufacturing and fabrication facilities. The rugged compact housing withstands demanding conditions and integrates seamlessly and securely into electrical enclosures in any non-traditional IT environment.

#### Ideal for Factory Floors and Extreme Temperatures

Get full use of the DIN850AC's power capacity because there is no derating based on its operating temperature range of 0°C (32°F) to 50°C (122°F), which expands the number of locations in which it can be used. Built to fit into small spaces, the DIN850AC is a UL 508 recognized component for use in industrial panels. Its pre-installed clamp enables quick mounting to a 35 mm DIN rail. Its fanless design reduces noise and increases reliability.

#### Reliable Battery Backup Keeps You Operational Through Power Outages

Power outages not only drain productivity from the factory floor, but they also damage expensive equipment. The DIN850AC protects productivity by providing enough runtime to maintain operation during a brief power outage and protects equipment by allowing it to complete an operation during an extended outage. It also prevents brownouts, overvoltages, surges and line noise from damaging equipment that could destroy data and contribute to costly downtime.

#### Convenient Automatic Restart

The DIN850AC automatically restarts when AC power is restored after an outage, eliminating the need for a costly site visit.

#### Stay in Control of Your Operation

LEDs on the front panel confirm normal operation and indicate alarm or fault status. Remote on/off and a battery indicator mode can help you avoid maintenance surprises. The DIN850AC is compatible with PowerAlert® Office software for UPS monitoring and control via USB connection.

#### Easy Preventative Maintenance and Initial Troubleshooting

The DIN850AC's self-test capability and user-replaceable internal battery can extend the life of the UPS and minimize disruption to operations. A resettable circuit breaker helps prevent dangerous system overloads.

### Highlights

- Recommended for industrial locations where temperatures range within 0°C and 50°C
- Protects equipment against blackouts, brownouts, overvoltages, surges and line noise
- Keeps power running during brief outages to allow time for safe system shutdown
- Restarts automatically when power is restored, eliminating a costly site visit
- Built-in clamp mounts easily to a "top hat" 35mm DIN rail with no mounting screws or brackets required

### Package Includes

- DIN850AC 850VA 510W 120V DIN Rail Industrial UPS
- USB communication cable
- Safety card
- Owner's manual



Powering Business Worldwide

## Specifications

OVERVIEW	
UPC Code	037332274922
UPS Type	Standby
INPUT	
Input Phase	Single-Phase
Rated input current (Maximum Load)	10A
Nominal Input Voltage(s) Supported	120V AC
UPS Input Connection Type	Hardwire
UPS Input Connection Description	Recommended 14 AWG 194°F(90°C) rated copper wire
Input Circuit Breakers	10A
Recommended Electrical Service	15A 120V
Maximum Input Amps	10
OUTPUT	
Output Capacity (VA)	850
Output Capacity (kVA)	0.85
Output Capacity (Watts)	510
Output Capacity (kW)	0.51
Power Factor	0.6
Nominal Voltage Details	120v nominal output in battery mode
Frequency Compatibility	50 / 60 Hz
Frequency Compatibility Details	50 or 60Hz +/- 10% (Auto-sensing)
Output Voltage Regulation (Battery Mode)	+/- 10%
Output AC Waveform (AC Mode)	Sine wave
Output (Watts)	510
Output AC Waveform (Battery Mode)	PWM sine wave
Nominal Output Voltage(s) Supported	120V
Output Receptacles	(1) Hardwire
Individually Controllable Load Banks	No
BATTERY	
Battery Type	Valve Regulated Lead Acid (VRLA)



Powering Business Worldwide

Runtime Full Load (min.)	2 min. (510W)
Runtime Half Load (min.)	7 min. (255W)
Expandable Runtime	No
DC System Voltage (VDC)	12
Battery Recharge Rate (Included Batteries)	0.7A Maximum; Less than 8 hours from 10% to 90%
Battery Access	Top-mounted battery access panel
Internal UPS Replacement Battery Cartridge	RBC12V9ET
<b>USER INTERFACE, ALERTS &amp; CONTROLS</b>	
Switches	Power ON/OFF/TEST - Momentary push button
Alarm Cancel Operation	Press and hold On/Off/Test button for 1 second
Audible Alarm	Yes
LED Indicators	ALARM - RED - Flashes when the battery needs to be recharged and tested. SOLID RED when the unit is subjected to an overload condition. YELLOW - ON SOLID when the UPS is supplying battery power to the loads. GREEN - ON SOLID GREEN when the line input voltage is normal.
<b>SURGE / NOISE SUPPRESSION</b>	
EMI / RFI AC Noise Suppression	Yes
AC Suppression Joule Rating	588
<b>PHYSICAL</b>	
Primary Form Factor	DIN-Rail
Cooling Method	Convection
Shipping Dimensions (hwd / in.)	15.87 x 7.95 x 7.72
Shipping Weight (kg)	6.00
UPS Housing Material	Steel
Unit Dimensions (hwd / in.)	5.220 x 12.280 x 5.500
Unit Weight (lbs.)	12.125
Unit Weight (kg)	5.50
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	32° to 122°F (0° to 50°C)
Storage Temperature Range	5° to 122°F (-15° to 50°C)
Relative Humidity	0-95% non-condensing
AC Mode BTU / Hr. (Full Load)	52.169
AC Mode Efficiency Rating (100% Load)	97%
Operating Elevation	0-10000 ft. (0-3000 m)



Powering Business Worldwide

Audible Noise	40 dBA at 1 meter
<b>COMMUNICATIONS</b>	
PowerAlert Software	PowerAlert Office
Communications Cable	USB 2.0 Cable
Network Management Card Description	Network management not supported
Communications Interface	(1) USB (HID enabled)
Emergency Power Off (EPO)/Remote On-Off (ROO)	Yes
<b>LINE / BATTERY TRANSFER</b>	
Transfer Time	<8ms typical, 10ms max
Low Voltage Transfer to Battery Power (Setpoint)	87V
High Voltage Transfer to Battery Power (Setpoint)	144V
<b>FEATURES &amp; SPECIFICATIONS</b>	
Cold Start (Startup in Battery Mode During a Power Failure)	Cold Start operation supported
High Availability UPS Features	Surge/noise protection
Green Energy-Saving Features	Greater than 95% efficiency - GREEN UPS; High efficiency economy mode operation
<b>APPLICATIONS</b>	
UPS Applications	Extreme Temperature Applications; Industrial
<b>STANDARDS &amp; COMPLIANCE</b>	
Product Certifications	CAN/CSA-C22.2 No. 107.3 (Canada); CSA (Canada); ICES (Canada); UL 1778; UL 508; NOM (Mexico)
Product Compliance	FCC Part 15 Class B (USA); RoHS
<b>WARRANTY &amp; SUPPORT</b>	
Product Warranty Period (Worldwide)	2-year limited warranty

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.