

## Specification Sheet

Part Number: 151-00927



Pre-drilled holes allows for easy installation by hand.

Cable can be removed and reinstalled without removing the clip, providing multiple use options.

Made of PA66HIRHSUV material for withstanding extreme conditions.

Fir Tree C-Clip, 0.24 - 0.30" Bundle Dia, 0.03 - 0.25" Panel, 0.26" Mount Hole, PA66HIRHSUV, Black, 100/pkg

|                |           |
|----------------|-----------|
| Article Number | 151-00927 |
|----------------|-----------|

|      |       |
|------|-------|
| Type | SC6.6 |
|------|-------|

|       |            |
|-------|------------|
| Color | Black (BK) |
|-------|------------|

|              |      |
|--------------|------|
| Quantity Per | pack |
|--------------|------|

|                     |                                                                                                                                                                                                                                                                                                                                                                                      |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Description | The C Clip with fir tree mount is ideal for panels with pre-drilled holes. Easy installation by hand eliminates the need for any tools. Once installed, the cable simply snaps into the clip. The cable can be removed and reinstalled without removing the clip. Made from PA66HIRHSUV material, the clip offers increased flexibility along with heat resistance and UV stability. |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                   |                                                                                                             |
|-------------------|-------------------------------------------------------------------------------------------------------------|
| Short Description | Fir Tree C-Clip, 0.24 - 0.30" Bundle Dia, 0.03 - 0.25" Panel, 0.26" Mount Hole, PA66HIRHSUV, Black, 100/pkg |
|-------------------|-------------------------------------------------------------------------------------------------------------|

|                  |                      |
|------------------|----------------------|
| Global Part Name | SC6.6-PA66HIRHSUV-BK |
|------------------|----------------------|

|                 |          |
|-----------------|----------|
| Fixation Method | Fir Tree |
|-----------------|----------|

|                    |      |
|--------------------|------|
| Width W (Imperial) | 0.72 |
|--------------------|------|

|                  |       |
|------------------|-------|
| Width W (Metric) | 18.26 |
|------------------|-------|

|                                |      |
|--------------------------------|------|
| Bundle Diameter Min (Imperial) | 0.24 |
|--------------------------------|------|

|                              |     |
|------------------------------|-----|
| Bundle Diameter Min (Metric) | 6.0 |
|------------------------------|-----|

|                                |     |
|--------------------------------|-----|
| Bundle Diameter Max (Imperial) | 0.3 |
|--------------------------------|-----|

|                              |     |
|------------------------------|-----|
| Bundle Diameter Max (Metric) | 7.6 |
|------------------------------|-----|

|                     |      |
|---------------------|------|
| Height H (Imperial) | 1.32 |
|---------------------|------|

|                   |       |
|-------------------|-------|
| Height H (Metric) | 33.43 |
|-------------------|-------|

|                                |      |
|--------------------------------|------|
| Panel Thickness Min (Imperial) | 0.03 |
|--------------------------------|------|

|                                |      |
|--------------------------------|------|
| Panel Thickness Max (Imperial) | 0.25 |
|--------------------------------|------|

|                              |     |
|------------------------------|-----|
| Panel Thickness Min (Metric) | 0.7 |
|------------------------------|-----|

|                              |      |
|------------------------------|------|
| Panel Thickness Max (Metric) | 6.35 |
|------------------------------|------|

|                                     |        |
|-------------------------------------|--------|
| Mounting Hole Diameter D (Imperial) | 0.26 " |
|-------------------------------------|--------|

|                                   |        |
|-----------------------------------|--------|
| Mounting Hole Diameter D (Metric) | 6.6 mm |
|-----------------------------------|--------|

|                                       |                                                                          |
|---------------------------------------|--------------------------------------------------------------------------|
| Mounting Hole Diameter D Max (Metric) | 6.6                                                                      |
| Disc Diameter (Metric)                | 18.55                                                                    |
| Disc Diameter (Imperial)              | 0.73                                                                     |
| Material                              | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Material Shortcut                     | PA66HIRHSUV                                                              |
| Flammability                          | UL 94 HB                                                                 |
| Halogen Free                          | Yes                                                                      |
| UV Resistant (Yes/No)                 | Yes                                                                      |
| Use Conditions                        | For Indoor and Outdoor Use                                               |
| Operating Temperature                 | -40°F to +221°F (-40°C to +105°C)                                        |
| Reach Compliant (Article 33)          | Yes                                                                      |
| ROHS Compliant                        | Yes                                                                      |
| Package Quantity (Imperial)           | 100                                                                      |
| Package Quantity (Metric)             | 100                                                                      |

Customs Number

3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Disclaimer](#)   [Terms and Conditions](#)