

Specification Sheet

Part Number: 151-01713



Patented retention design features inverted retaining legs, narrow opening and circular retainer to prevent inadvertent disengagement.

Controlled flex and angled entry promote easy installation.

Fir tree demonstrates easy insertion with high extraction resistance.

MOC Clip, 6 mm, with 6.5mm Fir Tree, PA66HIRHSUV, Black, 5000/ctn

Article Number 151-01713

Type MOC6FT6.5

Color Black (BK)

Quantity Per pack

Product Description The MOC with Round Fir Tree features HellermannTyton's unique retention clip with an integrated fir tree to fit securely in a 6.5 (+/-0.4) mm hole. The mount delivers a low insertion force while exhibiting high extraction resistance for a secure mounting point against a panel.

Short Description MOC Clip, 6 mm, with 6.5mm Fir Tree, PA66HIRHSUV, Black, 5000/ctn

Global Part Name MOC6FT6.5-PA66HIRHSUV-BK

| | |
|-------------------------------------|----------------------------------|
| Length L (Imperial) | 0.67 |
| Length L (Metric) | 17.0 |
| Fixation Method | Fir Tree |
| Bundle Diameter Min (Imperial) | 0.22 |
| Bundle Diameter Min (Metric) | 5.5 |
| Bundle Diameter Max (Imperial) | 0.27 |
| Bundle Diameter Max (Metric) | 6.8 |
| Height H (Imperial) | 1.09 |
| Height H (Metric) | 27.8 |
| Depth D (Imperial) | 0.39 |
| Depth D (Metric) | 10.0 |
| Panel Thickness Min (Imperial) | 0.02 |
| Panel Thickness Max (Imperial) | 0.22 |
| Panel Thickness Min (Metric) | 0.6 |
| Panel Thickness Max (Metric) | 5.5 |
| Mounting Hole Diameter D (Imperial) | 0.24 - 0.27 " 0.25 " (HEXAGONAL) |

| | |
|---|--|
| Mounting Hole Diameter D (Metric) | 6.1 - 6.9 mm 6.35 mm (hexagonal) |
| Mounting Hole Diameter D Min (Imperial) | 0.24 |
| Mounting Hole Diameter D Max (Imperial) | 0.27 |
| Mounting Hole Diameter D Max (Metric) | 6.9 |
| Material | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Material Shortcut | PA66HIRHSUV |
| Flammability | UL 94 HB |
| Halogen Free | Yes |
| UV Resistant (Yes/No) | Yes |
| Use Conditions | For Indoor and Outdoor Use |
| Operating Temperature | -40°F to +221°F (-40°C to +105°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 5000 |

Package Quantity (Metric) 5000

Customs Number 3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)