

Specification Sheet

Part Number: 211-60000



P-Clamps easily guide and locate wire and cables up to 1" in diameter.  
Designed with a radius edge to prevent chafing and cutting into insulation.

P-Clamp, 0.39" Wide, 0.13" Max Bundle Dia, 0.17" Mounting Hole Dia, PA66HS, Black, 100/pkg

|                     |                                                                                                                                                                                                           |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 211-60000                                                                                                                                                                                                 |
| Type                | H1P                                                                                                                                                                                                       |
| Color               | Black (BK)                                                                                                                                                                                                |
| Quantity Per        | pack                                                                                                                                                                                                      |
| Product Description | HellermannTyton P-Clamps easily guide and locate wires and cables. The clamps are designed with a radius edges to prevent chafing and cutting into insulation. Available sizes up to 1" bundle diameters. |
| Short Description   | P-Clamp, 0.39" Wide, 0.13" Max Bundle Dia, 0.17" Mounting Hole Dia, PA66HS, Black, 100/pkg                                                                                                                |
| Global Part Name    | H1P-PA66HS-BK                                                                                                                                                                                             |

|                                       |                                        |
|---------------------------------------|----------------------------------------|
| Fixation Method                       | screw-hole                             |
| Variant                               | Closed                                 |
| Width W (Imperial)                    | 0.39                                   |
| Width W (Metric)                      | 10.0                                   |
| Bundle Diameter Max (Imperial)        | 0.13                                   |
| Bundle Diameter Max (Metric)          | 3.2                                    |
| Nominal Diameter (Imperial)           | 0.13                                   |
| Nominal Diameter (Metric)             | 3.2                                    |
| Wall Thickness WT (Imperial)          | 0.031                                  |
| Wall Thickness WT (Metric)            | 0.8                                    |
| Mounting Hole Diameter D (Imperial)   | 0.17 "                                 |
| Mounting Hole Diameter D (Metric)     | 4.2 mm                                 |
| Mounting Hole Diameter D Max (Metric) | 4.2                                    |
| Mounting Hole Centers (Imperial)      | 0.33                                   |
| Material                              | Polyamide 6.6 heat stabilized (PA66HS) |

|                              |                                   |
|------------------------------|-----------------------------------|
| Material Shortcut            | PA66HS                            |
| Flammability                 | UL 94 V-2                         |
| UV Resistant (Yes/No)        | No                                |
| Use Conditions               | For Indoor and Outdoor Use        |
| Operating Temperature        | -40°F to +221°F (-40°C to +105°C) |
| Reach Compliant (Article 33) | Yes                               |
| ROHS Compliant               | Yes                               |
| Package Quantity (Imperial)  | 100                               |
| Package Quantity (Metric)    | 100                               |
| Customs Number               | 3926909988                        |

7930 N. Faulkner Road, Milwaukee, WI 53224  
 Phone: (800) 537-1512 | Email: corp@htamericas.com