



| Plug Component             |                                                |     | Plug Strip Dimension |      |       | Wire Spec.                                      | Terminal ROJ & Strip |      |       | Terminal Component                |                            |     |
|----------------------------|------------------------------------------------|-----|----------------------|------|-------|-------------------------------------------------|----------------------|------|-------|-----------------------------------|----------------------------|-----|
| Color                      | Component                                      | Qty | Strip                | ROJ  | Color |                                                 | Strip                | ROJ  | Color | Component                         | Color                      | Qty |
| 40P clear color<br>90±5° A | NEMA5-15P HOSPITAL GRADE<br>(LT-205(10A 125V)) | 1   | 10±1                 | 21±3 | Black | SJT 18AWGX3C 105°C (GRAY)<br>Length: 1829±50 mm | 7±1                  | 20±3 | Black | IEC 320 C13<br>(LT-501(10A 125V)) | 40P clear color<br>90±5° A | 1   |
| Nickel-Plated              | ∅4.75 U Grounding pin                          | 1   | 10±1                 | 21±3 | White |                                                 | 7±1                  | 20±3 | White | computer power<br>cord terminals  | Copper                     | 3   |
| Nickel-Plated              | 6.3*1.5(Solid Blades)                          | 2   | 10±1                 | 36±3 | Green |                                                 | 7±1                  | 20±3 | Green | (501 Inner Body)                  | White                      | 1   |
| Nickel-Plated              | Copper ring                                    | 1   |                      |      |       |                                                 |                      |      |       |                                   |                            |     |

**NOTE :**

1. PLUG : NEMA5-15P HOSPITAL GRADE (LT-205)
2. CONNECTOR : IEC-320 C13 (LT-501)
3. CORD : SJT 18AWGX3C 105°C GRAY 6FT
4. APPROVALS : UL, C-UL
5. Flexible cord : RHYTHM
6. Hi-Pot Test:2000v/1min<1mA>

**MARKING:**

RHYTHM: (UL) E88231 SJT 3X18AWG(0.824mm<sup>2</sup>)  
105°C 300V VW-1 CSA LL54496 SJT  
3X18AWG(0.824mm<sup>2</sup>)105°C 300V VW-1  
RHYTHM R

**Modification History**

|  |  |  |
|--|--|--|
|  |  |  |
|  |  |  |
|  |  |  |

|  |                    |                |      |             |          |               |                             |
|--|--------------------|----------------|------|-------------|----------|---------------|-----------------------------|
|  |                    | <b>DRAWER</b>  | Eric | <b>DATE</b> | 20/10/24 | <b>P/N</b>    | 800-18-00D-GR-0006F-1       |
|  |                    | <b>APPROVE</b> |      | <b>REV.</b> | 0        | <b>Dr.No.</b> | 1091092                     |
|  |                    |                |      | <b>TOL.</b> |          |               | ±5mm                        |
|  |                    |                |      |             |          |               |                             |
|  | <b>DESCRIPTION</b> | <b>DATE</b>    |      |             |          |               | <b>ALL DIMENSIONS IN mm</b> |

**CnC Tech**  
Industrial Cable and Connector Technology