


# DisplayPort Cable with Latching Connectors (M/M), 8K 60 Hz, HDR, HBR3, 4:4:4, HDCP 2.2, 9 ft. (2.7 m)

MODEL NUMBER: P580-009-8K6



8K DisplayPort cable connects your source and display devices to transmit enhanced 8K Ultra HD audio/video with HDR and 4:4:4 chroma.

## Features

### DisplayPort 1.4 Cable Gets Your Gaming, Home Theater or Digital Signage Setup 8K-Ready

This high-speed DisplayPort (DP) cable (M/M) securely connects source and display devices compatible with DP 1.4 audio/video signals. Backward compatible with all your existing DisplayPort devices, including Blu-ray players, game consoles and 4K televisions, the P580-009-8K6 is ideal for future-proofing your high-definition or Ultra HD application in anticipation of an 8K upgrade.

### Enjoy the Clarity of 4K/8K Video with Multi-Channel Audio and 4:4:4 Color

The P580-009-8K6 supports 8K Ultra HD resolutions up to 7680 x 4320 at 60 Hz with multi-channel sound. It's compatible with DisplayPort 1.4 standards for HDR, providing a wide range of vibrant colors with richer contrast, brighter whites and deeper blacks. HDCP 2.2 compliance allows you to stream 4K content with no complications. This BT.2020-compatible cable also supports 4:4:4 chroma subsampling for top-level PC gaming or using your HDTV as a PC monitor.

### Invest in Quality Construction for Reliable Performance

You're expecting this 8K cable to last a long time, which is why it has been constructed with high-quality materials, such as a rugged PVC jacket. Contacts and connectors are gold-plated to resist corrosion. The male connectors latch securely to help prevent the cable from becoming accidentally disconnected and disrupting a continuous audio/video signal. Double shielding reduces line noise (EMI/RFI) that can disrupt signals traveling through the DisplayPort cord.

## Specifications

| OVERVIEW     |               |
|--------------|---------------|
| UPC Code     | 037332254122  |
| Product Type | Passive Cable |
| Technology   | DisplayPort   |

## Highlights

- Supports UHD resolutions up to 8K @ 60 Hz (4:4:4) for state-of-the-art video quality
- Carries High Dynamic Range (HDR) signals for rich contrast and expanded color accuracy
- Complies with HDCP 2.2 standards to display up-to-date 4K video content
- Plug-and-play operation with no software required for easy, immediate installation

## System Requirements

Both source and display devices must be compatible with 8K standards to watch 8K video

## Package Includes

P580-009-8K6 DisplayPort 1.4 Cable (M/M), 8K 60 Hz, 9 ft. (2.7 m)



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                 |                         |
|---------------------------------|-------------------------|
| Cable Type                      | Passive                 |
| <b>VIDEO</b>                    |                         |
| Max Supported Video Resolution  | 7680 x 4320 (8K) @ 60Hz |
| Max Supported Color Depth       | 24-bit True Color       |
| HDR Support                     | Yes                     |
| 3D Video Supported              | Yes                     |
| Chroma Sub Sampling             | 4:4:4                   |
| EDID Support                    | Yes                     |
| Signal Transmission             | Bidirectional           |
| <b>INPUT</b>                    |                         |
| Bus Powered                     | Yes                     |
| <b>CONNECTIONS</b>              |                         |
| Side A - Connector 1            | DISPLAYPORT (MALE)      |
| Side B - Connector 1            | DISPLAYPORT (MALE)      |
| Connector Plating               | Gold                    |
| Contact Plating                 | Gold                    |
| Connector Style                 | Straight                |
| Latching or Gripping Connector  | No                      |
| <b>PHYSICAL</b>                 |                         |
| Color                           | Black                   |
| Material of Construction        | PVC                     |
| Cable Jacket Color              | Black                   |
| Connector Color                 | Blue                    |
| Cable Jacket Material           | PVC                     |
| Cable Jacket Rating             | VW-1                    |
| Cable Outer Diameter (OD)       | 6.8MM                   |
| Wire Gauge (AWG)                | 30                      |
| Cable Length (ft.)              | 9                       |
| Cable Length (m)                | 2.74                    |
| Cable Length (in.)              | 108                     |
| Ferrite Core                    | No                      |
| Shipping Dimensions (hwd / in.) | 9.50 x 7.00 x 0.75      |
| Shipping Weight (kg)            | 0.18                    |



Powering Business Worldwide

TRIPP LITE  
SERIES

|  |                              |
|--|------------------------------|
| Unit Dimensions (hwd / in.)                  | 9.500 x 7.000 x 0.750        |
| <b>ENVIRONMENTAL</b>                         |                              |
| Operating Temperature Range                  | 14 to 122 F (-10 to 50 C)    |
| Storage Temperature Range                    | 5 to 140 F (-15 to 60 C)     |
| Operating Humidity Range                     | 0% TO 90% RH, NON-CONDENSING |
| Storage Humidity Range                       | 0% TO 90% RH, NON-CONDENSING |
| <b>COMMUNICATIONS</b>                        |                              |
| EDID Compatible                              | Yes                          |
| Consumer Electronics Control (CEC) Supported | Yes                          |
| <b>FEATURES &amp; SPECIFICATIONS</b>         |                              |
| EMI/RFI Line Noise Protection                | No                           |
| Integrated/Removable Cable                   | No                           |
| MST Support                                  | No                           |
| Antibacterial                                | No                           |
| IP68 Rated                                   | No                           |
| IP20 Rated                                   | No                           |
| Fully Molded Connector Ends                  | No                           |
| Ohms   | No                           |
| Integral Strain Relief                       | No                           |
| Impedance-Matched Twisted-Pair Construction  | No                           |
| Scaler Function                              | No                           |
| IP67 Rated                                   | No                           |
| Displayport Specification                    | 1.4                          |
| HDCP Specification                           | 2.2                          |
| DIN Mountable                                | No                           |
| <b>STANDARDS &amp; COMPLIANCE</b>            |                              |
| Product Certifications                       | IEC/EN 62040                 |
| Product Compliance                           | RoHS; CE (Europe); REACH     |
| <b>WARRANTY &amp; SUPPORT</b>                |                              |
| Product Warranty Period (Worldwide)          | Lifetime limited warranty    |



*Powering Business Worldwide*

TRIPP LITE  
SERIES

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.